

TANGO ST DUO 221, Cappuccinatore device



**Ref: 602612
(UTANGOST2)**

Super Automatic Espresso Machine

- 2 Groups
- 2 Grinders
- Cappuccinator - Teflon Steam - Std Hot Water
- 380-415V 3N 50/60~Hz
- CE/CB Certified
- Inox

General Features

The Tango® ST delivers exceptional coffee quality with the patented Tango® Dual Infusion Chamber, engineered for high performance and precision. Ideal for busy environments like cafes, bars, and hospitality venues, this super-automatic machine offer unparalleled reliability and consistency, creating outstanding espresso every time. With intuitive controls and robust features, the Tango® ST makes exceptional coffee accessible for both barista and self-service settings.

TANGO ST DUO 221, Cappuccinatore device

Main Features

- 2 coffee grinders (2 x 1,7 kg coffee hoppers).
- 1 x Cappuccinatore device with double feature L: for hot milk and C: for foam by air injection.
- 2 groups full-automatic machine
- 2 x 6.5 liter steam/coffee boiler.
- Auto cleaning program.
- Programmable water and steam.
- The machine is able to create and compose a choice of 96 drinks menu and delivers 4 drinks simultaneously: the Tango® ST Duo is the unique machine of the automatic machines market offering such level of performance with the warranty of an exceptional extraction quality.
- The super automatic coffee machine Tango® ST Duo has two separate 7" screens to control the patented TANGO® double group head with its international recognized reliability.
- With a minimum 60cm width for a 2 groups super automatic coffee machine, the Tango® ST Duo is the ideal unit for businesses aiming to automatically transform coffee and fresh milk into a variety of espresso coffee beverages.
- Delivery Capacity:
Espresso 40ml: 440 cups/h
Lungo 100ml: 300 cups/h
Hot Water: 56 L/h
Cappuccino 100ml: 240 cups/h
Latte 100ml: 180 cups/h
- To obtain milk based beverages, the side milk refrigerator is needed.

Construction

- LCD Touchscreen.
- LED lights on body.
- PID (proportional-integral-derivative) Temperature control: a precise controller algorithm system that gives consistency and accuracy to brewing temperature management system.

Optional Accessories

- | | | |
|--|------------|--------------------------|
| • Mixed hot water outlet for TANGO ST1 and STP | PNC 871020 | ☐ |
| • TANGO hotel/breakfast service kit | PNC 871022 | ☐ |
| • Coffee ground direct discharge chute | PNC 871023 | ☐ |

TANGO ST DUO 221, Cappuccinatore device

Electric

Supply voltage: 400 V/3N ph/50 Hz

Electrical power, max: 5.2 kW

Plug type: Cable without plug

Water:

Cold water temperature
(min/max): 5 / 60 °C

Key Information:

Net weight: 130 kg

Shipping volume: 0.69 m³

Sustainability

Current consumption: 7.5 Amps

Certifications



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.


2025.11.25

Part of




Electrolux
Professional
Group


Front



Side



Top



UNIC