

# Rapido Blast Chiller-Freezer 10GN2/1 100/70 kg

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



**110549 (ZBFA12E)**

Rapido blast chiller freezer  
100/70kg, 10 GN 2/1 or  
600x400mm (29 levels pitch  
30mm) with touch screen  
control

## Short Form Specification

### Item No.

- Blast chiller freezer with high resolution full touch screen interface, multilanguage
- For 10 GN 2/1 or 600x400 mm trays. Up to 36 ice cream basins of 5 kg (165x360x125h mm)
- Load capacity: chilling 100 kg; freezing 70 kg
- AirFlow air distribution system to achieve maximum performance with 7 fan speed levels
- Chilling/Freezing modes: Automatic (10 food families with 100+ different pre-installed variants); Programs (a maximum 1000 programs can be stored and organized in 16 different categories); Manual (soft chilling, hard chilling, freezing, holding, turbo cooling and lite hot cycles); Special Cycles (Cruise chilling, proving, retarded proving, fast thawing, Sushi&Sashimi, Sous-Vide chilling, ice-cream, yogurt and chocolate)
- Special functions: MultiTimer chilling/freezing, Make-it-Mine to customize interface, Match connection to Magistar Combi Ovens, SoloMio to customize homepage, agenda Calendar
- Remaining time estimation for probe-driven cycles based on artificial intelligence techniques (ARTE 2.0)
- Automatic and manual defrosting and drying
- USB port to download HACCP data, programs and settings. Connectivity ready
- 3-point multi sensor core temperature probe
- Stainless steel construction throughout
- Internal rounded corners
- Built-in refrigeration unit
- R452a refrigerant gas
- Performance guaranteed at ambient temperatures of +43°C (Climatic class 5).

## Main Features

- Blast Chilling cycle: 100 kg from +90°C up to + 3°C in less than 90 minutes.
  - X-Freeze cycle (+10°C to -41°C): ideal for blast freezing all kinds of food (raw, half or fully cooked).
  - Lite-Hot cycle (+40°C to -18°C): ideal for soft heating preparations.
  - Turbo cooling: chiller works continuously at the desired temperature; ideal for continuous production.
  - Automatic mode including 10 food families (meat, poultry, fish, sauces and soup, vegetables, pasta/rice, bread, savory and sweet bakery, dessert, beverage fast cooling) with 100+ different pre-installed variants. Through Automatic Sensing Phase the blast chiller optimizes the chilling process according to size, quantity and type of food loaded to achieve the selected result. Real time overview of the chilling parameters. Possibility to personalize and save up to 70 variants per family.
  - Programs mode: a maximum of 1000 programs can be stored in the blast chiller's memory, to recreate the exact same high standard at any time. The programs can be grouped in 16 different categories to better organize the menu. 16-step chilling programs also available.
  - MultiTimer function to manage up to 20 different chilling cycles at the same time, improving flexibility and ensuring excellent results. Can be saved up to 200 MultiTimer programs.
  - Fan with 7 speed levels. Fan stops in less than 5 seconds when door is opened.
  - 3-point multi sensor core temperature probe for high precision and food safety.
  - Remaining time estimation for probe-driven cycles based on artificial intelligence techniques (ARTE 2.0 Patented US7971450B2 and related family) for an easier planning of the activities.
  - Customizable pre-cooling and pre-heating functions.
  - Automatic and manual defrosting and drying.
  - Performance guaranteed at ambient temperatures of +43°C (Climatic class 5).
  - Special Cycles: - Cruise Cycle (Patented EP1716769B1 and related family) automatically sets the parameters for the quickest and best chilling (it works with probe) - Proving - Retarded Proving - Fast Thawing - Sushi&Sashimi (anisakis-free food) - Chill Sous-vide - Ice Cream - Yogurt - Chocolate
  - AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
  - [NOT TRANSLATED]
  - [NOT TRANSLATED]
- ## Construction
- Built-in refrigeration unit.
  - Solenoid valve to automatically manage the gas pressure in the thermodynamic circuit.
  - Main components in 304 AISI stainless steel.
  - Evaporator with antitrust protection.

### APPROVAL:

- Motors and fan waterproof protected IP54.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- Removable magnetic gasket door with hygienic design.
- Ventilator swinging hinged panel for access to the evaporator for cleaning.
- Door stopper to keep the door open in order to avoid the formation of bad smells.
- Automatic heated door frame.

## User Interface & Data Management

- High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.
- Pictures upload for full customization of cycles.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- USB port to download HACCP data, share chilling programs and configurations.
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.
- Calendar works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- SoloMio lets the user group the favorite functions in the homepage for immediate access.
- With Match function the Oven and the Blast Chiller are connected to each other and communicate in order to guide the user through the cook&chill process optimizing time and efficiency (requires optional accessory).

## Sustainability

- Holding at +3 °C for chilling or -22 °C for freezing, automatically activated at the end of each cycle, to save energy and maintain the target temperature (manual activation is also possible).
- Zero Waste provides chefs with useful tips for minimizing food waste.  
Zero Waste is a library of Automatic recipes that aims to:
  - give a second life to raw food close to expiration date (e.g.: from milk to yogurt)
  - obtain genuine and tasty dishes from overripe fruit/vegetables (usually considered not appropriate for sale)
  - promote the use of typically discarded food items (e.g.: carrot peels).


## Included Accessories

- 1 of 3-sensor probe for blast chiller freezer PNC 880582


## Optional Accessories

- Bakery/pastry rilsan grid for blast chiller, lengthwise (600x400mm) PNC 880294
- Slide-in rack support for 10 GN 2/1 blast chiller freezer PNC 880563
- 6-sensor probe for blast chiller freezer PNC 880566
- Kit of 3 single sensor probes for blast chiller/freezers PNC 880567
- 3-sensor probe for blast chiller freezer PNC 880582
- 5 stainless steel runners for 10 GN 2/1 blast chiller freezer PNC 880588
- Flanged feet for blast chiller freezer PNC 880589
- 6 WHEELS FOR 10 GN 2/1 BLAST CHILLER FREEZER PNC 881285
- Pair of AISI 304 stainless steel grids, GN 1/1 PNC 922017
- AISI 304 stainless steel grid, GN 1/1 PNC 922062
- AISI 304 stainless steel grid, GN 2/1 PNC 922076
- Pair of AISI 304 stainless steel grids, GN 2/1 PNC 922175
- AISI 304 stainless steel bakery/pastry grid 400x600mm PNC 922264
- Tray rack with wheels 10 GN 2/1, 65mm pitch (std) PNC 922603
- Tray rack with wheels, 8 GN 2/1, 80mm pitch PNC 922604
- Bakery/pastry tray rack with wheels 400x600mm for 10 GN 2/1 oven and blast chiller freezer, 80mm pitch (8 runners) PNC 922609
- Trolley for slide-in rack for 6 & 10 GN 2/1 oven and blast chiller freezer PNC 922627
- Banquet rack with wheels holding 51 plates for 10 GN 2/1 oven and blast chiller freezer, 75mm pitch PNC 922650
- Probe holder for liquids PNC 922714

**Front**




**Side**



**D** = Drain  
**EI** = Electrical inlet (power)

**Top**



**Electric**

**Supply voltage:**  
110549 (ZBFA12E) 380-415 V/3N ph/50 Hz  
**Electrical power max.:** 5.5 kW  
**Heating power:** 1.9 kW  
Circuit breaker required

**Water:**

**Drain line size:** 1"1/2  
**Pressure, bar min:** 0

**Installation:**

**Clearance:** 5 cm on sides and back.  
Please see and follow detailed installation instructions provided with the unit

**Capacity:**

**Max load capacity:** 100 kg  
**Number and type of grids:** 10 (GN 2/1; 600x800)  
**Number and type of basins:** 21 (360x250x80h)

**Key Information:**

[NOT TRANSLATED] Left  
**External dimensions, Width:** 1250 mm  
**External dimensions, Depth:** 1092 mm  
**External dimensions, Height:** 1730 mm  
**Net weight:** 320 kg  
**Shipping weight:** 327 kg  
**Shipping volume:** 2.92 m<sup>3</sup>

**Refrigeration Data**

Built-in Compressor and Refrigeration Unit  
**Refrigeration power at evaporation temperature:** -20 °C  
[NOT TRANSLATED] AIR

**Product Information (EN17032 – Commission Regulation EU 2015/1095)**

**Chilling Cycle Time (+65°C to +10°C):** 95 min  
**Full load capacity (chilling):** 100 kg  
**Freezing Cycle Time (+65°C to -18°C):** 247 min  
**Full load capacity (freezing):** 70 kg

Test performed in a test room at 30°C to chill/ freeze (+10°C/-18°C) a full load of 40mm deep trays filled with mashed potatoes evenly distributed up to a height of 35 mm at starting temperature between 65° and 80°C within 120/270min.

**Sustainability**

**Refrigerant type:** R452A  
**GWP Index:** 2141  
**Refrigeration power:** 6790 W  
**Refrigerant weight:** 3000 g  
**Energy consumption, cycle (chilling):** 0.0708 kWh/kg  
**Energy consumption, cycle (freezing):** 0.2016 kWh/kg  
**Water consumption:** 0 lt/hr