

Modular Cooking Range Line EVO700 4 Drawer Refrigerated Base (R290)

ITEM #		
MODEL #		
NAME #		
SIS #		
AIA #		



372295 (Z7TTBECOMIN)

Refrigerated base with 4 drawers - R290

Short Form Specification

Item No.

Refrigerated base with 4 drawers. Built-in refrigerator compressor unit. Operating temperature range from -2°C to 10° C. To be installed below EVO700 top units. To be delivered with 50 mm height adjustable feet. Exterior panels in stainless steel with Scotch Brite finish. Suitable to operate with ambient temperature up to +43°C. Constructed to allow flush-fitting junction between units.

Main Features

- Unit can be easily installed below other 700 line top models.
- Adjustable temperature range from -2 °C to +10 °C to suit meat, fish and dairy storage requirements.
- Anti-tilt runners accept GN 1/1 containers.
- Forced air circulation for rapid cooling and an even temperature distribution.
- Right angled side edges eliminate gaps and possible dirt traps between units.
- Defrosting and automatic evaporation of condense drain: the condense is automatically evaporated thanks to the electric resistance in the condense drain container.
- GN compliant.
- Designed for modular installation into the cooking block.

Construction

- Exterior panels in Stainless steel with Scotch Brite finish to meet the highest hygiene standards.
- Built-in compressor to suit operating conditions.
- · Access to all components from the front.
- Unit delivered with 150 mm height adjustable feet in Stainless steel. Feet can be extended up to 250 mm.

Sustainability

 CFC and HCFC free (highly ecological refrigerant type: R290).


Optional Accessories


Flanged feet kit	PNC 206136	
 Frontal kicking strip for concrete installation, 1200 mm 	PNC 206151	
 Frontal kicking strip, 1200 mm 	PNC 206178	
• 4 feet for concrete installation (not for 900 line freestanding grill)	PNC 206210	
 2 panels for service duct (single installation) 	PNC 206248	
 Pair of side kicking strips 	PNC 206249	
 Pair of side kicking strips (concrete installation) 	PNC 206265	
 2 side covering panels, height 700 mm, depth 700 mm 	PNC 206319	
• 2 drawers for refrigerated base	PNC 206348	
 Base support for feet or wheels - 800mm (EV0700/900) 	PNC 206367	
 Base support for feet or wheels - 1200mm (EV0700/EV0900) 	PNC 206368	
 Base support for feet or wheels - 1600mm (EV0700/900) 	PNC 206369	
BASE SUPP. FOR FEET/WHEELS LATERAL 700	PNC 206371	
 Rear paneling - 1200mm (EV0700/900) 	PNC 206376	
• Kit 6 wheels - 3 swivelling with brake	PNC 206432	

APPROVAL:




Modular Cooking Range Line EVO700 4 Drawer Refrigerated Base (R290)





El = Electrical inlet (power)



Electric

Supply voltage: 230 V/1N ph/50 Hz

0.4 kW Electrical power max.: **Total Watts:** 0.4 kW Plug type: CE-SCHUKO

Key Information:

External dimensions, Width: 1200 mm **External dimensions, Depth:** 700 mm **External dimensions, Height:** 600 mm Net weight: 95 kg Shipping weight: 114 kg Shipping height: 820 mm Shipping width: 1300 mm Shipping depth: 800 mm Shipping volume: 0.85 m³ **Gross capacity:** 120 lt

Sustainability

Refrigerant type: R290 Refrigerant weight: 85 g











