

Modular Cooking Range Line EVO700 2-Hot Plates Electric Boiling Top Range

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____

**372014 (Z7ECED2R00)**2-hot plate (2,6 kW each)
electric boiling top**372126 (Z7ECED2R0N)**2-hot plate (2,6 kW each)
electric boiling top

Short Form Specification

Item No. _____

To be installed on open base installations, bridging supports or cantilever systems. Two 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The two 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Suitable for countertop installation.

Construction

- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- External panel in Stainless Steel with Scotch Brite finish.

APPROVAL: _____


Optional Accessories

- | | | |
|--|------------|--------------------------|
| • Junction sealing kit (only for 372014) | PNC 206086 | ☐ |
| • Support for bridge type installation, 800 mm (only for 372014) | PNC 206137 | ☐ |
| • Support for bridge type installation, 1000 mm (only for 372014) | PNC 206138 | ☐ |
| • Support for bridge type installation, 1200 mm (only for 372014) | PNC 206139 | ☐ |
| • Support for bridge type installation, 1400 mm (only for 372014) | PNC 206140 | ☐ |
| • Support for bridge type installation, 1600 mm (only for 372014) | PNC 206141 | ☐ |
| • Support for bridge type installation, 400 mm (only for 372014) | PNC 206154 | ☐ |
| • Frontal handrail 400 mm (only for 372014) | PNC 206166 | ☐ |
| • Frontal handrail 800 mm (only for 372014) | PNC 206167 | ☐ |
| • Large handrail (portioning shelf) 400 mm (only for 372014) | PNC 206185 | ☐ |
| • Large handrail (portioning shelf) 800 mm (only for 372014) | PNC 206186 | ☐ |
| • Frontal handrail 1200 mm (only for 372014) | PNC 206191 | ☐ |
| • Frontal handrail 1600 mm (only for 372014) | PNC 206192 | ☐ |
| • Right and left side handrails (only for 372014) | PNC 206240 | ☐ |
| • Water column with swivel arm (water column extension not included) (only for 372014) | PNC 206289 | ☐ |
| • Water column extension (only for 372014) | PNC 206291 | ☐ |
| • Chimney upstand, 400 mm (only for 372014) | PNC 206303 | ☐ |
| • 2 side covering panels, height 250 mm, depth 700 mm (only for 372014) | PNC 206320 | ☐ |
| • Chimney grid net, 400mm (only for 372014) | PNC 206400 | ☐ |


Modular Cooking Range Line

EVO700 2-Hot Plates Electric Boiling Top Range

Front




Side



EI = Electrical inlet (power)
 EQ = Equipotential screw

Top



Electric

Supply voltage:

372014 (Z7ECED2R00)

380-400 V/3 ph/50-60 Hz

372126 (Z7ECED2R0N)

230 V/3 ph/50/60 Hz

Predisposed for:

Total Watts:

5.2 kW

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Net weight:

20 kg

Shipping weight:

372014 (Z7ECED2R00)

23.8 kg

372126 (Z7ECED2R0N)

23 kg

Shipping height:

372014 (Z7ECED2R00)

550 mm

372126 (Z7ECED2R0N)

540 mm

Shipping width:

460 mm

Shipping depth:

820 mm

Shipping volume:

372014 (Z7ECED2R00)

0.21 m³

372126 (Z7ECED2R0N)

0.2 m³

[NOT TRANSLATED]

372014 (Z7ECED2R00)

EH72T

372126 (Z7ECED2R0N)

N7CE1

Front Plates Power:

2.6 - 0 kW

Back Plates Power:

2.6 - kW

Front Plates dimensions:

Ø 230

Back Plates dimensions:

Ø 230