

Modular Cooking Range Line EVO700 4-Hot Plates Electric Boiling Top Range

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



372015 (Z7ECEH4R00) 4-hot plate (2,6 kW each)
electric boiling top

372127 (Z7ECEH4R0N) 4-hot plate (2,6 kW each)
electric boiling top

Short Form Specification

Item No. _____

To be installed on open base installations, bridging supports or cantilever systems. Four 2.6 kW cast-iron hot plates hermetically sealed to the one-piece top. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The four 2.6kW cast-iron plates are hermetically sealed to the one-piece top.
- The special design of the control knob system guarantees against water infiltration.
- IPx4 water protection.
- Suitable for countertop installation.


Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

APPROVAL: _____

Optional Accessories

- Junction sealing kit (only for 372015) PNC 206086
- Support for bridge type installation, 800 mm (only for 372015) PNC 206137
- Support for bridge type installation, 1000 mm (only for 372015) PNC 206138
- Support for bridge type installation, 1200 mm (only for 372015) PNC 206139
- Support for bridge type installation, 1400 mm (only for 372015) PNC 206140
- Support for bridge type installation, 1600 mm (only for 372015) PNC 206141
- Frontal handrail 800 mm (only for 372015) PNC 206167
- Large handrail (portioning shelf) 800 mm (only for 372015) PNC 206186
- Frontal handrail 1200 mm (only for 372015) PNC 206191
- Frontal handrail 1600 mm (only for 372015) PNC 206192
- Right and left side handrails (only for 372015) PNC 206240
- Water column with swivel arm (water column extension not included) (only for 372015) PNC 206289
- Water column extension (only for 372015) PNC 206291
- Chimney upstand, 800 mm (only for 372015) PNC 206304
- 2 side covering panels, height 250 mm, depth 700 mm (only for 372015) PNC 206320
- Chimney grid net, 400mm (only for 372015) PNC 206400



Electric

Supply voltage:

372015 (Z7ECEH4R00)	380-400 V/3 ph/50-60 Hz
372127 (Z7ECEH4RON)	230 V/3 ph/50/60 Hz

Predisposed for:

Total Watts:	10.4 kW
---------------------	---------

Key Information:

Net weight:	40 kg
Shipping weight:	38 kg
Shipping height:	
372015 (Z7ECEH4R00)	530 mm
372127 (Z7ECEH4RON)	540 mm
Shipping width:	820 mm
Shipping depth:	860 mm
Shipping volume:	
372015 (Z7ECEH4R00)	0.37 m ³
372127 (Z7ECEH4RON)	0.38 m ³

[NOT TRANSLATED]

372015 (Z7ECEH4R00)	EH74T
372127 (Z7ECEH4RON)	N7CE1

Front Plates Power: 2.6 - 2.6 kW

Back Plates Power: 2.6 - 2.6 kW

Front Plates dimensions: Ø 230 Ø 230

Back Plates dimensions: Ø 230 Ø 230

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.