

Modular Cooking Range Line EVO700 4-Burner Gas Range on Electric Oven, 800mm

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____

**372149 (Z7GCGH4CEA)**4-burner (5,5 kW each) gas
range on electric oven (6 kW)
- (AGA)

Short Form Specification

Item No. _____

To be installed on stainless steel feet with height adjustment up to 50 mm. High efficiency flower flame burners with flame regulator and protected pilot light. Flame failure device as standard on burners to protect against accidental extinguishing. Stainless steel oven chamber with 3 levels of runners to accommodate 2/1 GN shelves (2 steam pans). Ribbed oven base plate. Exterior panels in stainless steel with Scotch Brite finish. Pan supports in heavy duty cast iron. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to have stainless steel feet with height adjustment up to 50 mm.
- The four 5.5 kW high efficiency flower flame burners allow the flame to adapt to different size pans.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Pan supports in cast iron are washable in a dishwasher.
- Burners to feature flame regulator.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of an electric standard oven positioned beneath the base plate. Stainless steel oven chamber to have 3 levels of runners to accommodate 2/1 GN shelves (2 steam pans) and ribbed enamelled steel base plate.
- Oven thermostat adjustable from 140 °C to 300 °C.
- Double skinned door with pressed internal panel for heat insulation.
- IPx4 water protection.

Construction



- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

APPROVAL: _____

Optional Accessories


• Junction sealing kit	PNC 206086	☐	• Base support for feet or wheels - 1600mm (EVO700/900)	PNC 206369	☐
• Draught diverter, 150 mm diameter	PNC 206132	☐	• Rear paneling - 800mm (EVO700/900)	PNC 206374	☐
• Matching ring for flue condenser, 150 mm diameter	PNC 206133	☐	• Rear paneling - 1000mm (EVO700/900)	PNC 206375	☐
• 4 wheels, 2 swivelling with brake (EVO700/900). It is mandatory to install with base supports for feet/wheels.	PNC 206135	☐	• Rear paneling - 1200mm (EVO700/900)	PNC 206376	☐
• Flanged feet kit	PNC 206136	☐	• Chimney grid net, 500mm	PNC 206402	☐
• Frontal kicking strip for concrete installation, 800 mm	PNC 206148	☐			
• Frontal kicking strip for concrete installation, 1000 mm	PNC 206150	☐			
• Frontal kicking strip for concrete installation, 1200 mm	PNC 206151	☐			
• Frontal kicking strip for concrete installation, 1600 mm	PNC 206152	☐			
• Frontal handrail 800 mm	PNC 206167	☐			
• Frontal kicking strip, 800 mm	PNC 206176	☐			
• Frontal kicking strip, 1000 mm	PNC 206177	☐			
• Frontal kicking strip, 1200 mm	PNC 206178	☐			
• Frontal kicking strip, 1600 mm	PNC 206179	☐			
• Large handrail (portioning shelf) 800 mm	PNC 206186	☐			
• Frontal handrail 1200 mm	PNC 206191	☐			
• Frontal handrail 1600 mm	PNC 206192	☐			
• 4 feet for concrete installation (not for 900 line freestanding grill)	PNC 206210	☐			
• Right and left side handrails	PNC 206240	☐			
• Flue condenser for 1 module, 150 mm diameter	PNC 206246	☐			
• Pair of side kicking strips	PNC 206249	☐			
• Single burner smooth plate for direct cooking - fits frontal burners only	PNC 206260	☐			
• Single burner ribbed plate for direct cooking- fits frontal burners only	PNC 206261	☐			
• Single burner radiant plate for pan support	PNC 206264	☐			
• Pair of side kicking strips (concrete installation)	PNC 206265	☐			
• Water column with swivel arm (water column extension not included)	PNC 206289	☐			
• Water column extension	PNC 206291	☐			
• Stainless steel grid for 2 burners	PNC 206297	☐			
• Chimney upstand, 800 mm	PNC 206304	☐			
• 2 side covering panels, height 700 mm, depth 700 mm	PNC 206319	☐			
• Wok pan support for open burners (EVO700/900)	PNC 206363	☐			
• Base support for feet or wheels - 800mm (EVO700/900)	PNC 206367	☐			
• Base support for feet or wheels - 1200mm (EVO700/EVO900)	PNC 206368	☐			

Modular Cooking Range Line EVO700 4-Burner Gas Range on Electric Oven, 800mm

Front

Side


EI = Electrical inlet (power)

G = Gas connection

Top


Electric

Supply voltage: 380-400 V/3N ph/50/60 Hz

Gas

Gas Power: 22 kW
Standard gas delivery: Natural Gas G20 (20mbar)
Gas Type Option: LPG;Town
Gas Inlet: 1/2"
Gas Power Option: Btu/hr (0 kW)

Key Information:

Oven working Temperature: 140 °C MIN; 300 °C MAX
Oven Cavity Dimensions (width): 540 mm
Oven Cavity Dimensions (height): 300 mm
Oven Cavity Dimensions (depth): 650 mm
External dimensions, Width: 800 mm
External dimensions, Depth: 700 mm
External dimensions, Height: 850 mm
Net weight: 80 kg
Front Burners Power: 5.5 - 5.5 kW
Back Burners Power: 5.5 - 5.5 kW
[NOT TRANSLATED] N7CG
Back Burners Dimension - mm Ø 60 Ø 60
Front Burners Dimension - mm Ø 60 Ø 60