

Modular Cooking Range Line EV0900 6-Burner Gas Range 10kW on Gas Oven with Cupboard

| ITEM # | |
|---------|---|
| MODEL # | |
| NAME # | |
| | |
| SIS # | _ |
| AIA # | |



392263 (Z9GCGLTC1B)

6-burner (10 kW each) gas range on gas oven (8,5 kW) and cupbboard base (AGA)

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty stainless steel. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.
- The six 10 kW high efficiency burners are available in two different sizes to suit high performing cooking requirements of the most demanding customers:
- -60 mm burners with continuous power regulation from 1.5 to 6 kW
- -100 mm burners with continuous power regulation from 2.2 kW to 10 kW
- Cupboard compartment for storage of pots, pans, sheet pans etc.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- Base compartment consists of a gas heated standard oven with stainless steel burners and self stabilizing flame positioned beneath the base plate. Oven chamber to have 3 levels of runners to accommodate 2/1 GN shelves (2 steam pans) and ribbed cast iron base plate.
- Oven thermostat adjustable from 120 °C to 280 °C.
- 40 mm thick oven door for heat insulation.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Control knobs provide smooth, continuous rotation from min to max power level.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Pan supports in stainless steel.
- Unit is 900mm deep to give a larger working surface area.

APPROVAL:




Modular Cooking Range Line EVO900 6-Burner Gas Range 10kW on Gas Oven with Cupboard


| l.a | cluded Accessories | | Kit town gas nozzles (G150) for EV0900 gas | PNC 206385 | |
|-----------|---|--------------|---|------------|--|
| | of Door for open base cupboard | PNC 206342 | ranges on gas oven • Chimney grid net, 400mm | PNC 206400 | |
| | · | 1110 2000 12 | Pressure regulator for gas units | PNC 927225 | |
| - | ptional Accessories | DNO 404050 | Ç Ç | | |
| | GN2/1 chrome grid for static oven | PNC 164250 | | | |
| | unction sealing kit | PNC 206086 | | | |
| | Oraught diverter, 150 mm diameter | PNC 206132 | | | |
| d | Natching ring for flue condenser, 150 mm iameter | PNC 206133 | | | |
| () W | wheels, 2 swivelling with brake EVO700/900). It is mandatory to install vith base supports for feet/wheels. | PNC 206135 | | | |
| • F | langed feet kit | PNC 206136 | | | |
| | supports runners for open base 400 mm or GN1/1 | PNC 206145 | | | |
| • F ii | rontal kicking strip for concrete nstallation, 1200 mm | PNC 206151 | | | |
| • F | rontal kicking strip for concrete nstallation, 1600 mm | PNC 206152 | | | |
| | SIDE KICKING STRIPS-CONCRETE NST-900 | PNC 206157 | | | |
| • S | ide handrail for right/left hand | PNC 206165 | | | |
| • S | Single burner smooth plate for direct ooking - fits frontal burners only | PNC 206171 | | | |
| • S | Single burner ribbed plate for direct ooking - fits frontal burners only | PNC 206172 | | | |
| • F | rontal kicking strip, 1200 mm | PNC 206178 | | | |
| • F | rontal kicking strip, 1600 mm | PNC 206179 | | | |
| • P | Pair of side kicking strips | PNC 206180 | | | |
| | panels for service duct (single nstallation) | PNC 206181 | | | |
| • F | rontal handrail 1200 mm | PNC 206191 | | | |
| • F | rontal handrail 1600 mm | PNC 206192 | | | |
| | panels for service duct (back to back nstallation) | PNC 206202 | | | |
| | feet for concrete installation (not for 900 ne freestanding grill) | PNC 206210 | | | |
| | lue condenser for 1 module, 150 mm liameter | PNC 206246 | | | |
| • E | lectric heating kit for cupboards | PNC 206259 | | | |
| • V | Vater column with swivel arm (water olumn extension not included) | PNC 206289 | | | |
| • V | Vater column extension | PNC 206290 | | | |
| • S | stainless steel grid for 2 burners | PNC 206298 | | | |
| • 0 | chimney upstand, 1200 mm | PNC 206306 | | | |
| d | side covering panels, height 700 mm, lepth 900 mm | PNC 206335 | | | |
| | oor for open base cupboard | PNC 206342 | | | |
| | drawers for open base, height 100 mm | PNC 206361 | | | |
| (| Vok pan support for open burners EVO700/900) | PNC 206363 | | | |
| (| Base support for feet or wheels - 1200mm EVO700/EVO900) | PNC 206368 | | | |
| (| Base support for feet or wheels - 1600mm EVO700/900) | PNC 206369 | | | |
| (| Base support for feet or wheels - 2000mm EVO700/900) | PNC 206370 | | | |
| • F | Rear paneling - 1200mm (EV0700/900) | PNC 206376 | | | |






Modular Cooking Range Line EVO900 6-Burner Gas Range 10kW on Gas Oven with Cupboard





Gas connection



Gas

Natural gas - Pressure:

392263 (Z9GCGLTC1B) 7" w.c. (17.4 mbar)

Gas Power:68.5 kWStandard gas delivery:Natural GasGas Type Option:LPG;Natural Gas

Gas Inlet: 1/2"

Key Information:

Oven working Temperature: 120 °C MIN; 280 °C MAX

Oven Cavity Dimensions (width): 575 mm Oven Cavity Dimensions (height): 300 mm Oven Cavity Dimensions (depth): 700 mm Net weight: 203 kg Shipping weight: 156 kg Shipping height: 1040 mm Shipping width: 1300 mm Shipping depth: 1020 mm 1.38 m³ Shipping volume: **Front Burners Power:** 10 - 10 kW **Back Burners Power:** 10 - 10 kW Middle Burners Power: 10 - 0/10 - 0 kW

[NOT TRANSLATED] N9CG
Back Burners Dimension - mm Ø 100 Ø 100

Front Burners Dimension - mm Ø 100 Ø 100

Middle Burners Dimension - mm Ø 100 Ø 100

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.



Modular Cooking Range Line EVO900 6-Burner Gas Range 10kW on Gas Oven with Cupboard