

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



### 218930 (ZCOE61C2S0)

Magistar Combi DI combi boilerless oven with digital control, 6x1/1GN, electric, programmable, automatic cleaning

## **Short Form Specification**

### Item No.

Combi oven with digital interface with guided selection.

- Boilerless steaming function to add and retain moisture.
- AirFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle.
- Automatic backup mode to avoid downtime.
- $\hbox{-}\, {\sf USB}\, {\sf port}\, to\, download\, {\sf HACCP}\, {\sf data}, programs\, {\sf and}\, {\sf settings}.\, {\sf Connectivity}\, {\sf ready}.$
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

### Main Features

- Digital interface with LED backlight buttons with guided selection.
- Boilerless steaming function to add and retain moisture for high quality, consistent cooking results.
- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Grease Collector: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- 2 different chemical options available: solid and liquid (requires optional accessory).
- Capacity: 6 GN 1/1 trays.
- [NOT TRANSLATED]

### Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

### **User Interface & Data Management**

- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).

**APPROVAL:** 



C	Optional Accessories			•	External connection kit for detergent and rinse aid	PNC	922618	
•	Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one)	PNC 922003			Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/ close device and drain)	PNC	922619	
•	Pair of AISI 304 stainless steel grids, GN 1/1	PNC 922017		•	Stacking kit for electric 6+6 GN 1/1 ovens or electric 6+10 GN 1/1 GN ovens	PNC	922620	
•	Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1	PNC 922036		•	Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer	PNC	922626	
	AISI 304 stainless steel grid, GN 1/1	PNC 922062		•	Trolley for mobile rack for 2 stacked 6 GN 1/1 ovens on riser	PNC	922628	
	Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2	PNC 922086		•	Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens	PNC	922630	
•	External side spray unit (needs to be mounted outside and includes support to be mounted on the oven)	PNC 922171		•	Riser on feet for 2 6 GN 1/1 ovens or a 6 GN 1/1 oven on base	PNC	922632	
•	Baking tray for 5 baguettes in perforated aluminum with silicon	PNC 922189			Riser on wheels for stacked 2x6 GN 1/1 ovens, height 250mm		922635	
•	coating, 400x600x38mm  Baking tray with 4 edges in perforated	PNC 922190		•	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC	922636	
•		PNC 922191			Plastic drain kit for 6 &10 GN oven, dia=50mm		922637	
	400x600x20mm	DNIO 000000		•	Trolley with 2 tanks for grease collection		922638	
	Pair of frying baskets AISI 304 stainless steel bakery/pastry	PNC 922239 PNC 922264			Grease collection kit for open base (2 tanks, open/close device and drain)	PNC	922639	
	grid 400x600mm			•	Wall support for 6 GN 1/1 oven	PNC	922643	
•	Double-step door opening kit	PNC 922265		•	Dehydration tray, GN 1/1, H=20mm	PNC	922651	
•	Grid for whole chicken (8 per grid -	PNC 922266		•	Flat dehydration tray, GN 1/1	PNC	922652	
•	1,2kg each), GN 1/1 Grease collection tray, GN 1/1, H=100	PNC 922321		•	Open base for 6 & 10 GN 1/1 oven, disassembled	PNC	922653	
•	mm Kit universal skewer rack and 4 long	PNC 922324			Bakery/pastry rack kit for 6 GN 1/1 oven with 5 racks 400x600mm and 80mm pitch	PNC	922655	
_	skewers for GN 1/1 ovens Universal skewer rack	PNC 922326			Stacking kit for gas 6 GN 1/1 oven placed	PNC	922657	
		PNC 922327			on 7kg and 15kg crosswise blast chiller			
	4 long skewers				freezer	DNC	022660	
•	Smoker for lengthwise and crosswise oven (4 kinds of smoker wood chips are available on request)	PNC 922338			Heat shield for stacked ovens 6 GN 1/1 on 6 GN 1/1 Heat shield for stacked ovens 6 GN 1/1 on			
•	Multipurpose hook	PNC 922348		_	10 GN 1/1		022001	_
	4 flanged feet for 6 & 10 GN , 2",	PNC 922351		•	Heat shield for 6 GN 1/1 oven	PNC	922662	
	100-130mm Grid for whole duck (8 per grid - 1,8kg	PNC 922362			Compatibility kit for installation of 6 GN 1/1 electric oven on previous 6 GN 1/1	_	922679	
	each), GN 1/1				electric oven			
	Tray support for 6 & 10 GN 1/1 disassembled open base	PNC 922382			Fixed tray rack for 6 GN 1/1 and 400x600mm grids	PNC	922684	
•	Wall mounted detergent tank holder	PNC 922386		•	Kit to fix oven to the wall	PNC	922687	
•	USB SINGLE POINT PROBE	PNC 922390		•	4 high adjustable feet for 6 & 10 GN	PNC	922688	
•	Tray rack with wheels, 6 GN 1/1, 65mm pitch (included)	PNC 922600		•	ovens, 100-115MM Tray support for 6 & 10 GN 1/1 open base	PNC	922690	
•	Tray rack with wheels, 5 GN 1/1,	PNC 922606		•	Detergent tank holder for open base	PNC	922699	
•	80mm pitch Bakery/pastry tray rack with wheels	PNC 922607		•	Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base	PNC	922702	
	holding 400x600mm grids for 6 GN 1/1			•	Wheels for stacked ovens	PNC	922704	
	oven and blast chiller freezer, 80mm			•	Mesh grilling grid	PNC	922713	
	pitch (5 runners)	DNC 000040			Probe holder for liquids		922714	
	Slide-in rack with handle for 6 & 10 GN 1/1 oven		_		Odourless hood with fan for 6 & 10 GN 1/1 electric ovens	_	922718	
	Open base with tray support for 6 & 10 GN 1/1 oven			•	Condensation hood with fan for 6 & 10 GN 1/1 electric oven	PNC	922723	
	Cupboard base with tray support for 6 & 10 GN 1/1 oven			•	Exhaust hood with fan for 6 & 10 GN 1/1	PNC	922728	
•	Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or400x600mm	PNC 922615		•	ovens Exhaust hood without fan for 6&10 1/1GN ovens	PNC	922733	















• Fixed tray rack, 5 GN 1/1, 85mm pitch	PNC 922740	
<ul> <li>4 high adjustable feet for 6 &amp; 10 GN ovens, 230-290mm</li> </ul>	PNC 922745	
<ul> <li>Tray for traditional static cooking, H=100mm</li> </ul>	PNC 922746	
<ul> <li>Double-face griddle, one side ribbed and one side smooth, 400x600mm</li> </ul>	PNC 922747	
TROLLEY FOR GREASE COLLECTION KIT	PNC 922752	
Water inlet pressure reducer	PNC 922773	
KIT FOR INSTALLATION OF	PNC 922774	
ELECTRIC POWER PEAK MANAGEMENT SYSTEM-6-10 GN OVENS		
EXTENSION FOR CONDENSATION TUBE	PNC 922776	
<ul> <li>Non-stick universal pan, GN 1/1, H=20mm</li> </ul>	PNC 925000	
<ul> <li>Non-stick universal pan, GN 1/ 1, H=40mm</li> </ul>	PNC 925001	
<ul> <li>Non-stick universal pan, GN 1/1, H=60mm</li> </ul>	PNC 925002	
<ul> <li>Double-face griddle, one side ribbed and one side smooth, GN 1/1</li> </ul>	PNC 925003	
Aluminum grill, GN 1/1	PNC 925004	
<ul> <li>Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1</li> </ul>	PNC 925005	
<ul> <li>Flat baking tray with 2 edges, GN 1/1</li> </ul>	PNC 925006	
<ul> <li>Baking tray for 4 baguettes, GN 1/1</li> </ul>	PNC 925007	
<ul> <li>Potato baker for 28 potatoes, GN 1/1</li> </ul>	PNC 925008	
<ul> <li>Non-stick universal pan, GN 1/2, H=20mm</li> </ul>	PNC 925009	
<ul> <li>Non-stick universal pan, GN 1/2, H=40mm</li> </ul>	PNC 925010	
<ul> <li>Non-stick universal pan, GN 1/2, H=60mm</li> </ul>	PNC 925011	
<ul> <li>Compatibility kit for installation on previous base GN 1/1</li> </ul>	PNC 930217	

















### **Front**



### Side



Cold Water inlet 1 C-WI-


ΕI Electrical inlet (power)

Cold Water Inlet 2

= Drain

Overflow drain pipe

### Top



### **Electric**

**Circuit breaker required** 

Supply voltage: 400-430 V/3N ph/50-60 Hz

Electrical power max.: 11.5 kW Electrical power, default: 11.1 kW

### Water:

Max inlet water supply

30 °C temperature:

Water inlet "FCW"

connection: 3/4" 1-6 bar Pressure, bar min/max: **Chlorides:** <10 ppm **Conductivity:** >50 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

### **Installation:**

Clearance: 5 cm rear and right

775 mm

Clearance: hand sides.

Suggested clearance for service access:

50 cm left hand side.

### Capacity:

GN: 6 (GN 1/1) Max load capacity: 30 kg

### **Key Information:**

**Door hinges:** Right Side

External dimensions,

Width: 867 mm External dimensions,

Depth:

External dimensions,

**Height:** 808 mm Weight: 111.5 kg 111.5 kg Net weight:

**Shipping weight:** 136 kg **Shipping volume:** 0.89 m<sup>3</sup>











