

| ITEM# | |
|---------|--|
| MODEL # | |
| MODEL # | |
| NAME # | |
| SIS# | |
| AIA# | |



218972 (ZCOG101C2U0)

Magistar Combi DI combi boilerless oven with digital control, 10x1/1GN, gas, programmable, automatic cleaning (Australia)

Short Form Specification

Item No.

Combi oven with digital interface with guided selection.

- Boilerless steaming function to add and retain moisture.
- AirFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle.
- Automatic backup mode to avoid downtime.
- $\hbox{-}\, {\sf USB}\, {\sf port}\, to\, download\, {\sf HACCP}\, {\sf data}, programs\, {\sf and}\, {\sf settings}.\, {\sf Connectivity}\, {\sf ready}.$
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Digital interface with LED backlight buttons with guided selection.
- Boilerless steaming function to add and retain moisture for high quality, consistent cooking results.
- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- · Single sensor core temperature probe included.
- · Automatic fast cool down and pre-heat function.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Grease Collector: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- 2 different chemical options available: solid and liquid (requires optional accessory).
- Capacity: 10 GN 1/1 trays.
- [NOT TRANSLATED]

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Seamless hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX 5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

User Interface & Data Management

- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).







| Optional Accessories • Wheel kit for 6 & 10 GN 1/1 and 2/1 | PNC 922003 | Grease collection kit for GN 1/1-2/1 PNC 922619 cupboard base (trolley with 2 tanks, open/close device and drain) | |
|---|--------------------------|---|---|
| GN oven base (not for the disassembled one) | FNC 922003 | Stacking kit for gas 6 GN 1/1 oven placed PNC 922623 on gas 10 GN 1/1 oven | |
| Pair of AISI 304 stainless steel grids, GN 1/1 | PNC 922017 | Trolley for slide-in rack for 6 & 10 GN 1/1 PNC 922626 oven and blast chiller freezer | |
| Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922036 | Trolley for mobile rack for 6 GN 1/1 on 6 PNC 922630 or 10 GN 1/1 ovens | |
| AISI 304 stainless steel grid, GN 1/1 | PNC 922062 | Stainless steel drain kit for 6 & 10 GN PNC 922636 | |
| Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 | PNC 922086 | oven, dia=50mm Plastic drain kit for 6 &10 GN oven, PNC 922637 | |
| External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) | PNC 922171 | dia=50mm Grease collection kit for open base (2 PNC 922639 tanks, open/close device and drain) | |
| Baking tray for 5 baguettes in | PNC 922189 | Wall support for 10 GN 1/1 oven PNC 922645 | |
| perforated aluminum with silicon coating, 400x600x38mm | 1110 022 100 | Banquet rack with wheels holding 30 PNC 922648 plates for 10 GN 1/1 oven and blast chiller | ū |
| Baking tray with 4 edges in perforated aluminum, 400x600x20mm | PNC 922190 | freezer, 65mm pitch Banquet rack with wheels holding 23 PNC 922649 | |
| Baking tray with 4 edges in aluminum, 400x600x20mm | | plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch | |
| Pair of frying baskets | PNC 922239 | Dehydration tray, GN 1/1, H=20mm PNC 922651 | |
| AISI 304 stainless steel bakery/pastry | PNC 922264 | Flat dehydration tray, GN 1/1 PNC 922652 | |
| grid 400x600mm • Double-step door opening kit | PNC 922265 | Open base for 6 & 10 GN 1/1 oven, PNC 922653 disassembled | |
| Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 | PNC 922266 | Bakery/pastry rack kit for 10 GN 1/1 oven PNC 922656 with 8 racks 400x600mm and 80mm pitch | |
| Grease collection tray, GN 1/1, H=100 mm | PNC 922321 | Heat shield for stacked ovens 6 GN 1/1 on PNC 922661 10 GN 1/1 | |
| Kit universal skewer rack and 4 long | PNC 922324 | Heat shield for 10 GN 1/1 oven PNC 922663 | |
| skewers for GN 1/1 ovens | | Kit to convert from natural gas to LPG PNC 922670 | |
| Universal skewer rack | PNC 922326 | Kit to convert from LPG to natural gas PNC 922671 | |
| 4 long skewers | PNC 922327 | Flue condenser for gas oven PNC 922678 | |
| Multipurpose hook | PNC 922348 | Fixed tray rack for 10 GN 1/1 and PNC 922685 | |
| 4 flanged feet for 6 & 10 GN , 2", 100-130mm | PNC 922351 | 400x600mm grids Kit to fix oven to the wall PNC 922687 | |
| each), GN 1/1 | PNC 922362 | 4 high adjustable feet for 6 & 10 GN PNC 922688 ovens, 100-115MM | |
| Thermal cover for 10 GN 1/1 oven and blast chiller freezer | PNC 922364 | Tray support for 6 & 10 GN 1/1 open base PNC 922690 Reinforced tray rack with wheels, lowest PNC 922694 | |
| Tray support for 6 & 10 GN 1/1 disassembled open base | PNC 922382 | support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch | _ |
| Wall mounted detergent tank holder | PNC 922386 | Detergent tank holder for open base PNC 922699 | |
| USB SINGLE POINT PROBETray rack with wheels 10 GN 1/1, | PNC 922390 PNC 922601 | Bakery/pastry runners 400x600mm for 6 & PNC 922702 10 GN 1/1 oven base | |
| 65mm pitch (std) | | Wheels for stacked ovens PNC 922704 | |
| Tray rack with wheels, 8 GN 1/1, 80mm pitch | PNC 922602 | Spit for lamb or suckling pig (up to 12kg) PNC 922709 for GN 1/1 ovens | |
| Bakery/pastry tray rack with wheels | PNC 922608 | Mesh grilling grid PNC 922713 | |
| 400x600mm for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners) | | Probe holder for liquids PNC 922714 Exhaust hood with fan for 6 & 10 GN 1/1 PNC 922728 | |
| Slide-in rack with handle for 6 & 10 GN 1/1 oven | PNC 922610 | ovens Exhaust hood without fan for 6&10 1/1GN PNC 922733 | |
| Open base with tray support for 6 & 10 GN 1/1 oven | PNC 922612 | ovens Fixed tray rack, 8 GN 1/1, 85mm pitch PNC 922741 | |
| Cupboard base with tray support for 6 | PNC 922614 | Fixed tray rack, 8 GN 2/1, 85mm pitch PNC 922742 | |
| & 10 GN 1/1 oven | | 4 high adjustable feet for 6 & 10 GN PNC 922745 | |
| Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or400x600mm | PNC 922615 | ovens, 230-290mm Tray for traditional static cooking, H=100mm PNC 922746 | |
| External connection kit for detergent and rinse aid | PNC 922618 | | |
| | | | |

















| Double-face griddle, one side ribbed and one side smooth, 400x600mm | PNC 922747 | |
|--|------------|--|
| TROLLEY FOR GREASE COLLECTION KIT | PNC 922752 | |
| Water inlet pressure reducer | PNC 922773 | |
| Non-stick universal pan, GN 1/1, H=20mm | PNC 925000 | |
| Non-stick universal pan, GN 1/1, H=40mm | PNC 925001 | |
| Non-stick universal pan, GN 1/1, H=60mm | PNC 925002 | |
| Double-face griddle, one side ribbed and one side smooth, GN 1/1 | PNC 925003 | |
| Aluminum grill, GN 1/1 | PNC 925004 | |
| Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 | PNC 925005 | |
| • Flat baking tray with 2 edges, GN 1/1 | PNC 925006 | |
| Baking tray for 4 baguettes, GN 1/1 | PNC 925007 | |
| Potato baker for 28 potatoes, GN 1/1 | PNC 925008 | |
| Non-stick universal pan, GN 1/2, H=20mm | PNC 925009 | |
| Non-stick universal pan, GN 1/2, H=40mm | PNC 925010 | |
| Non-stick universal pan, GN 1/2, H=60mm | PNC 925011 | |
| Compatibility kit for installation on previous base GN 1/1 | PNC 930217 | |

















Front



Side



Cold Water inlet 1

Electrical inlet (power)

Cold Water Inlet 2


Gas connection

D

= Drain

DO = Overflow drain pipe

Top



Electric

Circuit breaker required

Supply voltage: 230-240 V/1 ph/50 Hz

Electrical power max.: 1.1 kW Electrical power, default: 1.1 kW

Total thermal load: 77725.2 BTU (22.8 kW)

Gas Power: 22.8 kW Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection diameter:

1/2" MNPT

Max inlet water supply

temperature: 30 °C **Chlorides:** <10 ppm >50 µS/cm **Conductivity:** Drain "D": 50mm

Water inlet "FCW"

3/4" connection: Pressure, bar min/max: 1-6 bar

Electrolux Professional recommends the use of treated water, based

on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and right Clearance:

Suggested clearance for

50 cm left hand side. service access:

Capacity:

10 - 1/1 Gastronorm

Max load capacity: 50 kg

Key Information:

Door hinges: Right Side

External dimensions,

Width: 867 mm

External dimensions,

775 mm Depth:

External dimensions,

1058 mm **Height:** Weight: 139 kg Net weight: 139 kg

Shipping weight: 157 kg **Shipping volume:** 1.06 m³









