

### Modular Cooking Range Line EVO700 HP Automatic Electric Pasta Cooker, 1 Well 24.5 litres



## **Short Form Specification**

#### Item No.

Infrared heating system positioned below the well. Constant starch removal during the cooking process. Pressed tank in 316 AISI stainless steel to protect against corrosion. Control panel with energy regulator to regulate working conditions. Height adjustable feet in stainless steel. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

ITEM #		
MODEL #		
NAME #		
<u>SIS #</u>		
AIA #		

#### **Main Features**

- In addition to cooking pasta, the appliance can be used for noodles of every kind, rice, dumplings and vegetables.
- Unit to have infared heating system positioned beneath the base of the well.
- Water basin in 316 type Stainless steel.
- Water basin is seamlessly welded into the top of the appliance.
- Electric pre-heating system built-in to the unit for high thermal efficiency and rapid temperature recovery.
- Electrically-heated 3.5kW water boiler guarantees high thermal efficiency, rapid temperature recovery and a superior production rate.
- Unit to feature skimming zone for starch removal: improved water quality over time.
- Easy-to-use control panel with switch to regulate rapid filling and refilling with pre-heated water.
- Safety thermostat to avoid operation without water.
- Large drain with manual ball-valve for fast emptying of well.
- Automatic lifting system: two stainless steel basket suppots, holding one GN 1/2 basket each, to provide automatic lifting of baskets upon cycle termination. Possibility to program 5 different cooking times per basket in addition to the selection of 4 different boiling cycles, from gentle (home-made fresh pasta) to full power (regular pasta).
- All major compartments located in front of unit for ease of maintenance.
- Unit delivered with four 50 mm legs in stainless steel as standard (all round Stainless steel kick plates as option).

## Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- IPX4 water resistance certification.

**APPROVAL:** 

Part of

Zanussi Professional www.zanussiprofessional.com



#### **Included Accessories**

1 of 2 single portion baskets for automatic PNC 206312
programmable pasta cooker

#### **Optional Accessories**

C	ptional Accessories		
•	Junction sealing kit	PNC 206086	
•	4 wheels, 2 swivelling with brake (EV0700/900). It is mandatory to install	PNC 206135	
	with base supports for feet/wheels.	DNO 000100	
	Flanged feet kit	PNC 206136	
	Frontal handrail 400 mm	PNC 206166	
	Frontal handrail 800 mm	PNC 206167	
	Frontal kicking strip, 400 mm	PNC 206175	
	Frontal kicking strip, 800 mm	PNC 206176	
	Frontal kicking strip, 1000 mm	PNC 206177	
	Frontal kicking strip, 1200 mm	PNC 206178	
	Frontal kicking strip, 1600 mm	PNC 206179	
	Large handrail (portioning shelf) 400 mm	PNC 206185	
	Large handrail (portioning shelf) 800 mm	PNC 206186	
	Frontal handrail 1200 mm	PNC 206191	
	Frontal handrail 1600 mm	PNC 206192	
	4 feet for concrete installation (not for 900 line freestanding grill)	PNC 206210	
	Right and left side handrails	PNC 206240	
	Chimney upstand, 400 mm	PNC 206303	
	2 single portion baskets for automatic programmable pasta cooker	PNC 206312	
•	2 half size baskets 105x350 for automatic programmable pasta cooker	PNC 206314	
•	2 side covering panels, height 700 mm, depth 700 mm	PNC 206319	
	Automatic programmable basket lifting system for 24.5lt pasta cookers, 2 lifters	PNC 206354	
٠	False bottom for 24,5lt pasta cooker basket		
	Base support for feet or wheels - 400mm (EV0700/900)	PNC 206366	
•	Base support for feet or wheels - 800mm (EV0700/900)	PNC 206367	
•	Base support for feet or wheels - 1200mm (EV0700/EV0900)	PNC 206368	
•	Base support for feet or wheels - 1600mm (EV0700/900)	PNC 206369	
	Rear paneling - 600mm (EV0700/900)	PNC 206373	
	Rear paneling - 800mm (EV0700/900)	PNC 206374	
	Rear paneling - 1000mm (EV0700/900)	PNC 206375	
٠	Rear paneling - 1200mm (EV0700/900)	PNC 206376	
•	Base support for feet/wheels (600mm)	PNC 206431	
•	FRONT TRAY FOR AUTOMATIC PASTA COOKER 400MM	PNC 206456	
•	2 BASKETS L+R 105x160x240 FOR PASTA COOKERS	PNC 921020	
	2 BASKETS L+R 105x105x240 FOR PASTA COOKERS	PNC 921021	
	FALSE BOTTOM 230x350x60 FOR PASTA COOKER BASKETS	PNC 921022	
	2 half size baskets 170x220 for 24,5lt pasta cookers	PNC 921610	
•	2 half size baskets 105x350 for pasta cookers for 24,5lt pasta cookers	PNC 921619	



Modular Cooking Range Line EVO700 HP Automatic Electric Pasta Cooker, 1 Well 24.5 litres

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



#### Front 1000 37 1/8 " 943 mm NIEI 10 3/4 9/16 ' 117 mm 274 mm 2 3/16 " 55 mm 11 7/16 ' 2 3/16 55 mm 290 mn Side 27 9/16 1 700 mm 5 3/16 " 132 mm 150 # WI ΕQ D ΕI Ħ 12 9 9/16 305 mm 242 mm 3 9/16 91 mm 20 1/16 " 2 1/4 " 510 mm 57 mm **D** = Drain **EI** = Electrical inlet (power) **EQ** = Equipotential screw WI = Water inlet Тор 15 3/4 ' 400 mm

# 



## Modular Cooking Range Line EVO700 HP Automatic Electric Pasta Cooker, 1 Well 24.5 litres

## Electric

Supply voltage:	
372354 (Z700ADBAMC)	380-400 V/3N ph/50/60 Hz
Electrical power max.:	9 kW
Total Watts:	9 kW
	380-400V 3N~ 50/60Hz
Predisposed for:	8.2-9kW
Water:	

Drain "D":1"Incoming Cold/hot Water line size:3/4"Total hardness:5-50 ppm

It is recommended to use treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

### **Key Information:**

Headda wall dimensions (width)	050
Usable well dimensions (width):	250 mm
Usable well dimensions (height):	300 mm
Usable well dimensions (depth):	400 mm
Well Capacity (MAX):	24.5 It MAX
Net weight:	55 kg
Shipping weight:	70 kg
Shipping height:	1140 mm
Shipping width:	460 mm
Shipping depth:	820 mm
Shipping volume:	0.43 m³

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Modular Cooking Range Line EVO700 HP Automatic Electric Pasta Cooker, 1 Well 24.5 litres

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.