

Modular Cooking Range Line EVO900 Full Module Gas Fry Top, Chromium Plated



Short Form Specification

Item No.

Smooth polished chrome cooking surface 20 kW gas powered burners with thermostatic valve and self stabilizing flame. To be installed on open base installations, bridging supports or cantilever systems. Removable drawer below the cooking surface for the collection of grease and fat. Body and work top of unit entirely in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

ITEM #		
MODEL #		
NAME #		
<u>SIS #</u>		
AIA #		

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Large drain hole on cooking surface permits the draining of fat into large 1,5 liter collector placed under the cooking surface.
- Safety thermostat with temperature markings for additional safety.
- Stainless steel high splash guards on the rear and sides of cooking surface. Splash guards can be easily removed for cleaning and are dishwasher-safe.
- Piezo spark ignition with thermostatic valve for added safety.
- Units have separate controls for each half module of the cooking surface.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Temperature range from 90° up to 270°C.
- Polished chromium surface avoids the mixing of flavors when passing from one type of food to another.
- Cooking surface 15mm thick polished chrome for optimum grilling results and ease of use.
- Suitable for countertop installation.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Cooking surface to be completely smooth. (only for 392054)
- Unit is 900mm deep to give a larger working surface area.
- Cooking surface to be 2/3 smooth and 1/3 ribbed. (only for 392055)

APPROVAL:



Zanussi Professional www.zanussiprofessional.com



Included Accessories

 1 of Scraper for smooth plate for fry tops 	PNC 164255	
•	PNC 206420	
Optional Accessories		
Scraper for smooth plate for fry tops	PNC 164255	
Junction sealing kit	PNC 206086	
• Draught diverter, 150 mm diameter	PNC 206132	
 Matching ring for flue condenser, 150 mm diameter 	PNC 206133	
 Support for bridge type installation, 800 mm 	PNC 206137	
 Support for bridge type installation, 1000 mm 	PNC 206138	
 Support for bridge type installation, 1200 mm 	PNC 206139	
 Support for bridge type installation, 1400 mm 	PNC 206140	
 Support for bridge type installation, 1600 mm 	PNC 206141	
 Side handrail for right/left hand 	PNC 206165	
 Frontal handrail 800 mm 	PNC 206167	
 Large handrail (portioning shelf) 800 mm 	PNC 206186	
 Frontal handrail 1200 mm 	PNC 206191	
 Frontal handrail 1600 mm 	PNC 206192	
Flue condenser for 1 module, 150 mm diameter	PNC 206246	
 Chimney upstand, 800 mm (only for 392054) 	PNC 206304	
• 2 side covering panels, height 250 mm, depth 900 mm	PNC 206321	
 Grease/oil container kit for frytops 	PNC 206346	
 Chimney grid net, 400mm 	PNC 206400	
 Scraper for ribbed plate fry tops - kit includes knife blades for both smooth and ribbed surface (only for 392055) 	PNC 206420	
Water drain for full module fry top	PNC 216153	
Pressure regulator for gas units	PNC 927225	



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.



10 7/16 " 266 mm

EQ

G



Gaa

Fuend |

or aga o of apj at insu

7" w.c. (17.4 mbar) 20 kW Natural Gas G20 (20mbar) LPG;Natural Gas 1/2"

Working Temperature MIN:	90 °C
Working Temperature MAX:	270 °C
External dimensions, Width:	800 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	250 mm
Net weight:	105 kg
Shipping weight:	
392054 (Z9FTGHCS00)	101 kg
392055 (Z9FTGHCP00)	100 kg
Shipping height:	580 mm
Shipping width:	
392054 (Z9FTGHCS00)	1020 mm
392055 (Z9FTGHCP00)	1010 mm
Shipping depth:	860 mm
Shipping volume:	
392054 (Z9FTGHCS00)	0.51 m³
392055 (Z9FTGHCP00)	0.5 m³
[NOT TRANSLATED]	N9RG
Cooking surface width:	730 mm
Cooking surface depth:	700 mm

ainst temperature sensitive pproximately 150 mm should be ulation fitted.



Modular Cooking Range Line EVO900 Full Module Gas Fry Top, Chromium Plated

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.