

## Pastry and Bakery Line 3 Door Refrigerated Counter, -2°/+7°C, 600X400 grid

ITEM#	
MODEL #	
NAME #	
SIS#	
AIA#	



110908 (BPLZR3NL)

3-door Refrigerated Counter, 600x400 mm grids, -2+7°C, AISI 304

## **Short Form Specification**

#### Item No.

Internal and external doors, front and side panels in AISI 304 stainless steel.

Stainless steel worktop. Three reversible doors. Frontal access for easy maintenance. Uniformity of temperature guaranteed by the position of the evaporator and the design of the internal ventilation. Completely automatic defrosting.

Refrigerator counter has operating temperature that can be adjusted from  $-2^{\circ}$  to  $+7^{\circ}$ C.

Supplied with 9 pairs of runners 600x400mm.

## **Main Features**

- Suitable for use in ambient temperature of up to 40°C (climatic class 5).
- Electronic control panel and digital display.
- Frontal access for easy maintenance.
- Internal runners removable without any tools for faster cleaning operations.
- Adjustable temperature range from -2°C to +7°c.

#### Construction

- The position of the evaporator and the design of the internal ventilation facilitate the uniformity of the temperature.
- Stainless steel AISI 304 internal and external panels including back.
- Rounded internal corners for ease of cleaning.
- Self closing doors.
- 3 compartments with 3 doors.
- Adjustable feet from 140mm to 240mm.

## **Included Accessories**


 9 of Pair of runners 600x400 PNC 880673 mm for Pastry Counter


## **Optional Accessories**

- Shelf grid for cabinets -600X400mm
- PNC 728875 🗅
- Stainlees steel grid, 600x400mm for pastry counter
- PNC 728876 □
- Pair of runners 600x400 mm PNC 880673 ☐ for Pastry Counter



## **Pastry and Bakery Line** 3 Door Refrigerated Counter, -2°/+7°C, 600X400 grid





**EI** = Electrical inlet (power)



#### **Electric**

Supply voltage:

110908 (BPLZR3NL) 230 V/1N ph/50 Hz

Electrical power max.: 0.247 kW

**Key Information:** 

**Gross capacity:** 545 It **Net Volume:** 360 It N° of doors:

**Door hinges:** 1 Left+2 Right

**External dimensions,** 

Width: 2006 mm

External dimensions,

Depth: 800 mm

**External dimensions, Depth with Doors Open:** 

1280 mm

External dimensions,

**Height:** 850 mm

Type of external Stainless Steel AISI 304

material: Scotch Brite Type of internal material: **304 AISI** 

**Internal side panels** 

material: **304 AISI** 

#### **Refrigeration Data**

Control type:

Side

Top

Refrigeration power at

evaporation temperature: -10 °C

**Operating temperature** 

-2 °C

**Operating temperature** 

7°C max.:

#### **Product Information (EU Regulation** 2015/1094)

Type of model (EU Reg. 2015/1094): counter chilled

#### Sustainability

Energy Class (EU Reg. 2015/1094):


Yearly and daily energy consumption (EU Reg.

515kWh/year - 1kWh/24h 2015/1094):

Climate class (EU Reg.

2015/1094): Heavy Duty (5)

Energy Efficiency Index-EEI (EU Reg. 2015/1094): 22 R290 Refrigerant type: **GWP** Index: 3









## Pastry and Bakery Line 3 Door Refrigerated Counter, -2°/+7°C, 600X400 grid

# EU energy labelling from 1st July 2016

The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe. Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

SI 2020 No. 1528.

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

