

Eco Preparation 1200 mm Hot Cupboard with Upstand

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____

**132876 (MSR1217N)**Hot cupboard, with 100mm
upstand, 1200mm

Short Form Specification

Item No. _____

Made entirely from stainless steel. Inner welded frame in stainless steel. Unique connection of panels to inner frame. Worktop in 304 AISI stainless steel (40mm high) incorporates a layer of sound deadening material and has upturned edges. Upstand (h=100mm) with 8mm rounded edge. Sound-deadened sliding doors. Handles are formed by a fold in the sliding doors. Height-adjustable intermediate shelf with riveted corners and transversal reinforcement in stainless steel. Ventilated hot air flow system guarantees temperature evenness, air flows underneath the intermediate shelf and throughout the cabinet. Thermostat with digital display to adjust the internal temperature (up to 75°C). Mounted on feet, adjustable in height.

Main Features

- Handles in stainless steel for better hygiene and reliability.
- Digital display thermostat to control the internal temperature.
- Model specific to keep dishes warm.
- Sturdiness, stability and reliability of table accurately tested.
- 100 mm upstand with 13mm depth and 10 mm radiused corner, designed to be used against a wall.

Construction

- 40 mm worktop in 304 AISI stainless steel.
- Inner welded frame in stainless steel to guarantee superior strength and stability.
- Handles directly built into the sliding doors.
- Equipped with intermediate shelf which can be positioned at three different heights.
- Intermediate shelf in stainless steel with riveted corners and transversal reinforcement in stainless steel.
- Sturdy sound-deadened sliding doors on tracks located flush to the front of the frame.
- Easy access to the cupboard interior on all lengths guaranteed by the use of only 2 doors.
- Constructed entirely in stainless steel to offer maximum durability.
- Constructed entirely in stainless steel to offer maximum durability.
- Base panel has 40mm high profile, is 8/10 in thickness with upturned edges and bar reinforcement. It is welded to legs for further structure reinforcement.
- 304 AISI stainless steel feet, 150 mm high and 54 mm in diameter, adjustable by -35/+25 mm.

Optional Accessories

- Overshelf, neutral, one tier, PNC 132965
1200 mm
- Overshelf, with led light and PNC 132989
ceramic light, one tier, 1200mm
- Wheel kit for cupboards, 4 PNC 855299
wheels (2 with brakes), D=1000
mm

APPROVAL: _____

Electric**Supply voltage:****132876 (MSR1217N)** 220-240 V/1N ph/50/60 Hz**Total Watts:**

2.4 kW

Key Information:**Cabinet width:** 1030 mm**Cabinet depth:** 645 mm**Cabinet height:** 610 mm**Cabinet temperature:** 50-75 °C**External dimensions,
Width:** 1200 mm**External dimensions,
Depth:** 700 mm**External dimensions,
Height:** 1000 mm**Upstand Dimensions,
Height:** 100 mm**Upstand Dimensions,
Depth:** 13 mm**Upstand Dimensions,
Radius:** R=10**Worktop thickness:** 50 mm**Net weight:** 55 kg