

Modular Cooking Range Line 200 mm - 1 Well Electric Fryer 9 liter with oil pump

ITEM#	
MODEL #	
MODEL #	
NAME #	
SIS#	
AIA#	



285003 (ZXFRPB1BWQ)

9lt electric fryer with 1 well, 1 basket, oil pump and warning led

285005 (ZXFREB1BWQ)

9lt electric fryer with 1 well, 1 basket, oil pump and warning led

Short Form Specification

Item No.

Electric freestanding fryer with deep-drawn well is ideal for kitchens needing a versatile, compact, efficient but high productivity unit capable of cooking numerous portions time after time. The well layout, heating elements layout and the "eco" mode, require a minimum amount of oil and guarantee long oil life. Made in stainless steel. 4-position tilting elements to ease cleaning and use. Oil pump.

Main Features

- All major compartments located in front of unit for ease of maintenance.
- IP24 protected.
- Overheat protection thermostat as standard on all units
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Oil drains through a tap into a drainage container positioned under the well.
- Supplied as standard with 1 basket and 1 right side door for cupboard.
- Deep drawn well.
- Internal high efficiency tilting heating elements for high productivity and ease of cleaning of internal well.
- Integrated s/s oil filter.
- Oil pump timer for temporized filtration to be set up to 5 minutes.
- · Control knobs positioned behind the door.
- Unit delivered with four 50 mm legs in stainless steel as standard.
- 4-lights display to indicate equipment under voltage, heaters on in "eco" mode, heaters on in "fry" mode, the unit is in overheating protection mode.

Construction

- Interior of well with rounded corners for ease of cleaning
- One piece pressed 1.5 mm work top in Stainless steel.
- Exterior panels in Stainless steel with Scotch Brite finish to meet the highest hygiene standards.
- The unit is designed for freestanding installation having external frame closed on sides, back and bottom.
- A bracket for wall mounting installation is provided as standard.
- Folding lid with storage in the door.
- The V-shaped well is made of two pieces of pressed stainless steel that are seamlessly laser-welded. (only for 285005)
- Unit is 60 cm deep to give a compact working area and reduced footprint.

Sustainability

- Eco function switches the unit in stand-by mode to save energy. Fast temperature recovery to restart frying in less than one minute.
- This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

Included Accessories

1 of Basket for 9 lt fryer
 1 of Stainless steel oil collecting filter for 9 lt fryer

PNC 206390
PNC 206393

Optional Accessories

Basket for 9 lt fryer
PNC 206390 □
PNC 206391 □
PNC 206391 □

APPROVAL:



Modular Cooking Range Line 200 mm - 1 Well Electric Fryer 9 liter with oil pump

r PNC 206392	
9 PNC 206393	
PNC 206394	
PNC 206438	
PNC 206439	
PNC 206440	
PNC 206443	
	PNC 206393 PNC 206394 PNC 206438 PNC 206439 PNC 206440





Modular Cooking Range Line 200 mm - 1 Well Electric Fryer 9 liter with oil pump

Front 35 11/16 튙 90 E Q 1 9/16 " Side 29 11/16 " 1 3/4 " 45 mm 750 1 33 7/16 " 850 mm ΕQ ΕI 3 15/16 - 5 7/8 4 7/8 " 14 3/4 ' 3 15/16 " -150 mm ė **EI** = Electrical inlet (power) **EQ** = Equipotential screw Top

ONVGLO

Electric

Supply voltage:

285003 (ZXFRPB1BWQ) 240 V/1 ph/50/60 Hz 285005 (ZXFREB1BWQ) 415 V/3N ph/50/60 Hz

Rated amps:

285003 (ZXFRPB1BWQ) 30.8 A 285005 (ZXFREB1BWQ) 17.8 A **Total Watts:** 7.4 kW

Key Information:

Number of wells:

Usable well dimensions (width):

Usable well dimensions (height):

Usable well dimensions

(depth):

Well capacity:

Thermostat Range: External dimensions, Width:

External dimensions,

Depth:

External dimensions, **Height:**

Net weight:

Integrated oil filter

Oil pump

1

170 mm

330 mm

500 mm

7 It MIN; 9 It MAX

90 °C MIN; 185 °C MAX

200 mm

600 mm

930 mm

35 kg

Modular Cooking Range Line 200 mm - 1 Well Electric Fryer 9 liter with oil pump