

Modular Cooking Range Line 200 mm - 1 Well Electric Fryer 9 liter

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____



285002 (ZXFRPB1BWF) 9lt electric fryer with 1 well, 1 basket and warning led

285004 (ZXFREB1BWF) 9lt electric fryer with 1 well, 1 basket and warning led

Short Form Specification

Item No.

Electric freestanding fryer with deep-drawn well ideal for kitchens needing a versatile, compact, efficient but high productivity unit capable of cooking numerous portions time after time. The well layout, heating elements layout and the "eco" mode, require a minimum amount of oil and guarantee long oil life. Made in stainless steel. 4-position tilting elements to ease cleaning and use.

Main Features

- All major compartments located in front of unit for ease of maintenance.
- IP24 protected.
- Overheat protection thermostat as standard on all units.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Oil drains through a tap into a drainage container positioned under the well.
- Supplied as standard with 1 basket and 1 right side door for cupboard.
- Deep drawn well.
- Internal high efficiency tilting heating elements for high productivity and ease of cleaning of internal well.
- Integrated s/s oil filter.
- Control knobs positioned behind the door.
- Unit delivered with four 50 mm legs in stainless steel as standard.
- 4-lights display to indicate equipment under voltage, heaters on in "eco" mode, heaters on in "fry" mode, the unit is in overheating protection mode.

Construction

- Interior of well with rounded corners for ease of cleaning.
- One piece pressed 1.5 mm work top in Stainless steel.
- Exterior panels in Stainless steel with Scotch Brite finish to meet the highest hygiene standards.
- Unit is 60 cm deep to give a compact working area and reduced footprint.
- The unit is designed for freestanding installation having external frame closed on sides, back and bottom.
- A bracket for wall mounting installation is provided as standard.
- Folding lid with storage in the door.

Sustainability

- Eco function switches the unit in stand-by mode to save energy. Fast temperature recovery to restart frying in less than one minute.
- This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

Included Accessories

- 1 of Basket for 9 lt fryer PNC 206390
- 1 of Stainless steel oil collecting filter for 9 lt fryer PNC 206393


Optional Accessories

- Basket for 9 lt fryer PNC 206390 ☐
- Connecting kit for 9 lt fryer PNC 206391 ☐
- Fabric oil collecting filter for 9 lt fryer PNC 206392 ☐
- Stainless steel oil collecting filter for 9 lt fryer PNC 206393 ☐
- Perforated fish plate for 9 lt fryers PNC 206394 ☐


APPROVAL: _____

- Kit of feet support for 2 modules of 200mm fryers PNC 206438 ☐
- Kit of feet support for 3 modules of 200mm fryers PNC 206439 ☐
- Kit of feet support for 4 modules of 200mm fryers PNC 206440 ☐
- Stainless steel oil large filter for 9lt fryer PNC 206443 ☐

Modular Cooking Range Line
200 mm - 1 Well Electric Fryer
9 liter




Front



Side

EI = Electrical inlet (power)
EQ = Equipotential screw



Top

Electric

predisposed for

285002 (ZXFRPB1BWF) 230 V 1N 50/60 Hz 6,8 kW

285004 (ZXFREB1BWF) 400 V 3 50/60 Hz 6,8 kW

Supply voltage:

285002 (ZXFRPB1BWF) 220-240 V/1N ph/50/60 Hz

285004 (ZXFREB1BWF) 380-415 V/3N ph/50/60 Hz

Rated amps:

285002 (ZXFRPB1BWF) 30.8 A

285004 (ZXFREB1BWF) 17.8 A

Total Watts:

7.4 kW

Key Information:

Number of wells:	1
-------------------------	---

Usable well dimensions (width): 170 mm

Usable well dimensions (height): 330 mm

Usable well dimensions (depth): 500 mm

Well capacity: 7 lt MIN; 9 lt MAX

Thermostat Range: 90 °C MIN; 185 °C MAX

**External dimensions,
Width:**

200 mm

**External dimensions,
Depth:**

600 mm

External dimensions, Height: 930 mm

Net weight: 35 kg

- Integrated oil filter