

Plug In Easy CookingPRO Counter for 3 3PH Units



352083 (Z2VVDDBQZA)

Easy CookingPRO Mobile Counter, suitable for 3 Plug-in appliances with two 1-phase and three 3-phase sockets

Short Form Specification

Item No.

Plug in mobile cooking station in heavy duty AISI 304 stainless steel. Can be combined with up to three Easy CookingPRO table top units 3PHASE: flat induction hobs, induction wok, induction griddle. Plate holder shelf coupled with tempered glass and lighting for a better visibility from guest side. Automatic ventilation adjustment according to cooking intensity thanks to Easy CookingPRO Match function. Integrated air filtration system - Easy CookingPRO Ventilation - to absorb efficiently grease particles and bad odours in the working area. It is a 2-stage system with stainless steel and ceramic activated carbon filters easy to remove for cleaning operations. For additional storage space, up to four optional neutral 30 lt drawers are available.

Counter Plug Type : IEC/EN 60309-1/2 - 32 Amps. Mounted on 4 swiveling wheels (2 with brakes).

Main Features

<u>ITEM #</u> MODEL # NAME #

SIS #

AIA #

- Can be combined with up to three tabletop appliances Easy CookingPRO 3PHASE and/or Easy CookingPRO 1PHASE (Plug Type Schuko): flat induction hobs, induction woks, induction griddles.
- Compact, lightweight and easy to move.
- Plate holder shelf coupled with tempered glass and lighting for a better visibility from guest side.
- Designed for Easy CookingPRO Match function for automatic regulation of fan speed according to cooking intensity. Can be activated exclusively with Easy CookingPRO stand alone units.
- Easy CookingPRO Ventilation is a low noise air filtration system to absorb efficiently grease particles and bad odours in the working area. It is a 2-stage filtering system with stainless steel fat filters and ceramic activated carbon ones.
- 30 It neutral drawer accepting N° 1 GN1/1 is available as optional accessory.
- Through the user interface with soft touch buttons the operator can:
 - -vary the 4 fan speed;
 - switch on the LED lighting system of the cooking area;
 - display indications on maintenance operations (e.g. on filters) or any anomalous operating conditions.

Construction

- Heavy duty AISI 304 Stainless steel construction.
- Mounted on 4 swivelling wheels with brakes on the 2 front wheels (on the operator side).
- Frontal panel in AISI 304 can be customized requiring a special execution.
- Grease and odours filters are easily accessible and removable from operator's side for efficient maintanance without any tool.
- Side support frames each holding n.2 GN 1/9 containers and n.1 tools holder. All included in the standard delivery and easily removable for better cleanability.
- Plug type: IEC/EN 60309-1/2 32 amps.
- IPx4 water protection.

٠

Included Accessories

- 3 of Carbon filter for Mobile Counter PNC 650190
 - 3 of Labyrinth grease filter with Stainless steel grid for Mobile Counter
- 1 of Support frame for containers PNC 650192 including 2 x 1/9 GN trays and 1 kitchen tool holder for Mobile Counter, left side
- 1 of Support frame for containers including 2 x 1/9 GN trays and 1 kitchen tool holder for Mobile Counter, right side

Optional Accessories

- Tilting side shelf for Mobile Counter PNC 650005
- Neutral drawer for Mobile Counter PNC 650189
- Carbon filter for Mobile Counter PNC 650190
- Labyrinth grease filter with stainless PNC 650191 steel grid for Mobile Counter

APPROVAL:

Part of



- Support frame for containers including 2 x PNC 650192 1/9 GN trays and 1 kitchen tool holder for Mobile Counter, left side
 Support frame for containers including 2 x PNC 650193 1/9 GN trays and 1 kitchen tool holder for
- Mobile Counter, right side
 Kitchen tool holder to be inserted into support frame for Mobile Counter
- Side paper towel support PNC 650195
- Cover in PVC for Mobile Counter 3 modules PNC 651004







1653 EO 284 s 763. EI 22 Side 788 350 MAX **EI** = Electrical inlet (power) **EO** = Electrical Outlet Тор <u>MIN 100</u> <u>MIN 100</u>

Electric

Front

Supply voltage: Electrical power max: Plug type: 380-415 V/3N ph/50/60 Hz 20 kW IEC/EN 60309-1/2

Key Information:

Frontal power sockets available for Plug-in Units: External dimensions, Width: External dimensions, Depth: External dimensions, Height: Net weight: 3 x 3 Phase Plugs (Plug type IEC/ EN 60309-1/2) + 2 x 1 Phase Plugs (Plug Type Schuko) 1653 mm 788 mm 1284 mm 230 kg

Plug In Easy CookingPRO Counter for 3 3PH Units

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.