

Plug In **Easy CookingPRO Counter for 2** 1PH Units, 1 refrigerated drawer

ITEM #	
MODEL #	
NAME #	
SIS #	
ΔΙΔ #	



352084 (Z2VVADBRZA)

Easy CookingPRO Mobile Counter with 1 refrigerated drawer, suitable for 2 Plug-in appliances with four 1-phase sockets

Short Form Specification

Item No.

Plug in mobile cooking station in heavy duty AISI 304 stainless steel. Can be combined with up to two Easy CookingPRO table top units 1PHASE (Plug Type Schuko): flat induction hobs, induction wok, induction griddle. Plate holder shelf coupled with tempered glass and lighting for a better visibility from guest side. One integrated stainless steel refrigerated drawer with 37lt capacity accepting N° 1 GN1/1 + N° 1 GN 2/4 trays. Temperature range between 0 and + 10°C. No drain required. Automatic ventilation adjustment according to cooking intensity thanks to Easy CookingPRO Match function. Integrated air filtration system - Easy CookingPRO Ventilation - to absorb efficiently grease particles and bad odours in the working area. It is a 2-stage system with stainless steel and ceramic activated carbon filters easy to remove for cleaning operations. For additional storage space, one optional neutral 30 lt drawers is available. Counter Plug Type : IEC/EN 60309-1/2 - 32 Amps. Mounted on 4 swiveling wheels (2 with brakes).

Main Features

- Can be combined with up to three tabletop appliances Easy CookingPRO 1PHASE (Plug Type Schuko): flat induction hobs, induction wok, induction griddle.
- Compact, lightweight and easy to move.
- Plate holder shelf coupled with tempered glass and lighting for a better visibility from guest side.
- Designed for Easy CookingPRO Match function for automatic regulation of fan speed according to cooking intensity. Can be activated exclusively with Easy CookingPRO stand alone units.
- Easy CookingPRO Ventilation is a low noise air filtration system to absorb efficiently grease particles and bad odours in the working area. It is a 2-stage filtering system with stainless steel fat filters and ceramic activated carbon ones.
- Integrated stainless steel refrigerated drawer temperature regulation between 0°C and +10°C. No drain
- 37 It refrigerated drawer capacity accepting N° 1 GN1/1 + N° 1 GN 2/4 trays.
- 30 It neutral drawer accepting N° 1 GN1/1 is available as optional accessory.
- Through the user interface with soft touch buttons the operator can:

 - vary the 4 fan speed;
 switch on the LED lighting system of the cooking area;
 - set the temperature of the refrigerated drawer;
 - -display indications on maintenance operations (e.g. on filters) or any anomalous operating conditions.

Construction

- Heavy duty AISI 304 Stainless steel construction.
- Mounted on 4 swivelling wheels with brakes on the 2 front wheels (on the operator side).
- Frontal panel in AISI 304 can be customized requiring a special execution.
- Grease and odours filters are easily accessible and removable from operator's side for efficient maintanance without any tool.
- Side support frames each holding n.2 GN 1/9 containers and n.1 tools holder. All included in the standard delivery and easily removable for better cleanability.
- Plug type: IEC/EN 60309-1/2 32 amps.
- IPx4 water protection.

Included Accessories

- 2 of Carbon filter for Mobile Counter PNC 650190 PNC 650191
- · 2 of Labyrinth grease filter with stainless steel grid for Mobile Counter

PNC 650192

- 1 of Support frame for containers including 2 x 1/9 GN trays and 1 kitchen tool holder for Mobile Counter, left side
- 1 of Support frame for containers including 2 x 1/9 GN trays and 1 kitchen tool holder for Mobile Counter, right side

PNC 650193

Optional Accessories

· Tilting side shelf for Mobile Counter

PNC 650005

APPROVAL:





Plug In Easy CookingPRO Counter for 2 1PH Units, 1 refrigerated drawer

Neutral drawer for Mobile Counter	PNC 650189	
 Carbon filter for Mobile Counter 	PNC 650190	
 Labyrinth grease filter with stainless steel grid for Mobile Counter 	PNC 650191	
 Support frame for containers including 2 x 1/9 GN trays and 1 kitchen tool holder for Mobile Counter, left side 	PNC 650192	
 Support frame for containers including 2 x 1/9 GN trays and 1 kitchen tool holder for Mobile Counter, right side 	PNC 650193	
 Kitchen tool holder to be inserted into support frame for Mobile Counter 	PNC 650194	
 Side paper towel support 	PNC 650195	
• Cover in PVC for Mobile Counter 2 modules	PNC 651003	






Plug In Easy CookingPRO Counter for 2 1PH Units, 1 refrigerated drawer

Front E0 1284 E-2 581 763. Side 788 400

350

EI = Electrical inlet (power) **EO** = Electrical Outlet



Electric

Supply voltage:

380-415/380-400 V/3N ph/50/60

352084 (Z2VVADBRZA) Electrical power max.: 14.5 kW

Plug type: IEC/EN 60309-1/2

Key Information:

External dimensions, Width: 1231 mm **External dimensions, Depth:** 788 mm **External dimensions, Height:** 1284 mm Net weight: 180 kg

Frontal power sockets available for Plug-in Units: 4 x 1 Phase Plugs (Plug Type

Schuko)

Sustainability

Refrigerant type: R600a

