

# Modular Cooking Range Line EVO700 One Well Freestanding Gas Fryer 15 liter

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



372070 (Z7FRGD1GF0)

15-It gas fryer with 1 "V" shape well (external burners), 1 basket and lid included - free standing

# **Short Form Specification**

#### Item No.

To be installed on height adjustable feet in stainless steel. Two high efficiency 7 kW burners in stainless steel. Suitable for natural gas or LPG. Deep drawn V-shaped well. Oil drains through a tap into a container under the well. Exterior panels in stainless steel with Scotch Brite finish. One piece pressed work top in 1.5 mm thick stainless steel. Right-angled side edges to allow flush-fitting junction between units.

## **Main Features**

- Unit to be mounted on 50mm height adjustable feet in stainless steel.
- Deep drawn V-Shaped well.
- Two high efficiency 7 kW burners in stainless steel with flame failure device attached to the outside of the well.
- Thermostatic regulation of oil temperature up to a maximum of 185 °C.
- Flame failure device on each burner.
- Overheat protection thermostat as standard on all units.
- Oil drains through a tap into a drainage container positioned under the well.
- All major compartments located in front of unit for ease of maintenance.
- Piezo spark ignition for added safety.
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- IPx4 water protection.
- Optional portable oil quality monitoring tool (code 9B8081) for efficient oil management.

## Construction

- Interior of well with rounded corners for ease of cleaning.
- All exterior panels in Stainless Steel with Scotch Brite finishing.
- One piece pressed 1.5 mm work top in Stainless steel.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.

## **Sustainability**

 This model is compliant with Swiss Energy Efficiency Ordinance (730.02).



# Modular Cooking Range Line EVO700 One Well Freestanding Gas Fryer 15 liter


			Base support for feet or wheels - 1200mm	PNC 206368	
Included Accessories			(EV0700/EV0900)		
<ul><li>1 of Door for open base cupboard</li><li>1 of Basket for 14 and 15lt fryers</li></ul>	PNC 206342 PNC 921691	•	<ul> <li>Base support for feet or wheels - 1600mm (EVO700/900)</li> </ul>	PNC 206369	
			<ul> <li>Rear paneling - 600mm (EV0700/900)</li> </ul>	PNC 206373	
Optional Accessories	DNC 00c00c		• Rear paneling - 800mm (EV0700/900)		
Junction sealing kit     Drawaht divertors 100 man dispractors	PNC 206086		• Rear paneling - 1000mm (EV0700/900)		
Draught diverter, 120 mm diameter  Matching ring for flux condenses.	PNC 206126		• Rear paneling - 1200mm (EV0700/900)		
<ul> <li>Matching ring for flue condenser, 120 -130 mm diameter</li> </ul>	PNC 206127		<ul> <li>Chimney grid net, 400mm</li> </ul>		
Flanged feet kit	PNC 206136	1 1	Base support for feet/wheels (600mm)		
<ul> <li>Frontal kicking strip for concrete</li> </ul>	PNC 206147		Basket for 14 and 15lt fryers		
installation, 400 mm		•	2 half size baskets for 14 and 15lt fryers		
<ul> <li>Frontal kicking strip for concrete installation, 800 mm</li> </ul>	PNC 206148	_	• Filter for fryer oil collection basin for 7lt, 14lt, 15lt free standing fryers		_
<ul> <li>Frontal kicking strip for concrete installation, 1000 mm</li> </ul>	PNC 206150	_	Unclogging rod for 15lt fryers drainage pipe		_
<ul> <li>Frontal kicking strip for concrete installation, 1200 mm</li> </ul>	PNC 206151	_	Deflector for floured products for the 15lt fryer		
<ul> <li>Frontal kicking strip for concrete installation, 1600 mm</li> </ul>	PNC 206152		<ul> <li>Pressure regulator for gas units</li> </ul>	PNC 927225	
<ul> <li>Frontal handrail 400 mm</li> </ul>	PNC 206166				
<ul> <li>Frontal handrail 800 mm</li> </ul>	PNC 206167				
<ul> <li>Frontal kicking strip, 400 mm</li> </ul>	PNC 206175				
<ul> <li>Frontal kicking strip, 800 mm</li> </ul>	PNC 206176				
<ul> <li>Frontal kicking strip, 1000 mm</li> </ul>	PNC 206177				
<ul> <li>Frontal kicking strip, 1200 mm</li> </ul>	PNC 206178				
<ul> <li>Frontal kicking strip, 1600 mm</li> </ul>	PNC 206179				
<ul> <li>Large handrail (portioning shelf) 400 mm</li> </ul>	PNC 206185				
<ul> <li>Large handrail (portioning shelf) 800 mm</li> </ul>	PNC 206186				
<ul> <li>Frontal handrail 1200 mm</li> </ul>	PNC 206191				
<ul> <li>Frontal handrail 1600 mm</li> </ul>	PNC 206192				
<ul> <li>4 feet for concrete installation (not for 900 line freestanding grill)</li> </ul>	PNC 206210				
<ul> <li>Sediment tray for 15lt fryers</li> </ul>	PNC 206235				
<ul> <li>Right and left side handrails</li> </ul>	PNC 206240				
<ul> <li>Pair of side kicking strips</li> </ul>	PNC 206249				
<ul> <li>Pair of side kicking strips (concrete installation)</li> </ul>	PNC 206265				
<ul> <li>Oil drain pipe for 15lt free standing fryer</li> </ul>	PNC 206301				
<ul> <li>Chimney upstand, 400 mm</li> </ul>	PNC 206303				
<ul> <li>Flue condenser for 1/2 module, 120 mm diameter</li> </ul>	PNC 206310				
<ul> <li>2 side covering panels, height 700 mm, depth 700 mm</li> </ul>	, PNC 206319				
<ul> <li>Door for open base cupboard</li> </ul>	PNC 206342				
<ul> <li>Base support for feet or wheels - 400mm (EV0700/900)</li> </ul>	PNC 206366				
Base support for feet or wheels - 800mm (EV0700/900)	PNC 206367				






# Modular Cooking Range Line EVO700 One Well Freestanding Gas Fryer 15 liter










**EQ** = Equipotential screw

**G** = Gas connection

## Top



DNV-GL C C AGA E

#### Gas

Gas Power: 14 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG; Natural Gas

Gas Inlet: 1/2"

## **Key Information:**

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Usable well dimensions (width): 240 mm
Usable well dimensions (height): 505 mm
Usable well dimensions (depth): 380 mm

Well capacity: 13 It MIN; 15 It MAX
Thermostat Range: 105 °C MIN; 185 °C MAX

Net weight:55 kgShipping weight:58 kgShipping height:1120 mmShipping width:460 mmShipping depth:820 mmShipping volume:0.42 m³Certification group:N7FG

