

Modular Cooking Range Line EVO900 4-Burner Gas Boiling Top - Town Gas

ITEM #	
MODEL #	
NAME #	
SIS #	_
AIA #	



392193 (Z9GCTH4Y00)

4-burner (3x5,5 kW and 1x7,5 kW) gas boiling top - town gas

Short Form Specification

Item No.

To be installed on open base installations, bridging supports or cantilever systems. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty stainless steel. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- The three 5.5 kW and one 7.5 kW high efficiency burners are available in two different sizes to suit high performing cooking requirements of the most demanding customers:
 - -5.5 kW burner with 60 mm diameter
 - -7.5 kW burner with 100 mm diameter
- Gas appliance supplied for use with town gas.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- Protected pilot light.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Suitable for countertop installation.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- · Pan supports in stainless steel.
- Unit is 900mm deep to give a larger working surface

APPROVAL:



Modular Cooking Range Line EVO900 4-Burner Gas Boiling Top - Town Gas


Optional Accessories


	D110 00000	_
 Junction sealing kit 	PNC 206086	
 Draught diverter, 150 mm diameter 	PNC 206132	
 Matching ring for flue condenser, 150 mm diameter 	PNC 206133	
 Support for bridge type installation, 800 mm 	PNC 206137	
• Support for bridge type installation, 1000 mm	PNC 206138	
Support for bridge type installation, 1200 mm	PNC 206139	
• Support for bridge type installation, 1400 mm	PNC 206140	
• Support for bridge type installation, 1600 mm	PNC 206141	
Side handrail for right/left hand	PNC 206165	
Frontal handrail 800 mm	PNC 206167	
Single burner smooth plate for direct cooking - fits frontal burners only	PNC 206171	
Single burner ribbed plate for direct cooking - fits frontal burners only	PNC 206172	
Large handrail (portioning shelf) 800 mm	PNC 206186	
Frontal handrail 1200 mm	PNC 206191	
Frontal handrail 1600 mm	PNC 206192	
• Flue condenser for 1 module, 150 mm diameter	PNC 206246	
Water column with swivel arm (water column extension not included)	PNC 206289	
Water column extension	PNC 206290	
 Stainless steel grid for 2 burners 	PNC 206298	
Chimney upstand, 800 mm	PNC 206304	
• 2 side covering panels, height 250 mm, depth 900 mm	PNC 206321	
 Wok pan support for open burners (EV0700/900) 	PNC 206363	
Kit town gas nozzles (G150) for EV0900 gas range	PNC 206384	
Pressure regulator for gas units	PNC 927225	






Modular Cooking Range Line EVO900 4-Burner Gas Boiling Top - Town Gas







Gas

Natural gas - Pressure:

392193 (Z9GCTH4Y00) 7" w.c. (17.4 mbar)

Gas Power: 28 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG;Town Gas

Gas Inlet: 1/2"

Key Information:

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.

Net weight: 79 kg Shipping weight: 99 kg Shipping height: 540 mm Shipping width: 1020 mm Shipping depth: 860 mm Shipping volume: 0.47 m^{3} **Front Burners Power:** 5.5 - 5.5 kW **Back Burners Power:** 5.5 - 7.5 kW **Certification group:** N9CT **Back Burners Dimension - mm** Ø 60 Ø 100 Front Burners Dimension - mm Ø 60 Ø 60

