

Modular Cooking Range Line EVO900 6-Burner Gas Range on Large Gas Oven

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA #	



392015 (Z9GCGL6SL0)

6-burner (2x10 kW, 4x6 kW) gas range on large gas oven (12 kW)

Short Form Specification

Item No.

To be mounted on stainless steel feet with height adjustment up to 50 mm and can be mounted on cantilever systems. High efficiency flower flame burners with continuous power regulation and optimized combustion. Flame failure device as standard on burners to protect against accidental extinguishing. Exterior panels of unit in stainless steel with Scotch Brite finish. Pan supports in heavy duty stainless steel. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

Main Features

- Unit to be mounted on stainless steel feet with height adjustment up to 50 mm. Unit can be easily mounted on cantilever systems.
- The four 6 kW and two 10 kW high efficiency burners are available in two different sizes to suit high performing cooking requirements of the most demanding customers:
- -60 mm burners with continuous power regulation from 1.5 to 6 kW
- -100 mm burners with continuous power regulation from 2.2 kW to 10 kW
- Gas appliance supplied for use with natural or LPG gas, conversion jets supplied as standard.
- Large sized pan support in cast iron (stainless steel as option) with long center fins to allow the use of the largest down to the smallest pans.
- · Burners with optimized combustion.
- Flame failure device on each burner protects against gas leakage when accidental extinguishing of the flame occurs.
- · Protected pilot light.
- Base compartment consists of a large gas heated standard oven with stainless steel burners and self stabilizing flame positioned beneath the base plate.
 Oven chamber to have 3 levels of runners to accomodate 2/1 GN shelves (2 steam pans) and ribbed cast iron base plate.
- Oven thermostat adjustable from 120 °C to 280 °C.
- · 40 mm thick oven door for heat insulation.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Control knobs provide smooth, continuous rotation from min to max power level.

Construction

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Pan supports in stainless steel.
- Unit is 900mm deep to give a larger working surface area

APPROVAL:




Modular Cooking Range Line EVO900 6-Burner Gas Range on Large Gas Oven


Included Accessories		Rear paneling - 1200mm (EV0700/900)Kit town gas nozzles (G150) for EV0900	PNC 206376 PNC 206385
• 1 of Chrome grid for large oven	PNC 206204	gas ranges on gas ovèn	
Optional Accessories		• Chimney grid net, 400mm	PNC 206400
 Junction sealing kit 	PNC 206086	 Kit G.25.3 (NI) gas nozzles for 900 freestanding gas cookers on oven 	PNC 206458
 Draught diverter, 150 mm diameter 	PNC 206132	 Pressure regulator for gas units 	PNC 927225
 Matching ring for flue condenser, 150 mm diameter 	PNC 206133		
 4 wheels, 2 swivelling with brake (EV0700/900). It is mandatory to install with base supports for feet/wheels. 	PNC 206135		
 Flanged feet kit 	PNC 206136		
 Frontal kicking strip for concrete installation, 1200 mm 	PNC 206151		
 Frontal kicking strip for concrete installation, 1600 mm 	PNC 206152		
 Side handrail for right/left hand 	PNC 206165		
 Single burner radiant plate for pan support 	PNC 206170		
 Single burner smooth plate for direct cooking - fits frontal burners only 	PNC 206171		
 Single burner ribbed plate for direct cooking - fits frontal burners only 	PNC 206172		
 Frontal kicking strip, 1200 mm 	PNC 206178		
 Frontal kicking strip, 1600 mm 	PNC 206179		
 Pair of side kicking strips 	PNC 206180		
 2 panels for service duct (single installation) 	PNC 206181		
 Frontal handrail 1200 mm 	PNC 206191		
 Frontal handrail 1600 mm 	PNC 206192		
 2 panels for service duct (back to back installation) 	PNC 206202		
 Chrome grid for large oven 	PNC 206204		
 Pair of cast iron grids for gas ranges and boiling tops 	PNC 206208		
 4 feet for concrete installation (not for 900 line freestanding grill) 	PNC 206210		
 Flue condenser for 1 module, 150 mm diameter 	PNC 206246		
 Water column with swivel arm (water column extension not included) 	PNC 206289		
 Water column extension 	PNC 206290		
 Stainless steel grid for 2 burners 	PNC 206298		
 Chimney upstand, 1200 mm 	PNC 206306		
 2 side covering panels, height 700 mm, depth 900 mm 	PNC 206335		
 Wok pan support for open burners (EV0700/900) 	PNC 206363		
 Base support for feet or wheels - 1200mm (EVO700/EVO900) 	PNC 206368		
 Base support for feet or wheels - 1600mm (EV0700/900) 	PNC 206369		
 Base support for feet or wheels - 2000mm (EV0700/900) 	PNC 206370		






Modular Cooking Range Line EV0900 6-Burner Gas Range on Large Gas Oven





Gas connection



Gas

Gas Power: 56 kW

Standard gas delivery: Natural Gas G20 (20mbar)

Gas Type Option: LPG:Natural Gas

Gas Inlet: 1/2"

Key Information:

Oven working Temperature: 120 °C MIN; 280 °C MAX

Oven Cavity Dimensions (width): 1000 mm Oven Cavity Dimensions (height): 380 mm Oven Cavity Dimensions (depth): 700 mm Net weight: 200 kg Shipping weight: 196 ka Shipping height: 1080 mm Shipping width: 1020 mm Shipping depth: 1260 mm Shipping volume: 1.39 m³ **Front Burners Power:** 6 - 6 kW **Back Burners Power:** 10 - 10 kW Middle Burners Power: 6 - 0/6 - 0 kW **Certification group:** N9CG **Back Burners Dimension - mm** Ø 100 Ø 100 Front Burners Dimension - mm Ø 60 Ø 60 Middle Burners Dimension - mm Ø 60 Ø 60

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.



Modular Cooking Range Line EVO900 6-Burner Gas Range on Large Gas Oven