

**Modular Cooking Range Line  
EVO900 800mm Electric Fry Top,  
Smooth and Ribbed Brushed  
Chrome Sloped Plate**

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_

**392358 (Z9IIMDAOMEA)**

Full module electric fry top with 2/3 smooth and 1/3 ribbed brushed chrome cooking plate, sloped, thermostatic control, scraper included

**Short Form Specification****Item No.** \_\_\_\_\_

2/3 smooth and 1/3 ribbed cooking surface in brushed chrome. Temperature range from 120°C to 280°C. To be installed on open base installations, bridging supports or cantilever systems. Removable drawer below the cooking surface for the collection of grease and fat. Body and work top of unit entirely in stainless steel with Scotch Brite finish. Extra strength work top in heavy duty 2 mm stainless steel. Right-angled side edges to allow flush-fitting junction between units.

**Main Features**

- Large drain hole on cooking surface permits the draining of fat into large 1 liter collector placed under the cooking surface.
- Electric elements in incoloy positioned under the cooking plate.
- Safety thermostat and thermostatic control.
- Units have separate controls for each half module of the cooking surface.
- Stainless steel high splash guards on the rear and sides of cooking surface. Splash guards can be easily removed for cleaning and are dishwasher-safe.
- The special design of the control knob system guarantees against water infiltration.
- IPX5 water protection.
- Unit to be mounted on open base cupboards, bridging supports or cantilever systems.
- Temperature range from 120° up to 280°C.
- Rough brushed chrome surface is highly resistant to scratches and facilitates cleaning operations at the end of the day.
- Scrapers with smooth and ribbed blades included as standard.
- Suitable for countertop installation.

**Construction**

- All exterior panels in Stainless Steel with Scotch Brite finishing.
- AISI 304 stainless steel worktop, 2mm thick.
- Model has right-angled side edges to allow flush fitting joints between units, eliminating gaps and possible dirt traps.
- Unit is 900mm deep to give a larger working surface area.
- Cooking surface 15mm thick brushed chrome for optimum grilling results and ease of use.
- Cooking surface 2/3 smooth and 1/3 ribbed.



**APPROVAL:** \_\_\_\_\_

### Included Accessories

- 1 of Scraper for smooth plate for fry tops PNC 164255
- 1 of Scraper for ribbed plate fry tops - kit includes knife blades for both smooth and ribbed surface PNC 206420


### Optional Accessories

- |  |            |                          |
|--|------------|--------------------------|
| • Scraper for smooth plate for fry tops  | PNC 164255 | <input type="checkbox"/> |
| • Junction sealing kit   | PNC 206086 | <input type="checkbox"/> |
| • Support for bridge type installation, 800 mm   | PNC 206137 | <input type="checkbox"/> |
| • Support for bridge type installation, 1000 mm  | PNC 206138 | <input type="checkbox"/> |
| • Support for bridge type installation, 1200 mm  | PNC 206139 | <input type="checkbox"/> |
| • Support for bridge type installation, 1400 mm  | PNC 206140 | <input type="checkbox"/> |
| • Support for bridge type installation, 1600 mm  | PNC 206141 | <input type="checkbox"/> |
| • Side handrail for right/left hand  | PNC 206165 | <input type="checkbox"/> |
| • Frontal handrail 800 mm  | PNC 206167 | <input type="checkbox"/> |
| • Large handrail (portioning shelf) 800 mm   | PNC 206186 | <input type="checkbox"/> |
| • Frontal handrail 1200 mm   | PNC 206191 | <input type="checkbox"/> |
| • Frontal handrail 1600 mm   | PNC 206192 | <input type="checkbox"/> |
| • 2 side covering panels, height 250 mm, depth 900 mm  | PNC 206321 | <input type="checkbox"/> |
| • Grease/oil container kit for frytops   | PNC 206346 | <input type="checkbox"/> |
| • Base support for feet or wheels - 800mm (EVO700/900)   | PNC 206367 | <input type="checkbox"/> |
| • Chimney grid net, 400mm  | PNC 206400 | <input type="checkbox"/> |
| • Scraper for ribbed plate fry tops - kit includes knife blades for both smooth and ribbed surface | PNC 206420 | <input type="checkbox"/> |
| • Water drain for full module fry top  | PNC 216153 | <input type="checkbox"/> |

**Front**

**Side**


EI = Electrical inlet (power)

EQ = Equipotential screw

**Top**

**Electric**

Supply voltage: 380-400 V/3 ph/50-60 Hz

Predisposed for:

Total Watts: 15 kW

**Key Information:**

External dimensions, Width: 800 mm

External dimensions, Depth: 900 mm

External dimensions, Height: 250 mm

Net weight: 105 kg

Shipping weight: 98 kg

Shipping height: 530 mm

Shipping width: 1010 mm

Shipping depth: 860 mm

Shipping volume: 0.46 m<sup>3</sup>

If appliance is set up or next to or against temperature sensitive furniture or similar, a safety gap of approximately 150 mm should be maintained or some form of heat insulation fitted.