

Magistar Combi DS Electric Combi Oven 10GN1/1

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



218812 (ZCOE101B2C0)

Magistar Combi DS combi boiler oven with digital control, 10x1/1GN, electric, programmable, automatic cleaning

218822 (ZCOE101B2A0)

Magistar Combi DS combi boiler oven with digital control, 10x1/1GN, electric, programmable, automatic cleaning

Short Form Specification

Item No.

Combi oven with digital interface with guided selection

- Built-in steam generator with real humidity control based upon Lambda Sensor.
- AirFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- HP Automatic Cleaning: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual (steam, combi and convection cycles); EcoDelta cooking cycle; Regeneration cycle.
- Automatic backup mode to avoid downtime.
- $\hbox{-}\, {\sf USB}\, {\sf port}\, to\, download\, {\sf HACCP}\, {\sf data}, programs\, {\sf and}\, {\sf settings}.\, {\sf Connectivity}\, {\sf ready}.$
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Built-in steam generator for highly precise humidity and temperature control according to the chosen settings.
- Real humidity control based upon Lambda Sensor to automatically recognize quantity and size of food for consistent quality results.
- Dry, hot convection cycle (25 °C 300 °C): ideal for low humidity cooking.
- Combination cycle (25 °C 300 °C): combining convected heat and steam to obtain humidity controlled cooking environment, accelerating the cooking process and reducing weight loss.
- Low temperature Steam cycle (25 °C 99 °C): ideal for sous-vide, re-thermalization and delicate cooking. Steam cycle (100 °C): seafood and vegetables. High temperature steam (101 °C - 130 °C).
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Pre-set program for Regeneration, ideal for banqueting on plate or rethermalizing on tray.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- HP Automatic Cleaning: Automatic and built-in self cleaning system with integrated descale of the steam generator. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Grease Collector: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- 2 different chemical options available: solid and liquid (requires optional accessory).
- Capacity: 10 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.





Magistar Combi DS **Electric Combi Oven 10GN1/1**

- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.
- Integrated door shield to avoid steam and heat dispersion from the door, when the roll-in rack is not used.

User Interface & Data Management

- Digital interface with LED backlight buttons with guided selection.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).

Sustainability

 Reduced power function for customized slow cooking cycles.

PNC 864388

PNC 920004

PNC 920005

PNC 922003

PNC 922017

PNC 922036

PNC 922062

PNC 922086

PNC 922171

PNC 922189

Optional Accessories

- · External reverse osmosis filter for single tank Dishwashers with atmosphere boiler and Ovens (only for 218822
- Water filter with cartridge and flow meter for low steam usage (less than 2 hours of full steam per day) (only for 218822)
- · Water filter with cartridge and flow meter for medium steam usage (only for 218822)
- Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) (only for 218822)
- · Pair of AISI 304 stainless steel grids, GN 1/1 (only for 218822)
- Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 (only for 218822)
- AISI 304 stainless steel grid, GN 1/1 (only for 218822)
- Grid for whole chicken (4 per grid -1,2kg each), GN 1/2 (only for 218822)
- External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) (only for 218822)
- Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm (only for
- · Baking tray with 4 edges in perforated PNC 922190 aluminum, 400x600x20mm (only for 218822)
- Baking tray with 4 edges in aluminum, PNC 922191 400x600x20mm (only for 218822)
- Pair of frying baskets (only for 218822) PNC 922239
- AISI 304 stainless steel bakery/pastry PNC 922264 grid 400x600mm (only for 218822)
- Double-step door opening kit (only for PNC 922265 218822)
- Grid for whole chicken (8 per grid -PNC 922266 1,2kg each), GN 1/1 (only for 218822)

 Grease collection tray, GN 1/1, H=100 mm PNC 922321 (only for 218822)

 \Box

- Kit universal skewer rack and 4 long PNC 922324 skewers for GN 1/1 ovens (only for 218822)
- PNC 922326 Universal skewer rack (only for 218822)
- 4 long skewers (only for 218822) PNC 922327 PNC 922348 Multipurpose hook (only for 218822)
- 4 flanged feet for 6 & 10 GN, 2", PNC 922351 100-130mm (only for 218822) Grid for whole duck (8 per grid - 1,8kg PNC 922362
- each), GN 1/1 (only for 218822) Thermal cover for 10 GN 1/1 oven and PNC 922364
- blast chiller freezer (only for 218822) Tray support for 6 & 10 GN 1/1 PNC 922382 \Box disassembled open base (only for 218822)
- Wall mounted detergent tank holder (only PNC 922386 for 218822)
- USB single point probe (only for 218822) PNC 922390 IoT module for OnE Connected and Match PNC 922421
- (one IoT board per appliance to connect oven to the blast chiller for Cook&Chill process). (only for 218822)
- Connectivity router (WiFi and LAN) (only PNC 922435 for 218822)
- Grease collection kit for ovens GN 1/1 & PNC 922438 2/1 (2 plastic tanks, connection valve with pipe for drain) (only for 218822)
- Tray rack with wheels, 10 GN 1/1, 65mm PNC 922601 pitch (only for 218822)
- Tray rack with wheels 8 GN 1/1, 80mm PNC 922602 pitch (only for 218822)
- Bakery/pastry tray rack with wheels PNC 922608 400x600mm for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners)
- (only for 218822) Slide-in rack with handle for 6 & 10 GN PNC 922610 1/1 oven (only for 218822)
- Open base with tray support for 6 & 10 PNC 922612 GN 1/1 oven (only for 218822) • Cupboard base with tray support for 6 & PNC 922614
- 10 GN 1/1 oven (only for 218822) Hot cupboard base with tray support for 6 PNC 922615
- & 10 GN 1/1 oven holding GN 1/1 or400x600mm (only for 218822)
- External connection kit for liquid detergent PNC 922618 and rinse aid (only for 218822) • Grease collection kit for GN 1/1-2/1 PNC 922619
- cupboard base (trolley with 2 tanks, open/ close device for drain) (only for 218822) • Stacking kit for 6+6 GN 1/1 ovens on PNC 922620 electric 6+10 GN 1/1 GN ovens (only for
- 218822) Trolley for slide-in rack for 6 & 10 GN 1/1 PNC 922626 oven and blast chiller freezer (only for
- Trolley for mobile rack for 6 GN 1/1 on 6 PNC 922630 or 10 GN 1/1 ovens (only for 218822)
- Stainless steel drain kit for 6 & 10 GN PNC 922636 oven, dia=50mm (only for 218822)
- Plastic drain kit for 6 &10 GN oven, PNC 922637 dia=50mm (only for 218822)













Magistar Combi DS Electric Combi Oven 10GN1/1

•	Trolley with 2 tanks for grease collection (only for 218822)	PNC 922638	-	6	Condensation hood with fan for stacking 6+6 or 6+10 GN 1/1 electric ovens (only	PNC 922727	
•	Grease collection kit for GN 1/1-2/1 open base (2 tanks, open/close device for drain) (only for 218822)	PNC 922639		• E	or 218822) Exhaust hood with fan for 6 & 10 GN 1/1 ovens (only for 218822)	PNC 922728	
•	Wall support for 10 GN 1/1 oven (only for 218822)	PNC 922645	_ ·	• E	Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens (only for 218822)	PNC 922732	
•	Banquet rack with wheels holding 30 plates for 10 GN 1/1 oven and blast	PNC 922648	_ ·	• E	Exhaust hood without fan for 6&10 1/1GN ovens (only for 218822)	PNC 922733	
	chiller freezer, 65mm pitch (only for 218822)		•		Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens (only for 218822)	PNC 922737	
•	Banquet rack with wheels holding 23 plates for 10 GN 1/1 oven and blast	PNC 922649	•		Fixed tray rack, 8 GN 1/1, 85mm pitch only for 218822)	PNC 922741	
	chiller freezer, 85mm pitch (only for 218822)				Fixed tray rack, 8 GN 2/1, 85mm pitch only for 218822)	PNC 922742	
	Dehydration tray, GN 1/1, H=20mm (only for 218822)	PNC 922651			4 high adjustable feet for 6 & 10 GN ovens, 230-290mm (only for 218822)	PNC 922745	
	218822)	PNC 922652			Tray for traditional static cooking, H=100mm (only for 218822)	PNC 922746	
•	Open base for 6 & 10 GN 1/1 oven, disassembled - NO accessory can be fitted with the exception of 922382 (only for 218822)	PNC 922653		C	Double-face griddle, one side ribbed and one side smooth, 400x600mm (only for 218822)	PNC 922747	
•	Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and	PNC 922656	Ц	2	Trolley for grease collection kit (only for 218822)	PNC 922752	
	80mm pitch (only for 218822) Heat shield for stacked ovens 6 GN	PNC 922661		2	218822)	PNC 922773	
	1/1 on 10 GN 1/1 (only for 218822) Heat shield for 10 GN 1/1 oven (only	PNC 922663		n	Kit for installation of electric power peak management system for 6 GN and 10 GN	PNC 922774	
	for 218822) Fixed tray rack for 10 GN 1/1 and	PNC 922685		• 1	ovens (only for 218822) Non-stick universal pan, GN 1/1, H=20mm	PNC 925000	
	400x600mm grids (only for 218822) Kit to fix oven to the wall (only for	PNC 922687		• 1	only for 218822) Non-stick universal pan, GN 1/ 1,	PNC 925001	
	218822)			• 1	H=40mm (only for 218822) Non-stick universal pan, GN 1/1, H=60mm	PNC 925002	
	4 high adjustable feet for 6 & 10 GN ovens, 100-115MM (only for 218822)	PNC 922688		•	only for 218822) Double-face griddle, one side ribbed and	PNC 925003	
	Tray support for 6 & 10 GN 1/1 oven base (only for 218822)	PNC 922690	u	C	one side smooth, GN 1/1 (only for 218822)		
	Reinforced tray rack with wheels, owest support dedicated to a grease collection tray for 10 GN 1/1 oven, 64mm pitch (only for 218822)	PNC 922694	•		Aluminum grill, GN 1/1 (only for 218822)	PNC 925004 PNC 925005	
				h	Frying pan for 8 eggs, pancakes, namburgers, GN 1/1 (only for 218822)		
•	Detergent tank holder for open base (only for 218822)	PNC 922699	_	(Flat baking tray with 2 edges, GN 1/1 only for 218822)	PNC 925006	_
•	Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base (only for	PNC 922702	_	f	for 218822)	PNC 925007	_
•	218822) Wheels for stacked ovens (only for	PNC 922704	П	(Potato baker for 28 potatoes, GN 1/1 (only for 218822)	PNC 925008	
	218822) Spit for lamb or suckling pig (up to	PNC 922709	<u> </u>		Non-stick universal pan, GN 1/2, H=20mm (only for 218822)	PNC 925009	
	12kg) for GN 1/1 ovens (only for 218822)		- •		Non-stick universal pan, GN 1/2, H=40mm (only for 218822)	PNC 925010	
•	Mesh grilling grid, GN 1/1 (only for 218822)	PNC 922713	_	(Non-stick universal pan, GN 1/2, H=60mm (only for 218822)	PNC 925011	
•	Probe holder for liquids (only for 218822)	PNC 922714	<u> </u>	• (Compatibility kit for installation on orevious base GN 1/1 (only for 218822)	PNC 930217	
•	Odour reduction hood with fan for 6 & 10 GN 1/1 electric ovens (only for 218822)	PNC 922718					
•	Odour reduction hood with fan for 6+6 or 6+10 GN 1/1 electric ovens (only for 218822)	PNC 922722					
•	Condensation hood with fan for 6 & 10 GN 1/1 electric oven (only for 218822)	PNC 922723					












Magistar Combi DS Electric Combi Oven 10GN1/1

D 778 mm 12 11/16 ' 322 mm 2 5/16 "

Side

Front




C- = Cold Water inlet 1 WI- (cleaning)

EI = Electrical inlet (power)

= Cold Water Inlet 2 WI-(steam generator)

D = Drain

DO = Overflow drain pipe



Electric

Circuit breaker required

Supply voltage:

218812 (ZCOE101B2C0) 220-240 V/3 ph/50-60 Hz 218822 (ZCOE101B2A0) 380-415 V/3N ph/50-60 Hz

Electrical power, max: 20.3 kW Electrical power, default: 19 kW

Water:

Inlet water temperature,

30 °C max:

Inlet water pipe size (CWI1,

CWI2): 3/4" Pressure, min-max: 1-6 bar **Chlorides:** <45 ppm **Conductivity:** >50 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and right Clearance: hand sides.

Suggested clearance for

50 cm left hand side. service access:

Capacity:

Trays type: 10 (GN 1/1) Max load capacity: 50 kg

Key Information:

Door hinges: Right Side

External dimensions,

Width: 867 mm

External dimensions,

775 mm Depth:

External dimensions,

1058 mm Height: Weight: 138 ka 138 kg

Net weight:

Shipping weight: 218812 (ZCOE101B2C0) 156 kg

218822 (ZCOE101B2A0) 155 kg

Shipping volume:

218812 (ZCOE101B2C0) 1.04 m³ 218822 (ZCOE101B2A0) 1.11 m³

Magistar Combi DS Electric Combi Oven 10GN1/1









