

ITEM #	
MODEL #	
NAME #	
SIS #	
AIA#	



218912 (ZCOE101C2C0)

Magistar Combi DI combi boilerless oven with digital control, 10x1/1GN, electric, programmable, automatic cleaning

218922 (ZCOE101C2A0)

Magistar Combi DI combi boilerless oven with digital control, 10x1/1GN, electric, programmable, automatic cleaning

Short Form Specification

Item No.

Combi oven with digital interface with guided selection.

- Boilerless steaming function to add and retain moisture.
- AirFlow air distribution system to achieve maximum performance with 5 fan speed levels.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Cooking modes: Programs (a maximum of 100 recipes can be stored); Manual;
 EcoDelta cooking cycle.
- Automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings. Connectivity ready.
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Boilerless steaming function to add and retain moisture for high quality, consistent cooking results.
- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Programs mode: a maximum of 100 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 4-step cooking programs also available.
- AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
- Fan with 5 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- Automatic fast cool down and pre-heat function.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only).
- Grease Collector: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- 2 different chemical options available: solid and liquid (requires optional accessory).
- Capacity: 10 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Hygienic internal chamber with all rounded corners for easy cleaning.
- · 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.
- Integrated door shield to avoid steam and heat dispersion from the door, when the roll-in rack is not used. (only for 218922)

User Interface & Data Management

- Digital interface with LED backlight buttons with guided selection.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plug-in sous-vide probe (optional accessory).



Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).











	Optional Accessories Water filter with cartridge and flow	PNC 920004	•	IoT module for OnE Connected and Match (one IoT board per appliance - to connect oven to the blast chiller for Cook&Chill process). (only for 218922)	PNC 922421	
	meter for low steam usage (less than 2 hours of full steam per day) (only for 218922)		•	Connectivity router (WiFi and LAN) (only for 218922)	PNC 922435	
•	Water filter with cartridge and flow meter for medium steam usage (only for 218922)	PNC 920005	•	Grease collection kit for ovens GN 1/1 & 2/1 (2 plastic tanks, connection valve with pipe for drain) (only for 218922)	PNC 922438	
•	Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the	PNC 922003		Tray rack with wheels, 10 GN 1/1, 65mm pitch (only for 218922)	PNC 922601	
•	disassembled one) (only for 218922) Pair of AISI 304 stainless steel grids, GN 1/1 (only for 218922)	PNC 922017		Tray rack with wheels 8 GN 1/1, 80mm pitch (only for 218922)	PNC 922602	
•	Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 (only for 218922)	PNC 922036	•	Bakery/pastry tray rack with wheels 400x600mm for 10 GN 1/1 oven and blast chiller freezer, 80mm pitch (8 runners) (only for 218922)	PNC 922608	
•	AISI 304 stainless steel grid, GN 1/1 (only for 218922)	PNC 922062	•	Slide-in rack with handle for 6 & 10 GN 1/1 oven (only for 218922)	PNC 922610	
•	Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 (only for 218922)	PNC 922086	•	Open base with tray support for 6 & 10 GN 1/1 oven (only for 218922)	PNC 922612	
•	External side spray unit (needs to be mounted outside and includes support	PNC 922171	•	Cupboard base with tray support for 6 & 10 GN 1/1 oven (only for 218922)	PNC 922614	
•	to be mounted on the oven) (only for 218922) Baking tray for 5 baguettes in	PNC 922189	•	Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or400x600mm (only for 218922)	PNC 922615	
	perforated aluminum with silicon coating, 400x600x38mm (only for		•	External connection kit for liquid detergent and rinse aid (only for 218922)	PNC 922618	
•	218922) Baking tray with 4 edges in perforated aluminum, 400x600x20mm (only for 218922)	PNC 922190	•	Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/close device for drain) (only for 218922)	PNC 922619	
•	Baking tray with 4 edges in aluminum, 400x600x20mm (only for 218922)	PNC 922191	•	Stacking kit for 6+6 GN 1/1 ovens on electric 6+10 GN 1/1 GN ovens (only for 218922)	PNC 922620	
•	Pair of frying baskets (only for 218922)	PNC 922239	•	Trolley for slide-in rack for 6 & 10 GN 1/1	PNC 922626	
•	AISI 304 stainless steel bakery/pastry grid 400x600mm (only for 218922)	PNC 922264		oven and blast chiller freezer (only for 218922)		
•	Double-step door opening kit (only for 218922)	PNC 922265	•	Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens (only for 218922)	PNC 922630	
•	Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 (only for 218922)	PNC 922266	•	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm (only for 218922)	PNC 922636	
•	Grease collection tray, GN 1/1, H=100 mm (only for 218922)	PNC 922321	•	Plastic drain kit for 6 &10 GN oven, dia=50mm (only for 218922)	PNC 922637	
•	Kit universal skewer rack and 4 long skewers for GN 1/1 ovens (only for	PNC 922324	•	Trolley with 2 tanks for grease collection (only for 218922)	PNC 922638	
•	218922) Universal skewer rack (only for 218922)	PNC 922326	•	Grease collection kit for GN 1/1-2/1 open base (2 tanks, open/close device for drain) (only for 218922)	PNC 922639	
	4 long skewers (only for 218922)	PNC 922327	•	Wall support for 10 GN 1/1 oven (only for 218922)	PNC 922645	
	Multipurpose hook (only for 218922) 4 flanged feet for 6 & 10 GN, 2", 100-130mm (only for 218922)	PNC 922348 PNC 922351	•	Banquet rack with wheels holding 30 plates for 10 GN 1/1 oven and blast chiller	PNC 922648	
•	Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 (only for 218922)	PNC 922362	•	freezer, 65mm pitch (only for 218922) Banquet rack with wheels holding 23	PNC 922649	
•	Thermal cover for 10 GN 1/1 oven and blast chiller freezer (only for 218922)	PNC 922364		plates for 10 GN 1/1 oven and blast chiller freezer, 85mm pitch (only for 218922)		
•	Tray support for 6 & 10 GN 1/1 disassembled open base (only for	PNC 922382		Dehydration tray, GN 1/1, H=20mm (only for 218922) Flat dehydration tray, GN 1/1 (only for	PNC 922651 PNC 922652	
•	218922) Wall mounted detergent tank holder	PNC 922386		218922) Open base for 6 & 10 GN 1/1 oven,	PNC 922653	_
•	(only for 218922) USB single point probe (only for 218922)	PNC 922390	•	disassembled - NO accessory can be fitted with the exception of 922382 (only for 218922)	. 140 022000	J











•	Bakery/pastry rack kit for 10 GN 1/1 oven with 8 racks 400x600mm and	PNC 922656	•	Trolley for grease collection kit (only for 218922)	PNC 922752	
	80mm pitch (only for 218922) Heat shield for stacked ovens 6 GN	PNC 922661	•	Water inlet pressure reducer (only for 218922)	PNC 922773	
	1/1 on 10 GN 1/1 (only for 218922)		•	Kit for installation of electric power peak management system for 6 GN and 10 GN	PNC 922774	
	Heat shield for 10 GN 1/1 oven (only for 218922)	PNC 922663		ovens (only for 218922)	DNO 005000	
•	Fixed tray rack for 10 GN 1/1 and 400x600mm grids (only for 218922)	PNC 922685	_	Non-stick universal pan, GN 1/1, H=20mm (only for 218922)		
•	Kit to fix oven to the wall (only for 218922)	PNC 922687	•	Non-stick universal pan, GN 1/1, H=40mm (only for 218922)	PNC 925001	
•	4 high adjustable feet for 6 & 10 GN ovens, 100-115MM (only for 218922)	PNC 922688	•	Non-stick universal pan, GN 1/1, H=60mm (only for 218922)	PNC 925002	
•	Tray support for 6 & 10 GN 1/1 oven base (only for 218922)	PNC 922690	•	Double-face griddle, one side ribbed and one side smooth, GN 1/1 (only for 218922)	PNC 925003	
•	Reinforced tray rack with wheels, lowest support dedicated to a grease	PNC 922694	•	•	PNC 925004	
	collection tray for 10 GN 1/1 oven, 64mm pitch (only for 218922)			Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1 (only for 218922)	PNC 925005	
•	Detergent tank holder for open base (only for 218922)	PNC 922699	•	Flat baking tray with 2 edges, GN 1/1 (only for 218922)	PNC 925006	
•	Bakery/pastry runners 400x600mm for 6 & 10 GN 1/1 oven base (only for	PNC 922702	•	· · ·	PNC 925007	
	218922) Wheels for stacked ovens (only for	PNC 922704	•	Potato baker for 28 potatoes, GN 1/1 (only for 218922)	PNC 925008	
	218922)		•	Non-stick universal pan, GN 1/2, H=20mm	PNC 925009	
•	Spit for lamb or suckling pig (up to 12kg) for GN 1/1 ovens (only for 218922)	PNC 922709	•	(only for 218922) Non-stick universal pan, GN 1/2, H=40mm	PNC 925010	
•	Mesh grilling grid, GN 1/1 (only for 218922)	PNC 922713	•	(only for 218922) Non-stick universal pan, GN 1/2, H=60mm	PNC 925011	
•	Probe holder for liquids (only for 218922)	PNC 922714	•	(only for 218922) Compatibility kit for installation on previous base GN 1/1 (only for 218922)	PNC 930217	
•	,	PNC 922718		previous base GIV I/1 (GIIIy IOI 216922)		
•	Odour reduction hood with fan for 6+6 or 6+10 GN 1/1 electric ovens (only for 218922)	PNC 922722				
•	Condensation hood with fan for 6 & 10 GN 1/1 electric oven (only for 218922)	PNC 922723				
•	Condensation hood with fan for stacking 6+6 or 6+10 GN 1/1 electric ovens (only for 218922)	PNC 922727				
•	Exhaust hood with fan for 6 & 10 GN 1/1 ovens (only for 218922)	PNC 922728				
•	Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens (only for 218922)	PNC 922732				
•	Exhaust hood without fan for 6&10 1/1GN ovens (only for 218922)	PNC 922733				
•	The state of the s	PNC 922737				
•	Fixed tray rack, 8 GN 1/1, 85mm pitch (only for 218922)	PNC 922741				
•	Fixed tray rack, 8 GN 2/1, 85mm pitch (only for 218922)	PNC 922742				
•	4 high adjustable feet for 6 & 10 GN ovens, 230-290mm (only for 218922)	PNC 922745				
•	Tray for traditional static cooking, H=100mm (only for 218922)	PNC 922746				
•	Double-face griddle, one side ribbed and one side smooth, 400x600mm (only for 218922)	PNC 922747				














D 778 mm 12 11/16 ' 322 mm 2 5/16 "

Side

Front




 Cold Water inlet 1 WI- (cleaning)

EI = Electrical inlet (power)

= Cold Water Inlet 2 WI-(steam generator)

D = Drain

DO = Overflow drain pipe



Electric

Circuit breaker required

Supply voltage:

218912 (ZCOE101C2C0) 220-240 V/3 ph/50-60 Hz 218922 (ZCOE101C2A0) 380-415 V/3N ph/50-60 Hz

Electrical power, max: 20.3 kW Electrical power, default: 19 kW

Water:

Inlet water temperature,

30 °C max:

Inlet water pipe size (CWI1,

CWI2): 3/4" Pressure, min-max: 1-6 bar **Chlorides:** <10 ppm **Conductivity:** >50 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and right Clearance:

hand sides.

Suggested clearance for service access:

50 cm left hand side.

Capacity:

Trays type: 10 (GN 1/1) Max load capacity: 50 kg

Key Information:

Door hinges: Right Side

External dimensions,

Width: 867 mm

External dimensions,

775 mm Depth:

External dimensions,

1058 mm Height: Weight: 127 kg Net weight: 127 kg **Shipping weight:** 144 kg

Shipping volume:

218912 (ZCOE101C2C0) 1.04 m³ 218922 (ZCOE101C2A0) 1.06 m³

Magistar Combi DI Electric Combi Oven 10GN1/1





