

## Eazy Electric Convection Oven 6GN 1/1 with Cleaning System

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_



**240008 (ZCD061WL)**

Compact Eazy, electric, 6x1/1GN, convection oven with direct steam and 11 humidity level settings, with automatic cleaning, left-hinged door

**240010 (ZCD061WR)**

Compact Eazy, electric, 6x1/1GN, convection oven with direct steam and 11 humidity level settings, with automatic cleaning, right-hinged door

### Short Form Specification

Item No. \_\_\_\_\_

Convection oven with direct steam: 90% steam saturation.  
Cooking cycles: hot air (max 280 °C) combined with 11 different humidity settings, ranging from browning to baking and par-steaming. Programmability: 99 free recipes with 9-step cooking. Variable fan speed with 3 levels. Double-glass door with book-like opening maintains a cool external temperature and incorporates a drip pan to collect excess condensation avoiding wet floors. Halogen lighting in the cooking chamber. Door, front panel and interior in AISI 304 stainless steel.  
Supplied with n.1 tray rack 1/1GN, 30mm pitch.

### Main Features

- Dry hot convection cycle (max 280 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation:
  - 0 = no additional moisture (browning, au gratin, baking, pre-cooked food)
  - 1-2 = low moisture (small portions of meat and fish)
  - 3-4 = medium low moisture (large pieces of meat, reheating, roasted chicken and proving)
  - 5-6 = medium moisture (roasted vegetable and first step of roasted meat & fish)
  - 7-8 = medium-high moisture (stewed vegetables)
  - 9-10 = high moisture (poached meat and jacket potatoes)
- Programmability: a maximum of 99 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. 9-step cooking programs also available.
- Eco-delta: the temperature inside the cooking cell is higher than the temperature of the food and rises accordingly.
- Automatic cleaning system: 3 different pre-set cycles to clean the cooking cell, according to the actual requirements. The cleaning system is built-in (no need for add-ons).
- Automatic and manual rapid cooling activation when going from a higher to a lower temperature.
- Exhaust valve electronically controlled to extract humidity in excess for extra crispy results.
- USB connection: to download HACCP data, upload/download the recipes.
- Variable fan speed with 3 levels.

### Construction


- Hygienic internal chamber with all rounded corners for easy cleaning.
- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning.
- Swing hinged front panel for easy service access to main components.
- IPx4 water protection.

APPROVAL: \_\_\_\_\_


## Optional Accessories

- |  |            |                          |
|--|------------|--------------------------|
| • Pair of AISI 304 stainless steel grids, GN 1/1                   | PNC 922017 | <input type="checkbox"/> |
| • Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2         | PNC 922086 | <input type="checkbox"/> |
| • Pair of frying baskets   | PNC 922239 | <input type="checkbox"/> |
| • Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1         | PNC 922266 | <input type="checkbox"/> |
| • Base support for stacked compact ovens                           | PNC 922368 | <input type="checkbox"/> |
| • Open base for compact 6x1/1GN oven                               | PNC 922369 | <input type="checkbox"/> |
| • Tray support for compact 6x1/1GN oven - open base                | PNC 922370 | <input type="checkbox"/> |
| • Stacking kit for compact 6x1/1GN oven                            | PNC 922371 | <input type="checkbox"/> |
| • External spray unit for compact 6x1/1GN oven                     | PNC 922372 | <input type="checkbox"/> |
| • 1-sensor core probe for compact 6x1/1GN oven                     | PNC 922373 | <input type="checkbox"/> |
| • Right-hinged door for compact 6x1/1GN oven (only for 240008)     | PNC 922376 | <input type="checkbox"/> |
| • Double-step door for opening compact 6x1/1GN oven                | PNC 922377 | <input type="checkbox"/> |
| • Kit to front air filter for compact 6x1/1GN oven                 | PNC 922379 | <input type="checkbox"/> |
| • Water inlet pressure reducer                                     | PNC 922773 | <input type="checkbox"/> |
| • Non-stick universal pan, GN 1/1, H=20mm                          | PNC 925000 | <input type="checkbox"/> |
| • Non-stick universal pan, GN 1/1, H=40mm                          | PNC 925001 | <input type="checkbox"/> |
| • Non-stick universal pan, GN 1/1, H=60mm                          | PNC 925002 | <input type="checkbox"/> |
| • Double-face griddle, one side ribbed and one side smooth, GN 1/1 | PNC 925003 | <input type="checkbox"/> |
| • Aluminum grill, GN 1/1   | PNC 925004 | <input type="checkbox"/> |
| • Frying pan for 8 eggs, pancakes, hamburgers, GN 1/1              | PNC 925005 | <input type="checkbox"/> |
| • Flat baking tray with 2 edges, GN 1/1                            | PNC 925006 | <input type="checkbox"/> |
| • Baking tray for 4 baguettes, GN 1/1                              | PNC 925007 | <input type="checkbox"/> |
| • Non-stick universal pan, GN 1/2, H=20mm                          | PNC 925009 | <input type="checkbox"/> |
| • Non-stick universal pan, GN 1/2, H=40mm                          | PNC 925010 | <input type="checkbox"/> |
| • Non-stick universal pan, GN 1/2, H=60mm                          | PNC 925011 | <input type="checkbox"/> |

**Front**




**Side**



- CW1** = Cold Water inlet 1 (cleaning)
- CW2** = Cold Water Inlet 2 (steam generator)
- D** = Drain
- EI** = Electrical inlet (power)

**Top**



**Electric**

**Supply voltage:**

240008 (ZCD061WL)	380-415 V/3N ph/50/60 Hz
240010 (ZCD061WR)	400 V/3N ph/50/60 Hz

**Electrical power max.:**

6.9 kW

**Circuit breaker required**

**Water:**

**Total hardness:** 5-50 ppm

**Electrolux Professional** recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

**Drain "D":** 40mm

**Water inlet "CW" connection:** 3/4"

**Pressure, bar min/max:** 1.5-3 bar

**Installation:**

**Clearance:** 5 cm rear and right hand sides.

**Suggested clearance for service access:**

50 cm left hand side.

**Capacity:**

**Max load capacity:** 12 kg

**Trays type:** 6 - 1/1 Gastronorm

**Key Information:**

**External dimensions, Width:** 519 mm

**External dimensions, Depth:** 803 mm

**External dimensions, Height:** 770 mm

**Net weight:**

240008 (ZCD061WL)	72 kg
240010 (ZCD061WR)	85 kg

**Shipping weight:**

240008 (ZCD061WL)	85 kg
240010 (ZCD061WR)	83 kg

**Shipping volume:** 0.66 m<sup>3</sup>