

## Water Treatment External manual water softener, 12lt

ITEM # \_\_\_\_\_

MODEL # \_\_\_\_\_

NAME # \_\_\_\_\_

SIS # \_\_\_\_\_

AIA # \_\_\_\_\_

**860412 (ADM)**External manual water  
softener - 12 lt

### Short Form Specification

**Item No.** \_\_\_\_\_

Designed specifically for single tank dishwashers such as undercounter, glasswasher and hood type models.

Routine regeneration is recommended to suit the use of water softener and the hardness of the water used.

Operating pressure between 1 and 8 bar.

Incorporates 12-litre cylinder in stainless steel 304 AISI.

Flow rate 1000l/h.

Every regeneration cycle requires 1,5kg of salt.

Water connection between 5°C to 15°C.

### Main Features

- Operating pressure between 1 and 8 bars.
- Water connection between 4°C and 15°C.
- Quantity of soft water depending on supply water hardness:
  - 30°F (16,5°d) - 1500lt
  - 40°F (22°d) - 1350lt
  - 60°F (33°d) - 1050lt
  - 80°F (44°d) - 750lt

### Construction

- Flow rate 1000 l/h.
- Incorporates 12 litre cylinder in stainless steel 304 AISI.

### Sustainability

- Every regeneration cycle requires 1,5 kg of salt.

**APPROVAL:** \_\_\_\_\_

**Key Information:****External dimensions,  
Width:****860412 (ADM)** 190 mm**External dimensions,  
Depth:**

190 mm

**External dimensions,  
Height:**

515 mm

**Net weight:**

19 kg

**Shipping height:**

23 5/8" (600 mm)

**Packaging size  
(WxDxH):**

190x190x510 mm