

Water Treatment External manual water softener, 20lt

ITEM # _____

MODEL # _____

NAME # _____

SIS # _____

AIA # _____

**860430 (ADM2)**External manual water
softener - 20 lt

Short Form Specification

Item No. _____

Designed specifically for single tank dishwashers such as undercounter, glasswasher and hood type models.

Routine regeneration is recommended to suit the use of water softener and the hardness of the water used.

Operating pressure between 1 and 8 bar.

Incorporates 12-litre cylinder in stainless steel 304 AISI.

Flow rate 1000l/h.

Every regeneration cycle requires 1,5kg of salt.

Water connection between 5°C to 15°C.

Main Features

- Operating pressure between 1 and 8 bars.
- Water connection between 4°C and 15°C.
- Quantity of soft water depending on supply water hardness:
 - 30°f (16,5°d) - 3000lt
 - 40°f (22°d) - 2000lt
 - 60°f (33°d) - 2100lt
 - 80°f (44°d) - 1500lt

Construction

- Incorporates 20 litre cylinder in stainless steel 304 AISI.
- Flow rate 1000 l/h.

Sustainability

- Every regeneration cycle requires 1,5 kg of salt.

APPROVAL: _____



Water Treatment External manual water softner, 20lt

Key Information:

**External dimensions,
Width:**

860430 (ADM2) 190 mm

**External dimensions,
Depth:**

190 mm

**External dimensions,
Height:**

900 mm

Net weight:

19 kg

Shipping height:

37 3/8" (950 mm)

**Packaging size
(WxDxH):**

190x190x900 mm

**Water Treatment
External manual water softner, 20lt**

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

2025.02.14

