

ITEM#		
MODEL #		
NAME #		
SIS#		
AIA#		



218680 (ZCOG61K2G0)

Magistar Combi TI combi boilerless oven with touch screen control, 6x1/1GN, gas, 2 cooking modes (recipe program, manual), automatic cleaning

225670 (ZCOG61K2G6)

Magistar Combi TI combi boilerless oven with touch screen control, 6x1/1GN, gas, 2 cooking modes (recipe program, manual), automatic cleaning

Short Form Specification

Item No.

Combi oven with high resolution full touch screen interface, multilanguage.

- Boilerless steaming function to add and retain moisture.
- AirFlow air distribution system to achieve maximum performance with 7 fan speed levels.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and economizer functions to save energy, water, detergent and rinse aid.
- Cooking modes: Programs (a maximum of 1000 recipes can be stored and organized in 16 different categories); Manual; EcoDelta cooking cycle.
- Special functions: MultiTimer cooking, Cooking Optimizer to cut running costs, Make-it-Mine to customize interface, SoloMio to customize homepage, agenda Calendar, automatic backup mode to avoid downtime.
- USB port to download HACCP data, programs and settings. Connectivity ready.
- Single sensor core temperature probe.
- Double-glass door with LED lights.
- Stainless steel construction throughout.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.

Main Features

- Boilerless steaming function to add and retain moisture for high quality, consistent cooking results.
- Dry hot convection cycle (max 300 °C) ideal for low humidity cooking. Automatic moistener (11 settings) for boiler-less steam generation.
- EcoDelta cooking: cooking with food probe maintaining preset temperature difference between the core of the food and the cooking chamber.
- Programs mode: a maximum of 1000 recipes can be stored in the oven's memory, to recreate the exact same recipe at any time. The recipes can be grouped in 16 different categories to better organize the menu. 16-step cooking programs also available.
- MultiTimer function to manage up to 60 different cooking cycles at the same time, improving flexibility and ensuring excellent cooking results. Can be saved up to 200 MultiTimer programs.
- AirFlow air distribution system to achieve maximum performance in chilling/heating evenness and temperature control thanks to a special design of the chamber combined with high precision variable speed fan.
- Fan with 7 speed levels from 300 to 1500 RPM and reverse rotation for optimal evenness. Fan stops in less than 5 seconds when door is opened.
- Single sensor core temperature probe included.
- · Automatic fast cool down and pre-heat function.
- Grease Collector: predisposed for integrated grease drain and collection for safer operation (dedicated base as optional accessory).
- Back-up mode with self-diagnosis is automatically activated if a failure occurs to avoid downtime.
- 2 different chemical options available: solid and liquid (requires optional accessory).
- Capacity: 6 GN 1/1 trays.
- OptiFlow air distribution system to achieve maximum performance in chilling/heating eveness and temperature control thanks to a special design of the chamber.

Construction

- Double thermo-glazed door with open frame construction, for cool outside door panel. Swing hinged easy-release inner glass on door for easy cleaning
- Hygienic internal chamber with all rounded corners for easy cleaning.
- 304 AISI stainless steel construction throughout.
- Front access to control board for easy service.
- IPX5 spray water protection certification for easy cleaning.
- Supplied with n.1 tray rack 1/1 GN, 67 mm pitch.
- Integrated door shield to avoid steam and heat dispersion from the door, when the roll-in rack is not used.

User Interface & Data Management

 High resolution full touch screen interface (translated in more than 30 languages) - color-blind friendly panel.



- Pictures upload for full customization of cooking cycles.
- Make-it-mine feature to allow full personalization or locking of the user interface.
- SoloMio lets the user group the favorite functions in the homepage for immediate access.
- Calendar works as an agenda where the user can plan the daily work and receive personalized alerts for each task.
- USB port to download HACCP data, share cooking programs and configurations. USB port also allows to plugin sous-vide probe (optional accessory).
- Connectivity ready for real time access to connected appliances from remote and HACCP monitoring (requires optional accessory).
- Trainings and guidances supporting materials easily accessible by scanning QR-Code with any mobile device.
- Automatic consumption visualization at the end of the cycle.

Sustainability

- Reduced power function for customized slow cooking cycles.
- HP Automatic Cleaning: Automatic and built-in self cleaning system. 5 automatic cycles (soft, medium, strong, extra strong, rinse-only) and green functions to save energy, water, detergent and rinse aid. Also programmable with delayed start.
- Cooking Optimizer function organizes the cooking sequence of the chosen cycles optimizing the work in the kitchen from a time and energy efficiency point of view.

Optional Accessories

eptional Accessories		
 Water filter with cartridge and flow meter for low steam usage (less than 2 hours of full steam per day) 	PNC 920004	
Water filter with cartridge and flow meter for medium steam usage	PNC 920005	
 Wheel kit for 6 & 10 GN 1/1 and 2/1 GN oven base (not for the disassembled one) 	PNC 922003	
 Pair of AISI 304 stainless steel grids, GN 1/1 	PNC 922017	
 Pair of grids for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922036	
 AISI 304 stainless steel grid, GN 1/1 	PNC 922062	
 Grid for whole chicken (4 per grid - 1,2kg each), GN 1/2 	PNC 922086	
 External side spray unit (needs to be mounted outside and includes support to be mounted on the oven) 	PNC 922171	
 Baking tray for 5 baguettes in perforated aluminum with silicon coating, 400x600x38mm 	PNC 922189	
 Baking tray with 4 edges in perforated aluminum, 400x600x20mm 	PNC 922190	
 Baking tray with 4 edges in aluminum, 400x600x20mm 	PNC 922191	
 Pair of frying baskets 	PNC 922239	
 AISI 304 stainless steel bakery/pastry grid 400x600mm 	PNC 922264	
 Double-step door opening kit 	PNC 922265	
 Grid for whole chicken (8 per grid - 1,2kg each), GN 1/1 	PNC 922266	
 USB probe for sous-vide cooking 	PNC 922281	
 Grease collection tray, GN 1/1, H=100 mm 	PNC 922321	

 Kit universal skewer rack and 4 long skewers for GN 1/1 ovens 	PNC 922324	
 Universal skewer rack 	PNC 922326	
 4 long skewers 	PNC 922327	\Box
Smoker for lengthwise and crosswise	PNC 922338	$\overline{\Box}$
oven		
 Multipurpose hook 	PNC 922348	
 4 flanged feet for 6 & 10 GN , 2", 100-130mm 	PNC 922351	
 Grid for whole duck (8 per grid - 1,8kg each), GN 1/1 	PNC 922362	
 Tray support for 6 & 10 GN 1/1 disassembled open base 	PNC 922382	
 Wall mounted detergent tank holder 	PNC 922386	
USB single point probe	PNC 922390	
- · · · · · · · · · · · · · · · · · · ·		
 IoT module for OnE Connected and Match (one IoT board per appliance - to connect oven to the blast chiller for Cook&Chill process). 	PNC 922421	J
 Connectivity router (WiFi and LAN) 	PNC 922435	
 Grease collection kit for ovens GN 1/1 & 2/1 (2 plastic tanks, connection valve with pipe for drain) 	PNC 922438	
 Match kit - to connect oven and blast chiller freezer for Cook&Chill process. The kit includes 2 boards and cables. Not for OnE Connected 	PNC 922439	
Tray rack with wheels, 6 GN 1/1, 65mm pitch	PNC 922600	
Tray rack with wheels 5 GN 1/1, 80mm pitch	PNC 922606	
Bakery/pastry tray rack with wheels holding 400x600mm grids for 6 GN 1/1 oven and blast chiller freezer, 80mm pitch (5 runners)	PNC 922607	
Slide-in rack with handle for 6 & 10 GN 1/1 oven	PNC 922610	
 Open base with tray support for 6 & 10 GN 1/1 oven 	PNC 922612	
 Cupboard base with tray support for 6 & 10 GN 1/1 oven 	PNC 922614	
 Hot cupboard base with tray support for 6 & 10 GN 1/1 oven holding GN 1/1 or400x600mm 	PNC 922615	
 External connection kit for liquid detergent and rinse aid 	PNC 922618	
 Grease collection kit for GN 1/1-2/1 cupboard base (trolley with 2 tanks, open/ close device for drain) 	PNC 922619	
Stacking kit for 6 GN 1/1 oven placed on gas 6 GN 1/1 oven	PNC 922622	
Stacking kit for 6 GN 1/1 oven placed on gas 10 GN 1/1 oven	PNC 922623	
Trolley for slide-in rack for 6 & 10 GN 1/1 oven and blast chiller freezer	PNC 922626	
Trolley for mobile rack for 2 stacked 6 GN 1/1 ovens on riser	PNC 922628	
Trolley for mobile rack for 6 GN 1/1 on 6 or 10 GN 1/1 ovens	PNC 922630	
Riser on feet for 2 6 GN 1/1 ovens or a 6 GN 1/1 oven on base	PNC 922632	
Riser on wheels for stacked 2x6 GN 1/1 ovens, height 250mm	PNC 922635	















•	Stainless steel drain kit for 6 & 10 GN oven, dia=50mm	PNC 922636		 Non-stick universal pan, GN 1/1, H=20mm Non-stick universal pan, GN 1/1, 	PNC 925000 PNC 925001
•	Plastic drain kit for 6 &10 GN oven,	PNC 922637		H=40mm	DNO 005000
_	dia=50mm	DNC 022620		Non-stick universal pan, GN 1/1, H=60mm Double face griddle, one side ribbed and	PNC 925002 PNC 925003
•	Grease collection kit for GN 1/1-2/1 open base (2 tanks, open/close device	PNC 922639		 Double-face griddle, one side ribbed and one side smooth, GN 1/1 	FNC 925005
	for drain)			Aluminum grill, GN 1/1	PNC 925004
	Wall support for 6 GN 1/1 oven	PNC 922643			PNC 925005
	Dehydration tray, GN 1/1, H=20mm	PNC 922651		hamburgers, GN 1/1	
	Flat dehydration tray, GN 1/1	PNC 922652		3 ,	PNC 925006
•	Open base for 6 & 10 GN 1/1 oven, disassembled - NO accessory can be fitted with the exception of 922382	PNC 922653		3 , 3 ,	PNC 925007 PNC 925008
•	Bakery/pastry rack kit for 6 GN 1/1 oven with 5 racks 400x600mm and 80mm pitch	PNC 922655		 Non-stick universal pan, GN 1/2, H=40mm Non-stick universal pan, GN 1/2, H=60mm 	PNC 925010
•	Stacking kit for 6 GN 1/1 combi or convection oven on 15&25kg blast chiller/freezer crosswise	PNC 922657		 Compatibility kit for installation on previous base GN 1/1 	PNC 930217
•	Heat shield for stacked ovens 6 GN 1/1 on 6 GN 1/1	PNC 922660			
•	Heat shield for stacked ovens 6 GN 1/1 on 10 GN 1/1	PNC 922661			
•	Heat shield for 6 GN 1/1 oven	PNC 922662			
	Kit to convert from natural gas to LPG	PNC 922670			
	Kit to convert from LPG to natural gas	PNC 922671			
	Flue condenser for gas oven	PNC 922678			
•	Fixed tray rack for 6 GN 1/1 and 400x600mm grids	PNC 922684			
•	Kit to fix oven to the wall	PNC 922687			
•	4 high adjustable feet for 6 & 10 GN ovens, 100-115MM	PNC 922688			
•	Tray support for 6 & 10 GN 1/1 oven base	PNC 922690			
	Detergent tank holder for open base	PNC 922699			
	6 & 10 GN 1/1 oven base	PNC 922702			
	Wheels for stacked ovens	PNC 922704			
•	Chimney adaptor needed in case of conversion of 6 GN 1/1 or 6 GN 2/1 ovens from natural gas to LPG	PNC 922706			
•	Mesh grilling grid, GN 1/1	PNC 922713			
	Probe holder for liquids	PNC 922714			
	Exhaust hood with fan for 6 & 10 GN 1/1 ovens	PNC 922728			
	Exhaust hood with fan for stacking 6+6 or 6+10 GN 1/1 ovens				
	Exhaust hood without fan for 6&10 1/1GN ovens	PNC 922733			
	Exhaust hood without fan for stacking 6+6 or 6+10 GN 1/1 ovens	PNC 922737			
	Fixed tray rack, 5 GN 1/1, 85mm pitch 4 high adjustable feet for 6 & 10 GN	PNC 922740 PNC 922745			
	ovens, 230-290mm Tray for traditional static cooking,	PNC 922746			
	H=100mm Double-face griddle, one side ribbed	PNC 922747	_		
	and one side smooth, 400x600mm		_		
	Trolley for grease collection kit	PNC 922752			
	Water inlet pressure reducer	PNC 922773			
•	Extension for condensation tube, 37cm	PNC 922776			















34 1/8 D 60 3/16 " 1528 mm 14 3/16 " 12 11/16 ' 5/16 2 5/16 " 29 9/16

2/8 708 CWI1||CWI2||EI 53 a 5/16 ° 3 15/16 " 100 mm 33 4 15/16 "

= Cold Water inlet 1 **WI-** (cleaning)


Electrical inlet (power)

C-= Cold Water Inlet 2 WI- (steam generator)

= Gas connection

D = Drain

DO = Overflow drain pipe





Front

Side

Circuit breaker required

Supply voltage:

218680 (ZCOG61K2G0) 220-240 V/1 ph/50 Hz 225670 (ZCOG61K2G6) 220-230 V/1 ph/60 Hz

Electrical power, max: 1.1 kW Electrical power, default: 1.1 kW

Total thermal load: 40908 BTU (12 kW)

Gas Power: 12 kW

Standard gas delivery: Natural Gas G20

ISO 7/1 gas connection

1/2" MNPT diameter:

Water:

Inlet water temperature,

30 °C

Inlet water pipe size (CWI1,

3/4" CWI2): Pressure, min-max: 1-6 bar **Chlorides:** <10 ppm **Conductivity:** >50 µS/cm Drain "D": 50mm

Electrolux Professional recommends the use of treated water, based on testing of specific water conditions.

Please refer to user manual for detailed water quality information.

Installation:

Clearance: 5 cm rear and right Clearance:

hand sides.

Suggested clearance for service access:

50 cm left hand side.

Capacity:

6 (GN 1/1) Trays type:

Max load capacity: 30 kg

Key Information:

Right Side **Door hinges:**

External dimensions,

867 mm Width:

External dimensions,

775 mm Depth:

External dimensions,

Height: 808 mm

Weight:

218680 (ZCOG61K2G0) 115 kg

225670 (ZCOG61K2G6) 118 kg

Net weight:

218680 (ZCOG61K2G0) 115 kg 118 kg

225670 (ZCOG61K2G6)

Shipping weight:

218680 (ZCOG61K2G0) 132 kg 135 kg

225670 (ZCOG61K2G6)

Shipping volume:

218680 (ZCOG61K2G0) 0.89 m³ 225670 (ZCOG61K2G6) 0.84 m³













