# 2 Door & 2 Drawer Freezer Counter, 415lt (-20/-15) - No Top

**712681 (AJ3F7AAB)**
2-door and 2x1/2-drawer freezer counter, -22-15°C, full AISI 304 (R290), without work top

## Main Features

- Anti-tilt runners accept GN 1/1 containers.
- Digital control panel with temperature display.
- Forced air circulation for rapid cooling and an even temperature distribution.
- Self closing stainless steel doors (< 90°).
- Compliant to CE requirements for safety.
- Anti-tilt runners accept GN1/1 trays and grids.
- Adjustable temperature range from -15°C to -20°C to suit all storage requirements.
- 0mm clearance installation space: tower configuration cooling unit guarantee performance with frontal ventilation only; this unique solution allows installation against the wall or side by side with other appliances, even on the cooling unit side to maximize the use of kitchen space.
- Combination of doors and drawers to suit any configuration needed, with the possibility to change the configuration on site. Right cooling unit available on request.
- Frontal and easy access to all components in the cooling unit.
- Certified safety CE requirements.
- Equipped with Airflow system:  forced air circulation system for rapid cooling and even temperature distribution within the cell.
- Digital white-digit display with internal temperature display and setting, manual activation of defrost cycle and turbo frost cycle (to rapidly cool warm loads).
- Tropicalized unit.

## Construction

- Access to all components from the front.
- Constructed in Stainless steel with Scotch Brite finish to meet the highest hygiene standards.
- Developed and produced in ISO 9001 and ISO 14001 certified factory.
- Fault code display.
- Interior base with rounded corners, pressed from a single sheet.
- Internal and external doors, front and side panels and removable worktop in AISI 304 Stainless steel.
- Mounted on Stainless steel adjustable legs to give 150 mm clearance for ease of cleaning.
- Rounded internal corners for ease of cleaning.
- 304 AISI stainless steel internal and external doors, front and side panels. Evaporator in aluminium.
- Pre-arranged for drain-pipe.
- Built-in refrigeration unit.
- Mounted on stainless steel feet to give 150 mm (-5/+50 mm) clearance for ease of cleaning the floor.
- Ease of cleaning and high hygiene standards thanks to the rounded internal corners, the easily removable runners, grids and air conveyors.
- Internal structure with 15 charging positions (3 cm pitch) available to host GN 1/1 grids, ensuring higher net capacity and a greater storage space.
- Extractable cooling unit to facilitate maintenance.
- IP21 protection index.


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

- Internal dimension of the drawers: - models with 2 1/2 drawers: 1st drawer (top drawer) 196x302x521 / 2nd drawer 198x302x521 (HxWxD) - models with 3 1/3 drawers: 1st and 2nd drawers (top and central drawer) 99x302x521 / 3rd drawers 103x302x521 (HxWxD) - models with 1/3+2/3 drawers: 1st drawer (top drawer) 99x302x521 / 2nd drawer 295x302x521 (HxWxD)

## User Interface & Data Management

- Fully compliant HACCP digital control: when temperature exceeds critical limits, acoustic and visual alarms are activated. Up to two months of event are kept in memory.
- Easy serviceability thanks to the intuitive control panel with access via app.
- Integrated RS485 port to facilitate connection to a remote computer and integrated HACCP systems.
- Connect the product (with accessory) to the OneConnected Platform via Wi Fi or ethernet connection for a seamless remote experience. Real-time monitoring and analytics, alarm management, HACCP data management, APIs, and advanced features keep your fridge fully under control.
- Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated HACCP systems.



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

# A focus on sustainability

## Sustainability

- 50 mm insulation thickness for energy saving.
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.
- CFC and HCFC free, highly ecological refrigerant type: R290 (ecological gas in foam: cyclopentane). Hydrocarbon refrigerant gas R290 for the lowest environmental impact (GWP=3), to reduce green house and ozone depletion effects.
- Fitted with 90 mm thickness of cyclopentane insulation for best insulating performance (thermal conductivity: 0,020 W/m*K) and lowest environmental impact (GWP=3).
- IQ Defrost - fully automatic defrost starts only when ice is actually building-up in the evaporator and adapts the defrosting duration to guarantee perfect ice removal while optimizing energy efficiency consumption.
- Hot gas automatic evaporation of defrost water.







EU energy labelling from 1st July 2016

*The European energy labelling scheme for professional refrigerators and freezers is based on requirements setting Minimum Energy Performance standards for commercial refrigeration cabinets sold within the EU. These requirements are designed to drive energy efficiency and environmentally friendly approach for professionals. The European energy labelling scheme will apply to all manufacturers and importers who sell and market products within the EU and it is mandatory across Europe. Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016. SI 2020 No. 1528.*

Important: all products which consume energy above the minimum level will not be able to be sold within the EU from 1 July 2016.

## Certifications & Recognitions

International system for mutual acceptance of test reports and certificates concerning the safety of electrical and electronic components, equipment, and products.

Product assessed by the manufacturer and deemed to meet EU safety, health, and environmental protection requirements.



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

# Technical specifications

**Electric**

| | |
|---|---|
| **Supply voltage:** | 220-240 V/1 ph/50 Hz |
| **Compressor power:** | hp |

**Key Information:**

| | |
|---|---|
| **Net Volume:** | 215 lt |
| **N° of doors:** | |
| **External dimensions, Width:** | 1795 mm |
| **External dimensions, Depth:** | 700 mm |
| **External dimensions, Depth with Doors Open:** | 1110 mm |
| **External dimensions, Height:** | 800 mm |
| **Depth with doors open:** | 1110 mm |
| **N° of drawers:** | |
| **Gross capacity:** | 0 liter |

**Refrigeration Data**

| | |
|---|---|
| **Control type:** | Digital |
| **Refrigeration power at evaporation temperature:** | -30 °C |
| **Operating temperature min.:** | -15 °C |
| **Operating temperature max.:** | -22 °C |
| **Operating mode:** | Ventilated |
| **Defrost type:** | |
| **N° defrost in 24 hrs:** | |

**Sustainability**

| | |
|---|---|
| **Noise level:** | 65.5 dBA |
| **Refrigerant type:** | R290 |
| **Refrigeration power:** | 569 W |
| **Refrigerant weight:** | 140 g |
| **Energy Class (EU Reg. 2015/1094):** | D |
| **Climate class (EU Reg. 2015/1094):** | Normal duty (cl.4) |
| **Energy Efficiency Index-EEI (EU Reg. 2015/1094):** | 68,76 |



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

# Installation drawings

Front




Side




Top




Other




EI = Electrical inlet (power)

# Accessories

## Included Accessories

| PNC Code | Description | Quantity |
|---|---|---|
| 881109 | Kit 1/1GN gray rilsan grid and 2 side runners for refrigerated counters | 2 |

## Optional Accessories

| PNC Code | Description |
|---|---|
| **Containers, trays and grids** | |
| 881107 | 1/1GN gray rilsan grid for refrigerated counters |
| 881108 | 2 side runners for 1/1GN refrigerated counters |
| 881109 | Kit 1/1GN gray rilsan grid and 2 side runners for refrigerated counters |
| 881110 | 1/1GN plastic container, h65mm |
| 881111 | 1/1GN plastic container, h100mm |
| 881112 | 1/1GN plastic container, h150mm |
| **Doors and drawers** | |
| 881179 | 2-drawer kit refrigerated counters |
| 881246 | Lock for refrigerator/freezer counters with 3 compartments - h650mm |
| **Feet, wheels and ramps** | |
| 881191 | Kit 4 wheels, h100mm (2 with brakes) for refrigerated counters |
| 881193 | Kit 4 wheels, h150mm (2 with brakes) for 2&3 compartment refrigerated counters |
| **Work tops** | |
| 881085 | Worktop for refrigerated Crio Line HP and freezer Crio Line HP, CP and SB counters refrigerated counters - 3 compartments |
| 881088 | Worktop and upstand for refrigerated Crio Line HP and freezer HP, CP and SB counters - 3 compartments |
| **Other accessories** | |
| 881298 | IoT module for refrigerated cabinets and counters |

## Recommended Detergents

| PNC Code | Description |
|---|---|
| 0S2881 | S01 STAINLESS STEEL SURFACE POLISHER; 6 BOTTLES X 750ML C/T |
| 0S2883 | S03 ALCOHOL BASE DETERGENT; 6 BOTTLES X 750ML; ADR&IMDG&IATA Limited Quantity |
| 0S2884 | S04 GLASSES & HARD SURFACES CLEANERS; 6 BOTTLES X 750ML |
| 0S3257 | S05 - MULTIPURPOSE DEGREASER; 6PCS X 750ML; ADR&IMDG Limited Quantity |


The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.