1 Glass Door Digital Freezer, 670lt (-20/-15) Remote

728845 (CTE71GFR)
1-glass door freezer 670L, -20-15°C, digital, AISI 304, remote

What our App can do for you:

- Stay Connected: real-time equipment monitoring ensures you're always up to date
- Smart Connection: bluetooth integration for fast, reliable control
- Control at Your Fingertips: adjustments made easy for seamless operations
- Effortless Compliance: download HACCP data in seconds, simplifying food safety management

Main Features

- Large storage area suitable to contain 2/1 GN grids or shelves on anti-tilt runners.
- Performance guaranteed at ambient temperatures of +32°C.
- Right hinged glass door with heated frame.
- Cabinet fitted with up to 75 mm thickness of cyclopentane insulation for best insulating performance with 100% environmental protection (thermal conductivity: 0,020 W/m*K).
- Adjustable temperature range from -15°C to -20°C to suit all storage requirements.
- 60 mm-thick insulation covering the evaporator can be easily removed with a single operation.
- Prearranged to fit RS485 port to facilitate connection to a remote computer and integrated HACCP systems.
- Airflow: back to front forced air flow and removable air conveyors provide even temperature distribution and fast cooling in any conditions.
- IQ Defrost: fully automatic defrost starts only when ice is actually building-up in the evaporator.
- Internal structure with 44 charging positions available to host grids, ensuring higher net capacity and a greater storage space.
- Tropicalized unit.

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Construction

- Interior base with rounded corners, pressed from a single sheet.
- Lockable door.
- Refrigerant type: R404a.
- Remote refrigeration unit.
- Constructed from the highest quality AISI 304 Stainless steel.
- Easy access to the main components for maintenance.
- Stainless steel runners and supports easily disassembled.
- The rounded internal corners, the easily removable runners, grids and air conveyors allow for ease of cleaning and high hygiene standards.
- Anti-corrosion bottom material avoids any damage that may be caused to the cabinet by aggressive detergents employed to clean the floors.

User Interface & Data Management

- Large digital white-digit display with cabinet temperature display and setting. Bluetooth technology included allows to keep HACCP historical data and download them through the app.
- Alpeninox Fridge Control APP makes the life easier for our customers:
  - Monitor safety of preservation process thanks to HACCP data & alarms for precise control
  - Save time and easy data management having the possibility to send the HACCP information in excel format directly to e-mail address
  - Quick operations: set the cabinet temperature/turbocooling and set date/hour
- Large digital white-digit display with cabinet temperature display and setting, activation of turbo frost cycle (to rapidly cool warm loads) and possibility to activate manually the defrost cycle.
- Large digital white-digit display with cabinet temperature display and setting, manual activation of defrost cycle, turbo frost cycle (to rapidly cool warm loads) and internal light switch.
- Connect the product (with accessory) to the OneConnected Platform via Wi Fi or ethernet connection for a seamless remote experience. Real-time monitoring and analytics, alarm management, HACCP data management, APIs, and advanced features keep your fridge fully under control.

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

A focus on sustainability

Sustainability

- CFC and HCFC-free insulation.
- Interior LED light to save energy and for best internal visibility.
- Door switch stops the fan when door is opened to avoid cold air exiting the cell, thus saving energy.
- Removable triple-chamber balloon magnetic gasket to improve insulation and reduce energy consumption and ease of cleaning.

Certifications & Recognitions

International system for mutual acceptance of test reports and certificates concerning the safety of electrical and electronic components, equipment, and products.

Product assessed by the manufacturer and deemed to meet EU safety, health, and environmental protection requirements.

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Technical specifications

Electric

Supply voltage:	220-240 V/1 ph/50/60 Hz

Key Information:

Number and type of grids (included):	3 (GN 2/1)
External dimensions, Width:	710 mm
External dimensions, Depth:	835 mm
External dimensions, Depth with Doors Open:	1480 mm
External dimensions, Height:	2050 mm
Number and type of doors:	1 Glass
Type of external material:	Stainless Steel AISI 304
Type of internal material:	Stainless Steel AISI 304
Internal panels material:	Stainless Steel AISI 304
Number of positions & pitch:	44; 30 mm
Gross capacity:	670 liter

Refrigeration Data

Control type:	Digital
Operating temperature min.:	-15 °C
Operating temperature max.:	-20 °C
Refrigeration type:	R404A;R452A
Operating mode:	Ventilated
N° defrost in 24 hrs:	
Suggested refrigeration power:	785 W
Condition at evaporation temperature:	-30 °C
Condition at condensation temperature:	55 °C
Condition at ambient temperature:	32 °C
Connection pipes (remote) - outlet:	9.5 mm
Connection pipes (remote) - inlet:	6 mm
***Note:**	Ref. Power calculated at a linear distance of 15 mt (piping)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Installation drawings

Front



Side



Top



Distances



EI = Electrical inlet (power)
RI = Refrigerant Inlet

RO = Refrigerant Outlet

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Accessories

Included Accessories

PNC Code	Description	Quantity
881018	AISI 304 stainless steel grid with 2 runners, 2/1GN	3

Optional Accessories

PNC Code	Description
Baskets	
881043	1/1GN rilsan steel wire basket h150mm
Containers, trays and grids	
880242	2 stainless steel runners for refrigerated cabinets - (Marine)
880243	1/1GN set of 8 PVC containers for fish
880248	Spacer for 670L and 1430L refrigerated cabinets
880705	Plastic container with false bottom, 1/1GN
881003	Kit to fit 10 pastry trays (400x600mm)
881004	2/1GN gray rilsan grid
881016	AISI 304 stainless steel grid, 2/1GN
881018	AISI 304 stainless steel grid with 2 runners, 2/1GN
881020	2/1GN gray rilsan grid with 2 runners
881021	Set of 2 stainless steel runners for 670/1430L refrigerators and freezers
881039	PVC container with lid and 2 runners, 2/1GN
881042	2/1GN perforated shelf
881047	2/1GN gray rilsan basket + 2 runners h150mm
Doors and drawers	
881163	Glass door protection kit
Feet, wheels and ramps	
880324	Pedal opening for cabinets
881035	Kit of 4 small swivelling wheels (2 with brake), diam 50mm, NOT for remote models
Other accessories	
881298	IoT module for refrigerated cabinets and counters

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.