



## 600881 (E1HCCEOMCS)

Plug-in Induction Wok

### Main Features

- Automatic pan detection to transfer power only when pan is present.
- High impact, heavy duty glass-ceramic wok bowl for durability and easy cleaning.
- 2-color user interface (white and red) for better readability.
- Plug in unit designed for table top installations.
- Glass touch display on top for maximum visibility.
- Power level settings from 1 to 10.
- Timer function can be used to set the cooking time, switching off the zone automatically at the end of the time set.
- Self-diagnostics: an error code is displayed (Exxx) in case of dysfunction.
- Designed for LiberoPro Duo function for automatic regulation of the LiberoPro Point fan speed according to cooking intensity.

### Construction

- IPx4 water protection.
- One induction wok shaped bowl 6mm thick.
- 4 sides unique frame in AISI 304 2 mm thick.
- Induction air filters easy to clean and remove for monthly cleaning.
- 4 feet, cord and plug included.

### Sustainability

- Rapid heat transfer directly to the pan, no heat is dispersed into the environment.
- This model is compliant with Swiss Energy Efficiency Ordinance (730.02).

### Optional Accessories

| PNC Code             | Description                                              |
|----------------------|----------------------------------------------------------|
| <b>Pots and pans</b> |                                                          |
| 910613               | Induction Wok pan with wooden handle (diam. 360mm)       |
| 911000               | Stainless steel wok pan, design in line with wok cuvette |
| 911003               | Non-stick wok pan, design in line with wok cuvette       |



## Recommended Detergents

| PNC Code | Description                                                                                                                                                                                                   |
|----------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| OS2881   | S01 STAINLESS STEEL SURFACE POLISHER; 6 BOTTLES X 750ML C/T                                                                                                                                                   |
| OS2882   | S02 Degreaser. A highly concentrated detergent specifically for cleaning and removing grease from appliances and surfaces. Active up to a maximum of 50°C Complete with spray bottle. Pack of 6x750ml bottles |
| OS2883   | S03 ALCOHOL BASE DETERGENT; 6 BOTTLES X 750ML; ADR&IMDG&IATA Limited Quantity                                                                                                                                 |
| OS2884   | S04 Glasses & Hard Surfaces Cleaner, 6 x 750ml bottles                                                                                                                                                        |



# Technical specifications

Electric

|                                 |                          |
|---------------------------------|--------------------------|
| Supply voltage:                 | 220-240 V/1N ph/50-60 Hz |
| Total Watts:                    | 3.5 kW                   |
| Plug type:                      | CE-SCHUKO                |
| Minimum Circuit Ampacity (MCA): | 16A                      |

Key Information:

|                              |        |
|------------------------------|--------|
| External dimensions, Width:  | 400 mm |
| External dimensions, Depth:  | 600 mm |
| External dimensions, Height: | 229 mm |
| Net weight:                  | 21 kg  |

Side

Top

Other

SCHUKO PLUG TYPE "F" 16A 250V  
 1,5 mt. CORD LENGTH  
 OR  
 UK PLUG TYPE "G" 13A 250V  
 1,5 mt. CORD LENGTH

EI = Electrical inlet (power)  
 EO = Electrical Outlet



Find out more:  
 ISO Certificates  
 Electrolux Professional Recognitions

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.