Corner drying zone for dual rinse rack type dishwasher - Marine

535099 (NCDDRE5)
Corner drying zone for green&clean Dual Rinse Rack Type Dishwasher

Main Features

- Electronically controlled to optimize drying results.
- Full accessibility to the interior of the tunnel and hygienic design to facilitate cleaning.
- Drying zone removes most of water from the crockery through a high powered fan that extracts dry air from outside mixing it with the internal air, thus providing dry plates at a temperature cool enough to handle safely.
- Dryer must always be ordered with a 90° or 180° dishwashing driven curve.
- IP25 protection against water jets, solid objects and small animals (larger than 6 mm).
- The feeding direction can be either left to right or right to left as it's reversible on site.
- All main components made in heavy duty anti-corrosive 304 type stainless steel: internal chamber, external, front and side panels and rack transportation system.
- Unit to be placed between dual rinse rack type dishwasher and handling system.

Construction

- The chamber is pressed with fully rounded corners without internal pipes and therefore no hidden dirt traps.
- The unit is built on modularity concept to easily connect with dual rinse rack type dishwasher without any modification including power, inlet water, drain water, detergent and rinse aid connections.

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Technical specifications

Electric	
Supply voltage:	380-415 V/3N ph/50/60 Hz
Default Installed Power:	8.5 kW
Key Information:	
External dimensions, Width:	872 mm
External dimensions, Depth:	872 mm
External dimensions, Height:	877 mm
Net weight:	62 kg
Shipping weight (gross):	61 kg
Shipping height:	1020 mm
Shipping width:	930 mm
Shipping depth:	940 mm
Shipping volume:	0.89 m³
Sustainability	
Noise level:	<62 dBA

Front



Side



Top



EI = Electrical inlet (power)
EQ = Equipotential screw
EO = Electrical Outlet
CWI = Cold Water Inlet
U = USB port
ES = Electrical signal IN/OUT

CE

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.