Modular Cooking Range Line

thermaline 80 - 4 Zone Freestanding Electric Solid Top with Ecotop, 2 Sides, H=800

588361 (MALDFCHDAO)
Electric Solid Top, 4 zones, ecoTop coating, two-side operated

Main Features

- 4 heating zones independently controlled.
- Rapid heat up of the plate and continuously ready for use.
- Overheat protection: the temperature sensor switches off the supply in case of overheating.
- Pans can easily be moved from one area to another without lifting.
- Wide rounded cleaning zone around the plates for easier cleaning.
- All major components may be easily accessed from the front.
- ECOTOP model has a 20 mm thick steel DIN 1.7335 nickel coated cooking surface.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Metal-covered knobs with embedded hygienic "soft-touch" grip for easier handling and cleaning. The special design of the controls prevents infiltration of liquids or soil into vital components.
- Large visible digital display manufactured in tempered glass to resist heat and chemicals, showing temperatures or power settings. The display also shows on/off status of the appliance and on/off status of the heating elements.
- Cooking plate and base joint profile guarantee against soil infiltration.
- Two electronic sensors per zone to control surface temperature and to protect cooking plate from overheating.
- 8 power levels.

Construction

- IPX5 water resistance certification.
- 2 mm top in 1.4301 (AISI 304).
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top and 70 mm recessed plinth.
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Unit constructed according to DIN 18860_2 with 20 mm drop nose top.
- Internal frame for heavy duty sturdiness in stainless steel.

Sustainability

- Standby function for energy saving and fast recovery of maximum power.

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Optional Accessories

PNC Code	Description
Connection and endrail kits	
912500	Connecting rail kit, 800mm
912971	Connecting rail kit: modular 80 (on the left) to ProThermetic tilting (on the right), ProThermetic stationary (on the left) to ProThermetic (on the right)
912972	Connecting rail kit: modular 80 (on the right) to ProThermetic tilting (on the left), ProThermetic stationary (on the right) to ProThermetic (on the left)
913109	Endrail kit, flush-fitting, left
913110	Endrail kit, flush-fitting, right
913200	Endrail kit (12.5mm) for thermaline 80 units, left
913201	Endrail kit (12.5mm) for thermaline 80 units, right
Filters	
913665	Filter W=800mm
Installation solutions	
913230	Insert profile D=800mm
Kicking strips	
912598	Stainless steel front kicking strip, 800mm width
912619	Stainless steel side kicking strips left and right, freestanding, 800mm width
Panels	
912508	Stainless steel side panel, 800x800mm, freestanding
913257	Side reinforced panel only in combination with side shelf, for freestanding units
913669	Stainless steel dividing panel, 800x800mm, (it should only be used between Electrolux Professional thermaline Modular 80 and thermaline C80)
913685	Stainless steel side panel, 800x800mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)
Shelves	
912526	Portioning shelf, 800mm width
912556	Portioning shelf, 800mm width
912577	Folding shelf, 300x800mm
912578	Folding shelf, 400x800mm
912583	Fixed side shelf, 200x800mm
912584	Fixed side shelf, 300x800mm
912585	Fixed side shelf, 400x800mm
913234	Perforated shelf for warming cabinets and cupboard bases (one-side operated TL80-85-90 and two-side operated for TL80)
913281	Shelf fixation for TL80-85-90 one-side operated, TL80 two-side operated

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

PNC Code	Description
Other accessories	
912825	Stainless steel plinth, freestanding, 800mm width
913247	Energy optimizer kit 32A - factory fitted
913677	Electric mainswitch 63A 10mm2 NM for modular H800 electric units (factory fitted)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Technical specifications

Electric	
Supply voltage:	400 V/3N ph/50/60 Hz
Electrical power max.:	12 kW
Key Information:	
Working Temperature MIN:	100 °C
Working Temperature MAX:	450 °C
External dimensions, Width:	800 mm
External dimensions, Depth:	800 mm
External dimensions, Height:	800 mm
Storage Cavity Dimensions (width):	580 mm
Storage Cavity Dimensions (height):	330 mm
Storage Cavity Dimensions (depth):	740 mm
Net weight:	145 kg
Configuration:	On Base; Two-Side Operated
Front Plates Power:	3 - 3 kW
Back Plates Power:	3 - 3 kW
Solid top usable surface (width):	670 mm
Solid top usable surface (depth):	650 mm
Sustainability	
Current consumption:	26 Amps

Front



Side



Top



EI = Electrical inlet (power)
EQ = Equipotential screw

Find out more:
ISO Certificates
Electrolux Professional Recognitions

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.