Modular Cooking Range Line

thermaline 90 - 1000 mm Passthrough base, 4 doors, GN conform, 2 Sides (H2) - H=450

589199 (MC2FCCJOOO)
Passthrough Base, with 4 doors, two-side operated, GN - H2

Main Features

- All major components may be easily accessed from the front.
- THERMODUL connection system creates a seamless work top when units are connected to each other thus avoiding soil penetrating vital components and facilitating the removal of units in case of replacement or service.
- Unit constructed according to DIN 18860_2 with 70 mm recessed plinth.

Construction

- IPX5 water resistance certification.
- Hygienic design of the open base compartment with large round edges.
- Storage space in the base of the appliance that can accept GN1/1 containers.
- 2 mm top in 1.4301 (AISI 304).
- Flat surface construction with minimal hidden areas to easily clean all surfaces
- Internal frame for heavy duty sturdiness in stainless steel.

Optional Accessories

PNC Code	Description
Kicking strips	
912636	Stainless steel front kicking strip, 1000mm width
912657	Stainless steel side kicking strip left and right, freestanding, 900mm width
Panels	
912512	Stainless steel side panel, 900x700mm, freestanding
913260	Side reinforced panel only in combination with side shelf, for freestanding units
913672	Stainless steel dividing panel, 900x700mm, (it should only be used between Electrolux Professional thermaline Modular 90 and thermaline C90)
913688	Stainless steel side panel, 900x700mm, flush-fitting (it should only be used against the wall, against a niche and in between Electrolux Professional thermaline and ProThermetic appliances and external appliances - provided that these have at least the same dimensions)

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

PNC Code	Description
Shelves	
913238	Perforated shelf for warming cabinets and cupboard bases (two-side operated for TL90)
913284	Shelf fixation for TL90 two-side operated
Other accessories	
912960	Stainless steel plinth, freestanding, 1000mm width

The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.

Technical specifications

Key Information:

External dimensions, Width:	1000 mm
External dimensions, Depth:	900 mm
External dimensions, Height:	450 mm
Cupboard Cavity Dimensions (width):	680 mm
Cupboard Cavity Dimensions (height):	330 mm
Cupboard Cavity Dimensions (depth):	810 mm
Net weight:	36 kg

Front



Side



Top



The company reserves the right to make modifications to the products without prior notice. All information correct at time of printing.