



Range Overview

Modular 80

Contents

Electric Solid Tops - 2 Zones	8
Electric Solid Tops - 2 Zones - Freestanding - H 700	8
Electric Solid Tops - 2 Zones - Freestanding - H 800	8
Electric Solid Tops - 4 Zones	8
Electric Solid Tops - 4 Zones - Freestanding - H 700	9
Electric Solid Tops - 4 Zones - Freestanding - H 800	9
Electric Solid Tops on Warming Cabinet - H 700	9
Electric Solid Tops on Warming Cabinet - H 800	9
Electric Solid Tops on Oven - H 700	10
Electric Solid Tops on Oven - H 800	10
Infrared Tops - 2 and 4 Zones	10
Electric Warming Plate Tops	10
Induction Tops - 1 and 2 Zones	11
Induction Tops - 4 Zones	11
Induction Tops on Warming Cabinet - 4 Zones	11
Induction Tops on Oven - 4 Zones	11
Gas Burner Tops - 2 Burners	12
Gas Burner Tops - 4 and 6 Burners	12
Gas Burner Tops - 2 Burners - Ecoflam	12
Gas Burner Tops - 4 and 6 Burners - Ecoflam	12
Electric Fry Tops - Smooth Chrome Plate	13
Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 700	13
Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 800	13
Electric Fry Tops - Ribbed Chrome Plate	13
Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 700	14
Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 800	14
Electric Fry Tops - Smooth/Ribbed Chrome Plate	14
Electric Fry Tops - Smooth/Ribbed Chrome Plate - Freestanding - H 700	14
Electric Fry Tops - Smooth/Ribbed Chrome Plate - Freestanding - H 800	15
Electric Free-Cooking Tops	15
Electric Free-Cooking Tops - Freestanding - H 700	15
Electric Free-Cooking Tops - Freestanding - H 800	15
Electric Free-Cooking Tops on Warming Cabinet	16
Electric Free-Cooking Tops on Electric Static Oven	16

Electric Bain Marie Tops GN 1/1	16
Electric Bain Marie Tops GN 2/1	16
Electric Aquacookers - Freestanding - H 700 and H 800	17
Electric Multi Braisers GN 1/1 and GN 2/1 - Freestanding - H 700	17
Electric Multi Braisers GN 1/1 - Freestanding - H 800	17
Electric Multi Braisers GN 2/1 - Freestanding - H 800	17
Pasta Cookers - Freestanding - H 700	18
Pasta Cookers - Freestanding - H 800	18
Electric Deep Fat Fryers - Freestanding - H 700	18
Electric Deep Fat Fryers - Freestanding - H 800	18
Electric Chip Scuttles	19
Mixing Tap Tops	19
Mixing Tap Tops - Freestanding - H 700	19
Mixing Tap Tops - Freestanding - H 800	19
Mixing Tap Tops - Freestanding - Automatic Water Refilling	20
Sink Units - Freestanding	20
Closed Work Tops - 100 to 300 mm	20
Closed Work Tops - 400 to 600 mm	20
Closed Work Tops - 700 and 800 mm	21
Closed Work Tops - 900 and 1000 mm	21
Closed Bases - H 450	21
Open Bases - H 450	21
Open Bases - H 450	22
Cupboard Bases - H 450	22
Passthrough Open Bases 500 - 800mm - H 450	22
Passthrough Open Bases 900 - 1500mm - H 450	22
Passthrough Cupboard Bases - H 450	23

Closed Bases - H 550	23
Open Bases - H 550	23
Open Bases - H 550	23
Cupboard Bases - H 550	24
Passthrough Open Bases - H 550	24
Passthrough Open Bases - H 550	24
Passthrough Cupboard Bases - H 550	24
Electric Warming Cabinet Bases - H 450	25
Electric Passthrough Warming Cabinet Bases - H 450	25
Electric Warming Cabinet Bases - H 550	25
Electric Passthrough Warming Cabinet Bases - H 550	25
Holding Cabinet Base (GN Conform) - H 450	26
Holding Cabinet Base (GN Conform) - H 550	26
Electric Static Oven Base	26
Ref-freezer bases R 290	26

Built for the toughest kitchens



**Incomparable
Swiss design**

Infinite combinations, reliable innovation, superior flexibility and the highest quality standards.



Energy savings

Innovative solutions for high efficiency and savings. Less consumptions and lower running costs. Better for your business and for the environment.





Simple&Safe

Everything made easy.
Superior ergonomics, maximum
cleanability and operator safety
guaranteed.



High performance & reliability

Precise temperature control with
perfect heat uniformity. Highly
resistant construction
with impeccable finishing.



Full flexible modular cooking line made of:

► Top units

■ H=250

► Stand alone units

■ H=700 (body height 700 mm Hygi-
enic)

■ H=800 (body height 800 mm)

► Bases (for installation of top units)

■ H=450 (for total body height
including top of 700 mm hygienic)

■ H=550 (for total body height of 800
mm)

Units can be found in various installation Operating Side configurations:

- **Stand alone one side island operation**
(control panel found on one side)
- **Stand alone two side island operation**
(control panel found on both side of the
units)
- **Stand alone one side against the wall
operation** (control panel on one side
with backsplash on rear of the unit)

Units can be installed on:

- **Feet** (feet can be covered with optional
closing stainless steel covering plinths)
- **Stainless steel plinths** (100 mm or 200
mm height)
- **On site concrete** or stainless steel
plinths
- **Wall/cantilever** configurations with
optional factory supplied kit (verify with
factory possible configurations certain
units)

Electric Solid Tops - 2 Zones



	■ 588003	■ 588004	■ 588005
External dim. - mm			
Width	500	500	500
Depth	800	800	800
Height	250	250	250
Electric Power - kW	6	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	
Ecotop	•	•	•

Electric Solid Tops - 2 Zones - Freestanding - H 800



	■ 588353	■ 588354
External dim. - mm		
Width	500	500
Depth	800	800
Height	800	800
Electric Power - kW	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
Ecotop	•	•

Electric Solid Tops - 4 Zones



	■ 588006	■ 588007	■ 588008	■ 588009	■ 588010	■ 588011
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	250	250	250	250	250	250
Electric Power - kW	12	12	12	12	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops - 4 Zones - Freestanding - H 700



	■ 588344	■ 588345	■ 588346	■ 588347	■ 588348	■ 588349
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	700	700	700	700	700	700
Electric Power - kW	12	12	12	12	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops - 4 Zones - Freestanding - H 800



	■ 588356	■ 588357	■ 588358	■ 588359	■ 588360	■ 588361
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	800	800	800	800	800	800
Electric Power - kW	12	12	12	12	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops on Warming Cabinet - H 700



	■ 588457	■ 588458	■ 588459	■ 588460	■ 588461	■ 588462
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	700	700	700	700	700	700
Electric Power - kW	14.3	14.3	14.3	14.3	14.3	14.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops on Warming Cabinet - H 800



	■ 588463	■ 588464	■ 588465	■ 588466	■ 588467	■ 588468
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	800	800	800	800	800	800
Electric Power - kW	14.3	14.3	14.3	14.3	14.3	14.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops on Oven - H 700



	■ 588411	■ 588412	■ 588413	■ 588414	■ 588415	■ 588416
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	700	700	700	700	700	700
Electric Power - kW	17.3	17.3	17.3	17.3	17.3	17.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Electric Solid Tops on Oven - H 800



	■ 588417	■ 588418	■ 588419	■ 588420	■ 588421	■ 588422
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	800	800	800	800	800	800
Electric Power - kW	17.3	17.3	17.3	17.3	17.3	17.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Ecotop				•	•	•

Infrared Tops - 2 and 4 Zones



	■ 588012	■ 588013	■ 588014	■ 588015	■ 588016	■ 588017
External dim. - mm						
Width	400	400	400	800	800	800
Depth	800	800	800	800	800	800
Height	250	250	250	250	250	250
Electric Power - kW	8	8	8	16	16	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	
Zones	2	2	2	4	4	4

Electric Warming Plate Tops



	■ 588336	■ 588337	■ 588096	■ 588097
External dim. - mm				
Width	600	600	1000	1000
Depth	800	800	800	800
Height	250	250	250	250
Electric Power - kW	0.55	0.55	0.95	0.95
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Induction Tops - 1 and 2 Zones



	■ 588019	■ 588020	■ 588021	■ 588025	■ 588026
External dim. - mm					
Width	400	400	400	500	500
Depth	800	800	800	800	800
Height	250	250	250	250	250
Electric Power - kW	10	10	10	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side
Backsplash		•			•
Zones	2	2	2	1	1
Wok				•	•

Induction Tops - 4 Zones



	■ 588022	■ 588023	■ 588024
External dim. - mm			
Width	800	800	800
Depth	800	800	800
Height	250	250	250
Electric Power - kW	20	20	20
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side
Backsplash		•	

Induction Tops on Warming Cabinet - 4 Zones



	■ 588433	■ 588434	■ 588435	■ 588436	■ 588437	■ 588438
External dim. - mm						
Width	800	800	800	800	800	800
Depth	800	800	800	800	800	800
Height	700	700	700	800	800	800
Electric Power - kW	22	22	22	22,3	22	22
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	2-side	1-side	1-side	2-side
Backsplash		•			•	

Induction Tops on Oven - 4 Zones



	■ 588427	■ 588428	■ 588430	■ 588431	■ 588432
External dim. - mm					
Width	800	800	800	800	800
Depth	800	800	800	800	800
Height	700	700	800	800	800
Electric Power - kW	25	25,3	25	25	25
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	2-side
Backsplash		•		•	

Gas Burner Tops - 2 Burners



	■ 588036	■ 588037	■ 588038
External dim. - mm			
Width	400	400	400
Depth	800	800	800
Height	250	250	250
Gas Power - kW	14	14	14
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	2	2	2

Gas Burner Tops - 4 and 6 Burners



	■ 588039	■ 588040	■ 588041
External dim. - mm			
Width	800	800	800
Depth	800	800	800
Height	250	250	250
Gas Power - kW	28	28	28
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	4	4	4

Gas Burner Tops - 2 Burners - Ecoflam



	■ 588047	■ 588048	■ 588049
External dim. - mm			
Width	400	400	400
Depth	800	800	800
Height	250	250	250
Gas Power - kW	14	14	14
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	2	2	2

Gas Burner Tops - 4 and 6 Burners - Ecoflam



	■ 588050	■ 588051	■ 588052
External dim. - mm			
Width	800	800	800
Depth	800	800	800
Height	250	250	250
Gas Power - kW	28	28	28
Operating side	1-side	1-side	2-side
Backsplash		•	
Burners	4	4	4

Electric Fry Tops - Smooth Chrome Plate



	■ 588056	■ 588057	■ 588058	■ 588059
External dim. - mm				
Width	400	400	800	800
Depth	800	800	800	800
Height	250	250	250	250
Electric Power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 700



	■ 588362	■ 588363	■ 588364	■ 588365
External dim. - mm				
Width	400	400	800	800
Depth	800	800	800	800
Height	700	700	700	700
Electric Power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Smooth Chrome Plate - Freestanding - H 800



	■ 588370	■ 588371	■ 588372	■ 588373
External dim. - mm				
Width	400	400	800	800
Depth	800	800	800	800
Height	800	800	800	800
Electric Power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Ribbed Chrome Plate



	■ 588064	■ 588065	■ 588066	■ 588067
External dim. - mm				
Width	400	400	800	800
Depth	800	800	800	800
Height	250	250	250	250
Electric Power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 700



	■ 588366	■ 588367	■ 588368	■ 588369
External dim. - mm				
Width	400	400	800	800
Depth	800	800	800	800
Height	700	700	700	700
Electric Power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Ribbed Chrome Plate - Freestanding - H 800



	■ 588374	■ 588375	■ 588376	■ 588408
External dim. - mm				
Width	400	400	800	800
Depth	800	800	800	800
Height	800	800	800	800
Electric Power - kW	5.1	5.1	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Fry Tops - Smooth/Ribbed Chrome Plate



	■ 588409	■ 588410
External dim. - mm		
Width	800	800
Depth	800	800
Height	250	250
Electric Power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Fry Tops - Smooth/Ribbed Chrome Plate - Freestanding - H 700



	■ 588404	■ 588405
External dim. - mm		
Width	800	800
Depth	800	800
Height	700	700
Electric Power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Fry Tops - Smooth/Ribbed Chrome Plate - Freestanding - H 800



	■ 588406	■ 588407
External dim. - mm		
Width	800	800
Depth	800	800
Height	800	800
Electric Power - kW	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Free-Cooking Tops



	■ 588322	■ 588323	■ 588324	■ 588325
External dim. - mm				
Width	500	500	800	800
Depth	800	800	800	800
Height	250	250	250	250
Electric Power - kW	6	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Free-Cooking Tops - Freestanding - H 700



	■ 588380	■ 588381
External dim. - mm		
Width	800	800
Depth	800	800
Height	700	700
Electric Power - kW	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Free-Cooking Tops - Freestanding - H 800



	■ 588382	■ 588383	■ 588384	■ 588385
External dim. - mm				
Width	500	500	800	800
Depth	800	800	800	800
Height	800	800	800	800
Electric Power - kW	6	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Free-Cooking Tops on Warming Cabinet



	■ 588469	■ 588470	■ 588471	■ 588472
External dim. - mm				
Width	800	800	800	800
Depth	800	800	800	800
Height	700	700	800	800
Electric Power - kW	14.3	14.3	14.3	14.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Free-Cooking Tops on Electric Static Oven



	■ 588423	■ 588424	■ 588425	■ 588426
External dim. - mm				
Width	800	800	800	800
Depth	800	800	800	800
Height	700	700	800	800
Electric Power - kW	17.3	17.3	17.3	17.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Bain Marie Tops GN 1/1



	■ 588086	■ 588087	■ 588400	■ 588401	■ 588402	■ 588403
External dim. - mm						
Width	400	400	500	500	500	500
Depth	800	800	800	800	800	800
Height	250	250	250	250	250	250
Electric Power - kW	1.5	1.5	1.5	1.5	1.5	1.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Mixing tap position	back	back	left	left	right	right

Electric Bain Marie Tops GN 2/1



	■ 588088	■ 588089
External dim. - mm		
Width	800	800
Depth	800	800
Height	250	250
Electric Power - kW	3	3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•
Mixing tap position	back	back

Electric Aquacookers - Freestanding - H 700 and H 800



	■ 588090	■ 588091	■ 588253	■ 588254
External dim. - mm				
Width	400	400	400	400
Depth	800	800	800	800
Height	700	700	800	800
Electric Power - kW	7.5	7.5	7.5	7.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Multi Braisers GN 1/1 and GN 2/1 - Freestanding - H 700



	■ 588183	■ 588184	■ 588189	■ 588190
External dim. - mm				
Width	400	400	800	800
Depth	800	800	800	800
Height	700	700	700	700
Electric Power - kW	5	5	10.2	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Electric Multi Braisers GN 1/1 - Freestanding - H 800



	■ 588277	■ 588278
External dim. - mm		
Width	400	400
Depth	800	800
Height	800	800
Electric Power - kW	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Electric Multi Braisers GN 2/1 - Freestanding - H 800



	■ 588283	■ 588284
External dim. - mm		
Width	800	800
Depth	800	800
Height	800	800
Electric Power - kW	10.2	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Pasta Cookers - Freestanding - H 700



	■ 588203	■ 588204	■ 588205	■ 588206
External dim. - mm				
Width	400	400	400	400
Depth	800	800	800	800
Height	700	700	700	700
Electric Power - kW	5	5	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	2x5	2x5	20	20

Pasta Cookers - Freestanding - H 800



	■ 588289	■ 588290	■ 588291	■ 588292
External dim. - mm				
Width	400	400	400	400
Depth	800	800	800	800
Height	800	800	800	800
Electric Power - kW	5	5	6	6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Tank capacity - lt	2x5	2x5	20	20

Electric Deep Fat Fryers - Freestanding - H 700



	■ 588209	■ 588210	■ 588211	■ 588212	■ 588328	■ 588329
External dim. - mm						
Width	400	400	400	400	400	400
Depth	800	800	800	800	800	800
Height	700	700	700	700	700	700
Electric Power - kW	5.4	5.4	12	12	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Tank capacity - lt	7	7	2x5	2x5	14	14

Electric Deep Fat Fryers - Freestanding - H 800



	■ 588295	■ 588296	■ 588297	■ 588298	■ 588330	■ 588331
External dim. - mm						
Width	400	400	400	400	400	400
Depth	800	800	800	800	800	800
Height	800	800	800	800	800	800
Electric Power - kW	5.4	5.4	12	12	10	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side	1-side	1-side
Backsplash		•		•		•
Tank capacity - lt	7	7	2x5	2x5	14	14

Electric Chip Scuttles



	■ 588094	■ 588095
External dim. - mm		
Width	400	400
Depth	800	800
Height	250	250
Electric Power - kW	1	1
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz
Operating side	1-side	1-side
Backsplash		•

Mixing Tap Tops



	■ 588098	■ 588099	■ 588100	■ 588101
External dim. - mm				
Width	200	200	200	200
Depth	800	800	800	800
Height	250	250	250	250
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Lever	•	•		
Knobs			•	•

Mixing Tap Tops - Freestanding - H 700



	■ 588386	■ 588387	■ 588388	■ 588389
External dim. - mm				
Width	200	200	200	200
Depth	800	800	800	800
Height	700	700	700	700
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Lever	•	•		
Knobs			•	•

Mixing Tap Tops - Freestanding - H 800



	■ 588390	■ 588391	■ 588392	■ 588393
External dim. - mm				
Width	200	200	200	200
Depth	800	800	800	800
Height	800	800	800	800
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•
Lever	•	•		
Knobs			•	•

Mixing Tap Tops - Freestanding - Automatic Water Refilling



	■ 588172	■ 588173	■ 588266	■ 588267
External dim. - mm				
Width	200	200	200	200
Depth	800	800	800	800
Height	700	700	800	800
Electric Power - kW	0.1	0.1	0.1	0.1
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Sink Units - Freestanding



	■ 588213	■ 588214	■ 588299	■ 588300
External dim. - mm				
Width	400	400	400	400
Depth	800	800	800	800
Height	700	700	800	800
Operating side	1-side	1-side	1-side	1-side
Backsplash		•		•

Closed Work Tops - 100 to 300 mm



	■ 588102	■ 588103	■ 588104	■ 588105	■ 588106	■ 588107
External dim. - mm						
Width	100	100	200	200	300	300
Depth	800	800	800	800	800	800
Height	250	250	250	250	250	250
Backsplash		•		•		•

Closed Work Tops - 400 to 600 mm



	■ 588108	■ 588109	■ 588110	■ 588111	■ 588112	■ 588113
External dim. - mm						
Width	400	400	500	500	600	600
Depth	800	800	800	800	800	800
Height	250	250	250	250	250	250
Backsplash		•		•		•

Closed Work Tops - 700 and 800 mm



	■ 588114	■ 588115	■ 588116	■ 588117
External dim. - mm				
Width	700	700	800	800
Depth	800	800	800	800
Height	250	250	250	250
Backsplash		•		•

Closed Work Tops - 900 and 1000 mm



	■ 588118	■ 588119	■ 588120	■ 588121
External dim. - mm				
Width	900	900	1000	1000
Depth	800	800	800	800
Height	250	250	250	250
Backsplash		•		•

Closed Bases - H 450



	■ 588394	■ 588396	■ 588398
External dim. - mm			
Width	100	200	300
Depth	800	800	800
Height	450	450	450

Open Bases - H 450



	■ 588126	■ 588131	■ 588132	■ 588326	■ 588133
External dim. - mm					
Width	400	500	600	700	800
Depth	800	800	800	800	800
Height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side

Open Bases - H 450



	■ 588127	■ 588128	■ 588129	■ 588130
External dim. - mm				
Width	900	1000	1200	1500
Depth	800	800	800	800
Height	450	450	450	450
Operating side	1-side	1-side	1-side	1-side

Cupboard Bases - H 450



	■ 588134	■ 588135	■ 588136	■ 588138	■ 588137
External dim. - mm					
Width	400	500	600	800	1000
Depth	800	800	800	800	800
Height	450	450	450	450	450
Operating side	1-side	1-side	1-side	1-side	1-side
Doors	1	1	1	2	2

Passthrough Open Bases 500 - 800mm - H 450



	■ 588145	■ 588146	■ 588140	■ 588147
External dim. - mm				
Width	500	600	700	800
Depth	800	800	800	800
Height	450	450	450	450
Operating side	2-side	2-side	2-side	2-side

Passthrough Open Bases 900 - 1500mm - H 450



	■ 588141	■ 588142	■ 588143	■ 588144
External dim. - mm				
Width	900	1000	1200	1500
Depth	800	800	800	800
Height	450	450	450	450
Operating side	2-side	2-side	2-side	2-side

Passthrough Cupboard Bases - H 450



	■ 588148	■ 588149	■ 588153	■ 588151	■ 588152
External dim. - mm					
Width	500	600	800	1000	1200
Depth	800	800	800	800	800
Height	450	450	450	450	450
Operating side	2-side	2-side	2-side	2-side	2-side
Doors	2	2	4	4	4

Closed Bases - H 550



	■ 588395	■ 588397	■ 588399
External dim. - mm			
Width	100	200	300
Depth	800	800	800
Height	550	550	550

Open Bases - H 550



	■ 588215	■ 588220	■ 588221	■ 588327	■ 588222
External dim. - mm					
Width	400	500	600	700	800
Depth	800	800	800	800	800
Height	550	550	550	550	550
Operating side	1-side	1-side	1-side	1-side	1-side

Open Bases - H 550



	■ 588216	■ 588217	■ 588218	■ 588219
External dim. - mm				
Width	900	1000	1200	1500
Depth	800	800	800	800
Height	550	550	550	550
Operating side	1-side	1-side	1-side	1-side

Cupboard Bases - H 550



	■ 588223	■ 588224	■ 588225	■ 588227	■ 588226
External dim. - mm					
Width	400	500	600	800	1000
Depth	800	800	800	800	800
Height	550	550	550	550	550
Operating side	1-side	1-side	1-side	1-side	1-side
Doors	1	1	1	2	2

Passthrough Open Bases - H 550



	■ 588234	■ 588235	■ 588229	■ 588236
External dim. - mm				
Width	500	600	700	800
Depth	800	800	800	800
Height	550	550	550	550
Operating side	2-side	2-side	2-side	2-side

Passthrough Open Bases - H 550



	■ 588230	■ 588231	■ 588232	■ 588233
External dim. - mm				
Width	900	1000	1200	1500
Depth	800	800	800	800
Height	550	550	550	550
Operating side	2-side	2-side	2-side	2-side

Passthrough Cupboard Bases - H 550



	■ 588237	■ 588238	■ 588240	■ 588241
External dim. - mm				
Width	500	600	1000	1200
Depth	800	800	800	800
Height	550	550	550	550
Operating side	2-side	2-side	2-side	2-side
Doors	2	2	4	4

Electric Warming Cabinet Bases - H 450



	■ 588305	■ 588306	■ 588307	■ 588308
External dim. - mm				
Width	500	600	800	1000
Depth	800	800	800	800
Height	450	450	450	450
Electric Power - kW	1	1	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN 1/1	GN 1/1	GN 2/1	GN 2/1
Doors	1	1	2	2

Not for installation below induction, ecotop, solid top and freecooking top units


Electric Passthrough Warming Cabinet Bases - H 450



	■ 588309	■ 588310	■ 588311	■ 588312
External dim. - mm				
Width	500	600	800	1000
Depth	800	800	800	800
Height	450	450	450	450
Electric Power - kW	1	1	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	2-side	2-side	2-side	2-side
Capacity	GN 1/1	GN 1/1	GN 2/1	GN 2/1
Doors	2	2	4	4

Not for installation below induction, ecotop, solid top and freecooking top units

Electric Warming Cabinet Bases - H 550



	■ 588313	■ 588314	■ 588315	■ 588316
External dim. - mm				
Width	500	600	800	1000
Depth	800	800	800	800
Height	550	550	550	550
Electric Power - kW	1	1	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Capacity	GN 1/1	GN 1/1	GN 2/1	GN 2/1
Doors	1	1	2	2

Not for installation below induction, ecotop, solid top and freecooking top units

Electric Passthrough Warming Cabinet Bases - H 550



	■ 588317	■ 588318	■ 588319	■ 588320
External dim. - mm				
Width	500	600	800	1000
Depth	800	800	800	800
Height	550	550	550	550
Electric Power - kW	1	1	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	2-side	2-side	2-side	2-side
Capacity	GN 1/1	GN 1/1	GN 2/1	GN 2/1
Doors	2	2	4	4

Not for installation below induction, ecotop, solid top and freecooking top units

Holding Cabinet Base (GN Conform) - H 450



	■ 588301
External dim. - mm	
Width	800
Depth	800
Height	450
Electric Power - kW	1
Electrical connection	230V 1N 50Hz
Operating side	1-side
2 Drawers	•

Holding Cabinet Base (GN Conform) - H 550



	■ 588303
External dim. - mm	
Width	800
Depth	800
Height	550
Electric Power - kW	1
Electrical connection	230V 1N 50Hz
Operating side	1-side
2 Drawers	•

Electric Static Oven Base



	■ 588157	■ 588158	■ 588247	■ 588248
External dim. - mm				
Width	800	800	800	800
Depth	800	800	800	800
Height	450	450	550	550
Electric Power - kW	5	5	5	5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Operating side	1-side	1-side	1-side	1-side
Passthrough oven		•		•

Not for installation below induction, ecotop, solid top and freecooking top units

Ref-freezer bases R 290



	■ 588483	■ 588484
External dim. - mm		
Width	1000	1200
Depth	800	800
Height	550	550
Electric Power - kW	0.67	0.76
Electrical connection	230V 1N 50Hz	230V 1N 50Hz
Operating side	1-side	1-side
Temperature range	+8/-22 °C	+8/-22 °C
Connectivity	•	•



Excellence is central to everything we do.
By anticipating our customers' needs, we strive for
Excellence with our people, innovations, solutions and services.
To be the OnE making our customers' work-life easier,
more profitable - and truly sustainable every day.

Follow us on



www.electroluxprofessional.com

Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated - the environmental needs of our customers in mind
- ▶ Our technology is ROHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

