



Range Overview

Modular 85

Contents

Electric Solid Tops	6
Electric Solid Tops - Freestanding	6
Electric Solid Tops on Warming Cabinet	6
Electric Solid Tops on Oven	7
Gas French Tops	7
Electric Warming Plate Tops	7
Infrared Tops	8
Induction Tops	8
Induction Tops on Warming Cabinet	8
Induction Tops on Oven	9
Induction Wok and Plates	9
Full Surface Induction Tops on Bases	9
Full Surface Induction Tops on Bases - H2	10
Gas Burner Tops	10
Gas Burner Tops - Ecoflam	10
Gas Burner Tops on Gas Static Oven	11
Electric Fry Tops - Chrome Plate	11
Electric Fry Tops - Chrome Plate - freestanding	11
Gas Fry Tops - Chrome Plate	12
Gas Fry Tops - Chrome Plate - Freestanding	12
Electric Free-Cooking Tops	12
Electric Free-Cooking Tops on Warming Cabinet	13
Electric Free-Cooking Tops on Oven	13
Gas Chargrill Tops	13
Electric Bain Marie Tops	14
Electric Aquacooker - Freestanding	14
Electric Multi Braisers - Freestanding	14
Pasta Cookers - Freestanding	15

Deep Fat Fryers - Freestanding	15
Electric Chip Scuttle	15
Mixing Tap Units - H 250	15
Mixing Tap Units - H 700	16
Closed Work Tops - 100 to 600 mm	16
Closed Work Tops - 700 to 1500 mm	16
Sink Unit - Freestanding	16
Closed Bases	17
Open Bases 400 - 800 mm	17
Open Bases 900 - 1500 mm	17
Cupboard Bases	17
Open Bases - H2 - 400 - 800 mm	18
Open Bases - H2 - 900 - 1500 mm	18
Cupboard Bases - H2	18
Electric Warming Cabinets	18
Electric Warming Cabinets - H2	19
Holding Cabinet Base	19
Electric Static Oven Base	19
Ref-freezer Bases R290	19

Robust and hardworking



**Incomparable
Swiss design**

Infinite combinations, reliable innovation, superior flexibility and the highest quality standards.



Energy savings

Innovative solutions for high efficiency and savings. Less consumptions and lower running costs. Better for your business and for the environment.





Simple&Safe

Everything made easy.
Superior ergonomics, maximum
cleanability and operator safety
guaranteed.



High performance & reliability

Precise temperature control with
perfect heat uniformity. Highly
resistant construction
with impeccable finishing.



Full flexible modular cooking line made of:

- ▶ **Top units**
H=250
- ▶ **Stand alone units**
H=700 (body height 700 mm Hygienic)
- ▶ **Bases** (for installation of top units)
H=450 (for total body height including
top of 700 mm hygienic)

Units can be found in various installation Operating Side configurations:

- ▶ **Stand alone one side against the wall
operation** (control panel on one side
with backsplash on rear of the unit)

Units can be installed on:

- ▶ **Feet** (feet can be covered with optional
closing stainless steel covering plinths)
- ▶ **Stainless steel plinths** (200 mm height)
- ▶ **On site concrete** or stainless steel
plinths
- ▶ **Wall/cantilever** configurations with
optional factory supplied kit (verify with
factory possible configurations certain
units)

Electric Solid Tops



	588501	588502	588503
External dim. - mm			
Width	500	800	800
Depth	850	850	850
Height	250	250	250
Electric Power - kW	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	2	4	4
Ecotop	•		•
Wall hanging *	•	•	•

Electric Solid Tops - Freestanding



	588681	588682	588683
External dim. - mm			
Width	500	800	800
Depth	850	850	850
Height	700	700	700
Electric Power - kW	6	12	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	2	4	4
Open base	•	•	•
Ecotop	•		•

Electric Solid Tops on Warming Cabinet



	588704	588705	588706	588707
External dim. - mm				
Width	800	800	800	800
Depth	850	850	850	850
Height	700	700	700	700
Electric Power - kW	14.3	14.3	14.3	14.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	4	4	4	4
Hygienic class	H2	H2		
Ecotop		•		•

Electric Solid Tops on Oven



	588694	588695
External dim. - mm		
Width	800	800
Depth	850	850
Height	700	700
Electric Power - kW	17.3	17.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	4	4
Ecotop		•

Gas French Tops



	588504	588690	588684
External dim. - mm			
Width	800	800	800
Depth	850	850	850
Height	250	700	700
Gas Power - kW	10	17	10
Open base			•
Gas oven		•	
Wall hanging *	•		

Electric Warming Plate Tops



	588686	588557
External dim. - mm		
Width	600	1000
Depth	850	850
Height	250	250
Electric Power - kW	0.55	0.95
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz

Infradred Tops



	588505	588506
External dim. - mm		
Width	400	800
Depth	850	850
Height	250	250
Electric Power - kW	8	16
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	2	4
Wall hanging *	•	•

Pot detection optional as a factory fitted accessory

Induction Tops



	588508	588509
External dim. - mm		
Width	400	800
Depth	850	850
Height	250	250
Electric Power - kW	10	20
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	2	4
Wall hanging *	•	•

Induction Tops on Warming Cabinet



	588698	588703
External dim. - mm		
Width	800	800
Depth	850	850
Height	700	700
Electric Power - kW	22	22
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	4	4
Hygienic class		H2

Induction Tops on Oven



	588697
External dim. - mm	
Width	800
Depth	850
Height	700
Electric Power - kW	25
Electrical connection	400V 3N 50/60Hz
Zones	4

Induction Wok and Plates



	588511	588512
External dim. - mm		
Width	500	500
Depth	850	850
Height	250	250
Electric Power - kW	5	10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	1	2
Wok	1	1 - front
Plate		1 - back

Full Surface Induction Tops on Bases



	588660	588661	588662
External dim. - mm			
Width	1000	1000	1000
Depth	850	850	850
Height	700	700	700
Electric Power - kW	28	30	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	4	4	4
Open base	•		
Warming cabinet		•	
Base with doors			•

Full Surface Induction Tops on Bases - H2



	588514	588517	588518	588519
External dim. - mm				
Width	500	1000	1000	1000
Depth	850	850	850	850
Height	700	700	700	700
Electric Power - kW	14	28	30	28
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	2	4	4	4
Open base	H2	H2		
Warming cabinet			H2	
Base with doors				H2

Gas Burner Tops



	588523	588524
External dim. - mm		
Width	400	800
Depth	850	850
Height	250	250
Gas Power - kW	14	28
Burners	2	4
Wall hanging *	•	•

also available with 10 kW burners

Gas Burner Tops - Ecoflam



	588527	588528
External dim. - mm		
Width	400	800
Depth	850	850
Height	250	250
Gas Power - kW	14	28
Burners	2	4
Wall hanging *	•	•

also available with 10 kW burners

Gas Burner Tops on Gas Static Oven



	588691	588692
External dim. - mm		
Width	800	800
Depth	850	850
Height	700	700
Gas Power - kW	35	35
Ecoflam		•
Zones	4	4

also available with 10 kW burners

Electric Fry Tops - Chrome Plate



	588530	588534	588531	588535	588539
External dim. - mm					
Width	400	400	800	800	800
Depth	850	850	850	850	850
Height	250	250	250	250	250
Electric Power - kW	5.1	5.1	15.3	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•
Wall hanging *	•	•	•	•	•

Electric Fry Tops - Chrome Plate - freestanding



	588665	588669	588666	588670	588674
External dim. - mm					
Width	400	400	800	800	800
Depth	850	850	850	850	850
Height	700	700	700	700	700
Electric Power - kW	5.1	5.1	15.3	15.3	15.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•

* Wall hanging configuration available with additional accessory

Gas Fry Tops - Chrome Plate



	588532	588536	588533	588537	588541
External dim. - mm					
Width	400	400	800	800	800
Depth	850	850	850	850	850
Height	250	250	250	250	250
Gas Power - kW	10	10	20	20	20
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•
Wall hanging *	•	•	•	•	•

Gas Fry Tops - Chrome Plate - Freestanding



	588667	588671	588668	588672	588676
External dim. - mm					
Width	400	400	800	800	800
Depth	850	850	850	850	850
Height	700	700	700	700	700
Gas Power - kW	10	10	20	20	20
Smooth plate	•		•		
Ribbed plate		•		•	
Smooth/ribbed plate					•

Electric Free-Cooking Tops



	588549	588551	588677	588678
External dim. - mm				
Width	500	800	500	800
Depth	850	850	850	850
Height	250	250	700	700
Electric Power - kW	6	12	6	12
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Open base			•	•
Wall hanging *	•	•		

Electric Free-Cooking Tops on Warming Cabinet



	588708	588709
External dim. - mm		
Width	800	800
Depth	850	850
Height	700	700
Electric Power - kW	14.3	14.3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Zones	4	4
Hygienic class	H2	

Electric Free-Cooking Tops on Oven



	588696
External dim. - mm	
Width	800
Depth	850
Height	700
Electric Power - kW	17.3
Electrical connection	400V 3N 50/60Hz
Zones	4

Gas Chargrill Tops



	588618	588619
External dim. - mm		
Width	400	800
Depth	850	850
Height	250	250
Gas Power - kW	10.5	21
Wall hanging *	•	•

* Wall hanging configuration available with additional accessory

Electric Bain Marie Tops



	588552	588553
External dim. - mm		
Width	400	800
Depth	850	850
Height	250	250
Electric Power - kW	1.5	3
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Capacity	GN 1/1	GN 2/1
Wall hanging *	•	•

Electric Aquacooker - Freestanding



	588554
External dim. - mm	
Width	400
Depth	850
Height	700
Electric Power - kW	7.5
Electrical connection	400V 3N 50/60Hz
Wall hanging *	•

Electric Multi Braisers - Freestanding



	588612	588615
External dim. - mm		
Width	400	800
Depth	850	850
Height	700	700
Electric Power - kW	5	10.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz
Capacity	GN 1/1	GN 2/1
Wall hanging *	•	•

Pasta Cookers - Freestanding



	588624	588625	588626	588627
External dim. - mm				
Width	400	400	400	400
Depth	850	850	850	850
Height	700	700	700	700
Gas Power - kW			11.5	
Electric Power - kW	5	6		10
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz		400V 3N 50/60Hz
Tank capacity - lt	2x5	20	20	40
Wall hanging *		•	•	•

Deep Fat Fryers - Freestanding



	588629	588630	588685	588687	588631	588632
External dim. - mm						
Width	400	400	400	400	500	500
Depth	850	850	850	850	850	850
Height	700	700	700	700	700	700
Gas Power - kW				14		21
Electric Power - kW	5.4	12	10		18	
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz		400V 3N 50/60Hz	
Tank capacity - lt	7	2x5	14	14	23	23
Wall hanging *			•	•	•	•

Electric Chip Scuttle



	588556
External dim. - mm	
Width	400
Depth	850
Height	250
Electric Power - kW	1
Electrical connection	230V 1N 50/60Hz
Wall hanging *	•

Mixing Tap Units



	588710	588711
External dim. - mm		
Width	200	200
Depth	850	800
Height	250	250
Lever	•	
Knobs		•
Wall hanging *	•	•

Mixing Tap Units - Freestanding



	588558	588559	588597
External dim. - mm			
Width	200	200	200
Depth	850	850	850
Height	700	700	700
Electric Power - kW			0.1
Electrical connection			230V 1N 50/60Hz
Lever	•		
Knobs		•	
Automatic			•

Closed Work Tops - 100 to 500 mm



	588560	588561	588562	588563	588564
External dim. - mm					
Width	100	200	300	400	500
Depth	850	850	850	850	850
Height	250	250	250	250	250
Wall hanging *	•	•	•	•	•

Closed Work Tops - 600 to 1000 mm



	588565	588566	588567	588568	588569
External dim. - mm					
Width	600	700	800	900	1000
Depth	850	850	850	850	850
Height	250	250	250	250	250
Wall hanging *	•	•	•	•	•

Sink Unit - Freestanding



	588635
External dim. - mm	
Width	400
Depth	850
Height	700

Closed Bases



	588688	588689	588693
External dim. - mm			
Width	100	200	300
Depth	850	850	850
Height	450	450	450

Open Bases 400 - 800 mm



	588636	588641	588642	588679	588643
External dim. - mm					
Width	400	500	600	700	800
Depth	850	850	850	850	850
Height	450	450	450	450	450

Open Bases 900 - 1500 mm



	588637	588638	588639	588640
External dim. - mm				
Width	900	1000	1200	1500
Depth	850	850	850	850
Height	450	450	450	450

Cupboard Bases



	588644	588645	588646	588648	588647
External dim. - mm					
Width	400	500	600	800	1000
Depth	850	850	850	850	850
Height	450	450	450	450	450
Doors	1	1	1	2	2

Open Bases - H2 - 400 - 800 mm



	588572	588577	588578	588659	588579
External dim. - mm					
Width	400	500	600	700	800
Depth	850	850	850	850	850
Height	450	450	450	450	450

Open Bases - H2 - 900 - 1500 mm



	588573	588574	588575	588576
External dim. - mm				
Width	900	1000	1200	1500
Depth	850	850	850	850
Height	450	450	450	450

Cupboard Bases - H2



	588580	588581	588582	588584	588583
External dim. - mm					
Width	400	500	600	800	1000
Depth	850	850	850	850	850
Height	450	450	450	450	450
Doors	1	1	1	2	2

Electric Warming Cabinets



	588655	588656	588657	588658
External dim. - mm				
Width	500	600	800	1000
Depth	850	850	850	850
Height	450	450	450	450
Electric Power - kW	1	1	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Doors	1	1	2	2

Not for installation below induction, ecotop, solid top and freecooking top units

Electric Warming Cabinets - H2



	588651	588652	588653	588654
External dim. - mm				
Width	500	600	800	1000
Depth	850	850	850	850
Height	450	450	450	450
Electric Power - kW	1	1	2	2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Doors	1	1	2	2

Not for installation below induction, ecotop, solid top and freecooking top units

Holding Cabinet Base (GN Conform)



	588649
External dim. - mm	
Width	800
Depth	850
Height	450
Electric Power - kW	1
Electrical connection	230V 1N 50Hz
Drawers (2)	•

Electric Static Oven Base



	588587
External dim. - mm	
Width	800
Depth	850
Height	450
Electric Power - kW	5
Electrical connection	400V 3N 50/60Hz

Not for installation below induction, ecotop, solid top and freecooking top units

Ref-freezer Bases R290



	588718	588719
External dim. - mm		
Width	1000	1200
Depth	850	850
Height	550	550
Electric Power - kW	0,67	0,76
Electrical connection	230V 1N 50Hz	230V 1N 50Hz
Operating side	1 side	1 side
Temperature range	+8/-22 °C	+8/-22 °C
Connectivity	•	•



Excellence is central to everything we do.
By anticipating our customers' needs, we strive for
Excellence with our people, innovations, solutions and services.
To be the OnE making our customers' work-life easier,
more profitable - and truly sustainable every day.

Follow us on



www.electroluxprofessional.com

Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated - the environmental needs of our customers in mind
- ▶ Our technology is ROHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

