



## Range Overview

### ProThermetic Boiling Pans



# Contents

## Tilting Boiling Pans / Kettles

Electric - 60 L	6
Electric - 60 and 100 L	6
Electric - 150 and 200 L	6
Electric - 300 and 400 L	7
Electric - Stirrer - 60 and 100 L	7
Electric - Stirrer - 150 and 200 L	7
Electric - Stirrer - 300 and 400 L	8
Electric - Variable Speed Stirrer - 150, 200 and 300 L	8
Gas - 60 and 100 L	9
Gas - 150 and 300 L	9
Steam - 60 L	10
Steam - 100 L	10
Steam - 150 L	10
Steam - 200 L	11
Steam - 300 L	11
Steam - 400 L	11
Steam - Stirrer - 60, 100 and 150 L	12
Steam - Stirrer - 200, 300 and 400 L	12
Steam - Variable Speed Stirrer - 150, 200 and 300 L	12

## Stationary Round Boiling Pans/ Kettles

Electric - 60 L - 800 mm and 850 mm Depth	13
Electric - 60 L - 900 mm Depth	13
Electric - 100 L - 800 mm and 850 mm Depth	14
Electric - 100 L - 900 mm Depth	14
Electric - 150 L - 850 mm and 900 mm Depth	14
Steam - 60 L, 100 L and 150 L - 850 mm and 900 mm Depth	15

## Stationary Rectangular Boiling Pans / Kettles

Electric - 80 L - 800 mm and 850 mm Depth	16
Electric - 80 L - 900 mm Depth	16
Electric - 200 L - 800 mm and 850 mm Depth	16
Electric - 200 L - 900 mm Depth	17
Electric - 300 L - 800 mm and 850 mm Depth	17
Electric - 300 L - 900 mm Depth	17
Electric - 400 L - 800 mm and 850 mm Depth	18
Electric - 400 L - 900 mm Depth	18

# Performance and Versatility

The ProThermetic range offers the best solution for high productivity kitchens: central kitchens and airport catering, hospitals, big hotels and restaurants.

An extensive range of product typologies offering tilting or stationary Boiling pans in different sizes, with different features and many possible configurations.



## Durable and Reliable

The *thermale* boiling pans deliver outstanding results **also in the toughest conditions**

- ▶ Internal surface of the vessel is in DIN 1.4404 AISI 316L for greater resistance even with acid products
- ▶ Heavy duty cooking well, deep cast in 1 piece (3 mm thick)



## Top performances

- ▶ **Perfect boiling** with the highest uniformity thanks to the indirect heating system with guaranteed cooking quality without sticking.
- ▶ Thanks to the indirect heating system with steam at 1.5 bar (125°C) pressure, heating times are reduced automatically.
- ▶ The design of the pan ensures ideal heat distribution as well as an easy stirring process and the possibility to prepare small food quantities.



## ProThermetic Tilting units are available in different body height configurations:

- ▶ **H=700** (body height 700 mm Hygienic)
- ▶ **H=800** (body height 800 mm)
- ▶ **H=400** (body height 400 mm for cantilever/wall mounted type installations)

### Units can be installed on:

- ▶ **Feet** (feet can be covered with optional closing stainless steel covering plinths)
- ▶ **Stainless steel plinths** (100 mm or 200 mm height depending on body height)
- ▶ **On site concrete** or stainless steel plinths
- ▶ **Wall/cantilever** configurations (for 400 mm body height units)
- ▶ **Touch screen** LED technology
- ▶ **USB** connection
- ▶ Step-by-step cooking process with programming of up to **15 cooking phases**
- ▶ **IPX6** water protection (for electric, gas and steam-heated appliances)
- ▶ Chassis, supporting frame and structure made of **stainless steel** (18/10)

## ProThermetic Stationary units are available in different body height configurations:

- ▶ **H=700** (body height 700 mm Hygienic)
- ▶ **H=800** (body height 800 mm)

### Units can be installed on:

- ▶ **Feet** (feet can be covered with optional closing stainless steel covering plinths)
- ▶ **Stainless steel plinths** (100 mm or 200 mm height depending on body height)
- ▶ **On site concrete** or stainless steel plinths
- ▶ **Wall/cantilever** configurations with optional factory supplied kit
- ▶ **Touch screen** LED technology
- ▶ **USB** connection
- ▶ Step-by-step cooking process with programming of up to **15 cooking phases**
- ▶ **IPX6** water protection (for electric, gas and steam-heated appliances)
- ▶ Chassis, supporting frame and structure made of **stainless steel** (18/10)



\* TÜV certificated appliances meet the requirements of the Directive 97/23/EC in terms of Safety of Pressure Vessels



## High Versatility

### The Chef's best friend

Ideal for any **creamy preparations** such as hummus, sauces, soups, purées and mashed vegetables.

### Easy mixing and stirring

Boiling pans are equipped with a stirrer offering the possibility of three stirring cycles: one direction, two directions with 4-second pause, two directions with 16-second pause.

### Flexible and high performing

- ▶ Variable from 20rpms up to 100 rpms
- ▶ Control of speed via touch panel
- ▶ Specific stirrer for mashed potatoes
- ▶ Variable speed stirrer 3,8 kW at 100 rpms (standard is 0,4 kW)

## Tilting Boiling Pans / Kettles

Electric - 60 L



	<b>586000</b> PBOT06EAE0	<b>586001</b> PBOT06EEEO	<b>586002</b> PBOT06ETEO	<b>586122</b> PBOT06EBEO	<b>586123</b> PBOT06EUEO
External dim. - mm					
width	1100	1100	1100	1100	1100
<b>depth</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>850</b>	<b>850</b>
height without plinth	700	800	400	700	400
overall height (lid open)	1658	1658	1658	1658	1658
overall depth (tilting movement)	980	980	980	980	980
Well capacity - L	60	60	60	60	60
Electric power - kW	12.2	12.2	12.2	12.2	12.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•			•	
Wall Mounted			•		•

## Tilting Boiling Pans / Kettles

Electric - 60 and 100 L



	<b>586003</b> PBOT06ECE0	<b>586004</b> PBOT06EGEO	<b>586005</b> PBOT06EVEO	<b>586006</b> PBOT10ECE0	<b>586007</b> PBOT10EGEO	<b>586008</b> PBOT10EVEO
External dim. - mm						
width	1100	1100	1100	1200	1200	1200
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	1756	1756	1756	1756	1756	1756
overall depth (tilting movement)	1073	1073	1073	1124	1124	1124
Well capacity - L	60	60	60	100	100	100
Electric power - kW	12.2	12.2	12.2	18.2	18.2	18.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

## Tilting Boiling Pans / Kettles

Electric - 150 and 200 L



	<b>586009</b> PBOT15ECE0	<b>586010</b> PBOT15EGEO	<b>586011</b> PBOT15EVEO	<b>586012</b> PBOT20EDE0	<b>586013</b> PBOT20EHE0	<b>586014</b> PBOT20EWE0
External dim. - mm						
width	1300	1300	1300	1400	1400	1400
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	1845	1845	1845	2047	2047	2047
overall depth (tilting movement)	1165	1165	1165	1335	1335	1335
Well capacity - L	150	150	150	200	200	200
Electric power - kW	24.2	24.2	24.2	30.2	30.2	30.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

## Tilting Boiling Pans / Kettles

Electric - 300 and 400 L



	<b>586015</b> PBOT30EDEO	<b>586016</b> PBOT30EHEO	<b>586017</b> PBOT30EWE0	<b>586018</b> PBOT40EDEO	<b>586019</b> PBOT40EHEO	<b>586883</b> PBOT40EWE0
External dim. - mm						
width	1500	1500	1500	1500	1500	1500
<b>depth</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	2069	2069	2069	2214	2214	2214
overall depth (tilting movement)	1360	1360	1360	1447	1447	1447
Well capacity - L	300	300	300	400	400	400
Electric power - kW	36.2	36.2	36.2	48.2	48.2	48.2
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

## Tilting Boiling Pans / Kettles

Electric - Stirrer\* - 60 and 100 L



	<b>586022</b> PBOT06RCEO	<b>586023</b> PBOT06RGE0	<b>586024</b> PBOT06RVE0	<b>586025</b> PBOT10RCEO	<b>586026</b> PBOT10RGE0	<b>586027</b> PBOT10RVE0
External dim. - mm						
width	1100	1100	1100	1200	1200	1200
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	1756	1756	1756	1756	1756	1756
overall depth (tilting movement)	1073	1073	1073	1124	1124	1124
Well capacity - L	60	60	60	100	100	100
Electric power - kW	12.5	12.5	12.5	18.5	18.5	18.5
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

\* Stirrer not included and to be ordered separately

## Tilting Boiling Pans / Kettles

Electric - Stirrer\* - 150 and 200 L



	<b>586028</b> PBOT15RCEO	<b>586029</b> PBOT15RGE0	<b>586030</b> PBOT15RVE0	<b>586031</b> PBOT20RDE0	<b>586032</b> PBOT20RHE0	<b>586033</b> PBOT20RWE0
External dim. - mm						
width	1300	1300	1300	1400	1400	1400
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	1845	1845	1845	2047	2047	2047
overall depth (tilting movement)	1165	1165	1165	1325	1325	1325
Well capacity - L	150	150	150	200	200	200
Electric power - kW	24.6	24.6	24.6	30.6	30.6	30.6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

\* Stirrer not included and to be ordered separately

## Tilting Boiling Pans / Kettles

Electric - Stirrer\* - 300 and 400 L



	<b>586034</b> PBOT30RDEO	<b>586035</b> PBOT30RHEO	<b>586036</b> PBOT30RWEO	<b>586037</b> PBOT40RDEO	<b>586038</b> PBOT40RHEO	<b>586884</b> PBOT40RWEO
External dim. - mm						
width	1500	1500	1500	1500	1500	1500
<b>depth</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	2069	2069	2069	2214	2214	2214
overall depth (tilting movement)	1360	1360	1360	1447	1447	1447
Well capacity - L	300	300	300	400	400	400
Electric power - kW	36.6	36.6	36.6	48.6	48.6	48.6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

\* Stirrer not included and to be ordered separately

## Tilting Boiling Pans / Kettles

Electric - Variable Speed Stirrer\* - 150, 200 and 300 L



	<b>586887</b> PBOT15WCEO	<b>586888</b> PBOT15WGEO	<b>586889</b> PBOT20WDEO	<b>586890</b> PBOT20WHEO	<b>586891</b> PBOT30WDEO	<b>586892</b> PBOT30WHEO
External dim. - mm						
width	1300	1300	1400	1400	1500	1500
<b>depth</b>	<b>900</b>	<b>900</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	700	800	700	800
overall height (lid open)	1845	1845	2047	2047	2069	2069
overall depth (tilting movement)	1165	1165	1325	1325	1360	1360
Well capacity - L	150	150	200	200	300	300
Electric power - kW	28	28	34	34	40	40
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•		•		•	

\* Stirrer not included and to be ordered separately



## Tilting Boiling Pans / Kettles

Gas - 60 and 100 L



	<b>586106</b> PBOT06GCCO	<b>586107</b> PBOT06GGCO	<b>586108</b> PBOT06GVCO	<b>586109</b> PBOT10GCCO	<b>586110</b> PBOT10GGCO	<b>586111</b> PBOT10GVCO
External dim. - mm						
width	1100	1100	1100	1200	1200	1200
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	1756	1756	1756	1756	1756	1756
overall depth (tilting movement)	1073	1073	1073	1124	1124	1124
Well capacity - L	60	60	60	100	100	100
Gas Power - kW	15	15	15	21	21	21
Electric power - kW	0.25	0.25	0.25	0.25	0.25	0.25
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

## Tilting Boiling Pans / Kettles

Gas - 150 and 300 L



	<b>586112</b> PBOT15GDCCO	<b>586113</b> PBOT15GHCO	<b>586114</b> PBOT15GVCO	<b>586115</b> PBOT30GDCCO	<b>586116</b> PBOT30GHCO	<b>586117</b> PBOT30GVCO
External dim. - mm						
width	1300	1300	1300	1500	1500	1500
<b>depth</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	1845	1845	1845	2069	2069	2069
overall depth (tilting movement)	1165	1165	1165	1360	1360	1360
Well capacity - L	150	150	150	300	300	300
Gas Power - kW	27	27	27	45	45	45
Electric power - kW	0.25	0.25	0.25	0.25	0.25	0.25
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Hygienic plinth	•			•		
Wall Mounted			•			•

## Tilting Boiling Pans / Kettles

Steam - 60 L



	<b>586045</b> PBOT06SCCO	<b>586046</b> PBOT06SGCO	<b>586047</b> PBOT06SVCO	<b>586048</b> PBOT06TCCO	<b>586050</b> PBOT06TVCO
External dim. - mm					
width	1100	1100	1100	1100	1100
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height without plinth	700	800	400	700	400
overall height (lid open)	1756	1756	1756	1756	1756
overall depth (tilting movement)	1073	1073	1073	1073	1073
Well capacity - L	60	60	60	60	60
Steam consumption - kg/h	34	34	34	34	34
Electric power - kW	0.2	0.2	0.2	0.2	0.2
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Manual control valve				•	•
Hygienic plinth	•			•	
Wall Mounted			•		•

## Tilting Boiling Pans / Kettles

Steam - 100 L



	<b>586051</b> PBOT10SCCO	<b>586052</b> PBOT10SGCO	<b>586053</b> PBOT10SVCO	<b>586054</b> PBOT10TCCO	<b>586056</b> PBOT10TVCO
External dim. - mm					
width	1200	1200	1200	1200	1200
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height without plinth	700	800	400	700	400
overall height (lid open)	1756	1756	1756	1756	1756
overall depth (tilting movement)	1124	1124	1124	1124	1124
Well capacity - L	100	100	100	100	100
Steam consumption - kg/h	46	46	46	46	46
Electric power - kW	0.2	0.2	0.2	0.2	0.2
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Manual control valve				•	•
Hygienic plinth	•			•	
Wall Mounted			•		•

## Tilting Boiling Pans / Kettles

Steam - 150 L



	<b>586057</b> PBOT15SCCO	<b>586058</b> PBOT15SGCO	<b>586059</b> PBOT15SVCO	<b>586060</b> PBOT15TCCO	<b>586061</b> PBOT15TGCO	<b>586062</b> PBOT15TVCO
External dim. - mm						
width	1300	1300	1300	1300	1300	1300
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height without plinth	700	800	400	700	800	400
overall height (lid open)	1845	1845	1845	1845	1845	1845
overall depth (tilting movement)	1165	1165	1165	1165	1165	1165
Well capacity - L	150	150	150	150	150	150
Steam consumption - kg/h	63	63	63	63	63	63
Electric power - kW	0.2	0.2	0.2	0.2	0.2	0.2
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Manual control valve				•	•	•
Hygienic plinth	•			•		
Wall Mounted			•			•

## Tilting Boiling Pans / Kettles

Steam - 200 L



	<b>586063</b> PBOT20SDCO	<b>586064</b> PBOT20SHCO	<b>586065</b> PBOT20SWCO	<b>586066</b> PBOT20TDCO	<b>586067</b> PBOT20THCO
External dim. - mm					
width	1400	1400	1400	1400	1400
<b>depth</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	400	700	800
overall height (lid open)	2047	2047	2047	2047	2047
overall depth (tilting movement)	1335	1335	1335	1335	1335
Well capacity - L	200	200	200	200	200
Steam consumption - kg/h	78	78	78	78	78
Electric power - kW	0.2	0.2	0.2	0.2	0.2
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Manual control valve				•	•
Hygienic plinth	•			•	
Wall Mounted			•		

## Tilting Boiling Pans / Kettles

Steam - 300 L



	<b>586069</b> PBOT30SDCO	<b>586070</b> PBOT30SHCO	<b>586071</b> PBOT30SWCO	<b>586072</b> PBOT30TDCO	<b>586073</b> PBOT30THCO
External dim. - mm					
width	1500	1500	1500	1500	1500
<b>depth</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	400	700	800
overall height (lid open)	2069	2069	2069	2069	2069
overall depth (tilting movement)	1360	1360	1360	1360	1360
Well capacity - L	300	300	300	300	300
Steam consumption - kg/h	101	101	101	101	101
Electric power - kW	0.2	0.2	0.2	0.2	0.2
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Manual control valve				•	•
Hygienic plinth	•			•	
Wall Mounted			•		

## Tilting Boiling Pans / Kettles

Steam - 400 L



	<b>586075</b> PBOT40SDCO	<b>586076</b> PBOT40SHCO	<b>586077</b> PBOT40TDCO	<b>586078</b> PBOT40THCO
External dim. - mm				
width	1500	1500	1500	1500
<b>depth</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	700	800
overall height (lid open)	2214	2214	2214	2214
overall depth (tilting movement)	1447	1447	1447	1447
Well capacity - L	400	400	400	400
Steam consumption - kg/h	118	118	118	118
Electric power - kW	0.2	0.2	0.2	0.2
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Manual control valve			•	•
Hygienic plinth	•		•	

## Tilting Boiling Pans / Kettles

Steam - Stirrer\* - 60, 100 and 150 L



	<b>586083</b> PBOT06QCEO	<b>586086</b> PBOT10QCEO	<b>586087</b> PBOT10QGEO	<b>586089</b> PBOT15QCEO	<b>586090</b> PBOT15QGEO
External dim. - mm					
width	1100	1200	1200	1300	1300
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height without plinth	700	700	800	700	800
overall height (lid open)	1756	1756	1756	1845	1845
overall depth (tilting movement)	1073	1124	1124	1165	1165
Well capacity - L	60	100	100	150	150
Steam consumption - kg/h	34	46	46	63	63
Electric power - kW	0.5	0.6	0.6	0.6	0.6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•	•		•	

\* Stirrer not included and to be ordered separately

## Tilting Boiling Pans / Kettles

Steam - Stirrer\* - 200, 300 and 400 L



	<b>586092</b> PBOT20QDEO	<b>586093</b> PBOT20QHEO	<b>586095</b> PBOT30QDEO	<b>586096</b> PBOT30QHEO	<b>586099</b> PBOT40QHEO
External dim. - mm					
width	1400	1400	1500	1500	1500
<b>depth</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	700	800	800
overall height (lid open)	2047	2047	2069	2069	2214
overall depth (tilting movement)	1335	1335	1360	1360	1447
Well capacity - L	200	200	300	300	400
Steam consumption - kg/h	78	78	101	101	118
Electric power - kW	0.6	0.6	0.6	0.6	0.6
Electrical connection	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz	400V 3N 50/60Hz
Hygienic plinth	•		•		

\* Stirrer not included and to be ordered separately

## Tilting Boiling Pans / Kettles

Steam - Variable Speed Stirrer\* - 150, 200 and 300 L



	<b>586895</b> PBOT15VCEO	<b>586896</b> PBOT15VGEO	<b>586897</b> PBOT20VDEO	<b>586898</b> PBOT20VHEO	<b>586899</b> PBOT30VDEO	<b>586900</b> PBOT30VHEO
External dim. - mm						
width	1300	1300	1400	1400	1500	1500
<b>depth</b>	<b>900</b>	<b>900</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>	<b>1000</b>
height without plinth	700	800	700	800	700	800
overall height (lid open)	1845	1845	2047	2047	2069	2069
overall depth (tilting movement)	1165	1165	1335	1335	1360	1360
Well capacity - L	150	150	200	200	300	300
Steam consumption - kg/h	65	65	85	85	105	105
Electric power - kW	4	4	4	4	4	4
Electrical connection	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz	230V 1N 50/60Hz
Hygienic plinth	•		•		•	

\* Stirrer included



## \* Stationary Round Boiling Pans / Kettles

Electric - 60 L - H 700 and H 800 - 800 mm and 850 mm Depth



	<b>586301</b> PBON06EAEM	<b>586305</b> PBON06EJEM	<b>586329</b> PBON06EMEM	<b>586325</b> PBON06EEEM	<b>586313</b> PBON06EKEM
External dim. - mm					
width	700	700	700	700	700
<b>depth</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>850</b>
height	700	700	800	800	700
overall height (lid open)	1556	1556	1556	1556	1556
Well capacity - L	60	60	60	60	60
Electric power - kW	12.2	12.2	12.2	12.2	12.2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap	•	•	•	•	•
Backsplash		•	•		•
Hygienic plinth	•	•			•
Wall mounted		•	•		•



## \* Stationary Round Boiling Pans / Kettles

Electric - 60 L - H 700 and H 800 - 900 mm Depth



	<b>586317</b> PBON06ECEM	<b>586321</b> PBON06ELEM	<b>586333</b> PBON06EGEM	<b>586337</b> PBON06EPEM
External dim. - mm				
width	700	700	700	700
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	700	800	800
overall height (lid open)	1547	1547	1547	1547
Well capacity - L	60	60	60	60
Electric power - kW	12.2	12.2	12.2	12.2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap	•	•	•	•
Backsplash		•		•
Hygienic plinth	•	•		
Wall mounted		•		•



### \* Stationary Round Boiling Pans / Kettles

Electric - 100 L - H 700 and H 800 - 800 mm and 850 mm Depth



	<b>586341</b> PBON10EAEM	<b>586345</b> PBON10EJEM	<b>586365</b> PBON10EEEM	<b>586369</b> PBON10EMEM	<b>586353</b> PBON10EKEM
External dim. - mm					
width	800	800	800	800	800
<b>depth</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>850</b>
height	700	700	800	800	700
overall height (lid open)	1647	1647	1647	1647	1647
Well capacity - L	100	100	100	100	100
Electric power - kW	18.2	18.2	18.2	18.2	18.2
Electrical connection	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz
Mixing tap	•	•	•	•	•
Backsplash		•		•	•
Hygienic plinth	•	•			•
Wall mounted		•		•	•



### \* Stationary Round Boiling Pans / Kettles

Electric - 100 L - H 700 and H 800 - 900 mm Depth



	<b>586357</b> PBON10ECEM	<b>586361</b> PBON10ELEM	<b>586373</b> PBON10EGEM	<b>586377</b> PBON10EPEM
External dim. - mm				
width	800	800	800	800
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	700	800	800
overall height (lid open)	1634	1634	1634	1634
Well capacity - L	100	100	100	100
Electric power - kW	18.2	18.2	18.2	18.2
Electrical connection	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz
Mixing tap	•	•	•	•
Backsplash		•		•
Hygienic plinth	•	•		
Wall mounted		•		•



### \* Stationary Round Boiling Pans / Kettles

Electric - 150 L - H 700 and H 800- 850 mm and 900 mm Depth



	<b>586385</b> PBON15EKEM	<b>586393</b> PBON15ELEM	<b>586389</b> PBON15ECEM	<b>586397</b> PBON15EGEM	<b>586401</b> PBON15EPEM
External dim. - mm					
width	900	900	900	900	900
<b>depth</b>	<b>850</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	700	700	800	800
overall height (lid open)	1701	1688	1688	1688	1688
Well capacity - L	150	150	150	150	150
Electric power - kW	24.2	24.2	24.2	24.2	24.2
Electrical connection	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz	400V 3N-50/60 Hz
Mixing tap	•	•	•	•	•
Backsplash	•	•			•
Hygienic plinth	•	•	•		
Wall mounted	•	•			•



## \* Stationary Round Boiling Pans / Kettles

Steam - 60 L, 100 L and 150 L - H 700 and H 800 - 850 mm and 900 mm Depth



	<b>586417</b> PBON06SKCM	<b>586481</b> PBON10SPCM	<b>586497</b> PBON15SLCM	<b>586505</b> PBON15SPCM
External dim. - mm				
width	700	800	800	900
<b>depth</b>	<b>850</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	800	700	800
overall height (lid open)	1556	1634	1688	1688
Well capacity - L	60	100	150	150
Steam consumption - kg/h	60	80	100	100
Electric power - kW	0.3	0.3	0.3	0.3
Electrical connection	230V 1N- 50/60 Hz	230V 1N- 50/60 Hz	230V 1N- 50/60 Hz	230V 1N- 50/60 Hz
Mixing tap	•	•	•	•
Backsplash	•	•	•	•
Hygienic plinth	•		•	
Wall mounted	•	•	•	•

## Stationary Rectangular Boiling Pans / Kettles

Electric - 80 L - H 700 and H 800 - 800 mm and 850 mm Depth



	<b>586509</b> PBEN08EAEM	<b>586511</b> PBEN08EJEM	<b>586523</b> PBEN08EMEM	<b>586521</b> PBEN08EEEM	<b>586515</b> PBEN08EKEM
External dim. - mm					
width	700	700	700	700	700
<b>depth</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>850</b>
height	700	700	800	800	700
overall height (lid open)	1731	1731	1731	1731	1731
Well capacity - L	80	80	80	80	80
Electric power - kW	18.2	18.2	18.2	18.2	18.2
Electrical connection	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz
Mixing tap	•	•	•	•	•
Backsplash		•	•		•
Hygienic plinth	•	•			•
Wall mounted		•	•		•

## Stationary Rectangular Boiling Pans / Kettles

Electric - 80 L - H 700 and H 800 - 900 mm Depth



	<b>586517</b> PBEN08ECEM	<b>586519</b> PBEN08ELEM	<b>586525</b> PBEN08EGEM	<b>586527</b> PBEN08EPEM
External dim. - mm				
width	700	700	700	700
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	700	800	800
overall height (lid open)	1718	1718	1718	1718
Well capacity - L	80	80	80	80
Electric power - kW	18.2	18.2	18.2	18.2
Electrical connection	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz
Mixing tap	•	•	•	•
Backsplash		•		•
Hygienic plinth	•	•		
Wall mounted		•		•

## Stationary Rectangular Boiling Pans / Kettles

Electric - 200 L - H 700 and H 800 - 800 mm and 850 mm Depth



	<b>586529</b> PBEN20EAEM	<b>586543</b> PBEN20EMEM	<b>586535</b> PBEN20EKEM
External dim. - mm			
width	1000	1000	1000
<b>depth</b>	<b>800</b>	<b>800</b>	<b>850</b>
height	700	800	700
overall height (lid open)	1730	1730	1730
Well capacity - L	200	200	200
Electric power - kW	30.2	30.2	30.2
Electrical connection	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz
Mixing tap	•	•	•
Backsplash		•	•
Hygienic plinth	•		•
Wall mounted		•	•



## Stationary Rectangular Boiling Pans / Kettles

Electric - 200 L - H 700 and H 800 - 900 mm Depth



	<b>586539</b> PBEN20ELEM	<b>586545</b> PBEN20EGEM	<b>586537</b> PBEN20ECEM	<b>586547</b> PBEN20EPEM
External dim. - mm				
width	1000	1000	1000	1000
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	800	700	800
overall height (lid open)	1717	1717	1717	1717
Well capacity - L	200	200	200	200
Electric power - kW	30.2	30.2	30.2	30.2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap	•	•	•	•
Backsplash	•			•
Hygienic plinth	•		•	
Wall mounted	•			•

## Stationary Rectangular Boiling Pans / Kettles

Electric - 300 L - H 700 and H 800 - 800 mm and 850 mm Depth



	<b>586549</b> PBEN30EAEM	<b>586551</b> PBEN30EJEM	<b>586561</b> PBEN30EEEM	<b>586563</b> PBEN30EMEM	<b>586555</b> PBEN30EKEM
External dim. - mm					
width	1400	1400	1400	1400	1400
<b>depth</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>850</b>
height	700	700	800	800	700
overall height (lid open)	1731	1731	1731	1731	1731
Well capacity - L	300	300	300	300	300
Electric power - kW	36.2	36.2	36.2	36.2	36.2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap	•	•	•	•	•
Backsplash		•		•	•
Hygienic plinth	•	•			•
Wall mounted		•		•	•

## Stationary Rectangular Boiling Pans / Kettles

Electric - 300 L - H 700 and H 800 - 900 mm Depth



	<b>586557</b> PBEN30ECEM	<b>586559</b> PBEN30ELEM	<b>586565</b> PBEN30EGEM	<b>586567</b> PBEN30EPEM
External dim. - mm				
width	1400	1400	1400	1400
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	700	800	800
overall height (lid open)	1718	1718	1718	1718
Well capacity - L	300	300	300	300
Electric power - kW	36.2	36.2	36.2	36.2
Electrical connection	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz	400V 3N~ 50/60 Hz
Mixing tap	•	•	•	•
Backsplash		•		•
Hygienic plinth	•	•		
Wall mounted		•		•

## Stationary Rectangular Boiling Pans / Kettles

Electric - 400 L - H 700 and H 800 - 800 mm and 850 mm Depth



	<b>586569</b> PBEN40EAEM	<b>586571</b> PBEN40EJEM	<b>586581</b> PBEN40EEEM	<b>586583</b> PBEN40EMEM	<b>586575</b> PBEN40EKEM
External dim. - mm					
width	1700	1700	1700	1700	1700
<b>depth</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>800</b>	<b>850</b>
height	700	700	800	800	700
overall height (lid open)	1731	1731	1731	1731	1731
Well capacity - L	400	400	400	400	400
Electric power - kW	48.2	48.2	48.2	48.2	48.2
Electrical connection	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz
Mixing tap	•	•	•	•	•
Backsplash				•	•
Hygienic plinth	•	•			•
Wall mounted		•		•	•

## Stationary Rectangular Boiling Pans / Kettles

Electric - 400 L - H 700 and H 800 - 900 mm Depth



	<b>586577</b> PBEN40ECEM	<b>586579</b> PBEN40ELEM	<b>586585</b> PBEN40EGEM	<b>586587</b> PBEN40EPEM
External dim. - mm				
width	1700	1700	1700	1700
<b>depth</b>	<b>900</b>	<b>900</b>	<b>900</b>	<b>900</b>
height	700	700	800	800
overall height (lid open)	1082	1082	1082	1082
Well capacity - L	400	400	400	400
Electric power - kW	48.2	48.2	48.2	48.2
Electrical connection	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz	400V 3N- 50/60 Hz
Mixing tap	•	•	•	•
Backsplash		•		•
Hygienic plinth	•	•		
Wall mounted		•		•





Excellence is central to everything we do.  
By anticipating our customers' needs, we strive for  
Excellence with our people, innovations, solutions and services.  
To be the OnE making our customers' work-life easier,  
more profitable – and truly sustainable every day.

Follow us on



[www.electroluxprofessional.com](http://www.electroluxprofessional.com)

## Excellence with the environment in mind

- ▶ All our factories are ISO 14001-certified
- ▶ All our solutions are designed for low consumption of water, energy, detergents and harmful emissions
- ▶ In recent years over 70% of our product features have been updated - the environmental needs of our customers in mind
- ▶ Our technology is ROHS and REACH compliant and over 95% recyclable
- ▶ Our products are 100% quality tested by experts

